

```
# Set some options.
Options -Indexes
Options +FollowSymLinks

# Customized error messages.
ErrorDocument 503 /maintenance/index.html

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings
php_flag ignore_user_abort on
php_flag magic_quotes_gpc off
php_flag register_globals off

# hash_bits_per_character default is 5.
# Higher values create shorter session ids.
# With hash_function 1, 5 bits: 32 chars, 6 bits: 27 chars
php_value session.hash_bits_per_character 6
php_flag session.auto_start off
php_flag session.cookie_httponly on
php_value session.hash_function 1

# add mime types for fonts
# see: http://linz.id.au/2011/02/08/setting-http-headers-on-css-fonts-for-great-justice-and-performance
# except for woff, which has a new mimetype
AddType application/vnd.ms-fontobject .eot
AddType font/ttf .ttf
AddType font/opentype .otf
AddType image/svg+xml .svg
AddType application/font-woff .woff

# Make static resources cacheable, html not cached (can be overridden by php if you set
# both the Cache-Control and Expires headers)
<IfModule mod_expires.c>
    # ExpiresByType sets both the (old) Expires header and the new cache-control header
    ExpiresActive On
    ExpiresByType text/html "now"
    ExpiresByType text/javascript "access plus 1 week"
    ExpiresByType application/javascript "access plus 1 week"
```

```

ExpiresByType application/javascript access plus 1 week
ExpiresByType text/css "access plus 1 week"
ExpiresByType application/font-woff "access plus 1 year"
ExpiresByType image/svg+xml "access plus 1 year"

# we use force_unique on file uploads, so new versions of the file have -1, -2, etc
# for other stuff, if you need to force a reload, append a version get parameter
ExpiresByType image/jpeg "access plus 1 week"
ExpiresByType image/gif "access plus 1 week"
ExpiresByType image/png "access plus 1 week"
ExpiresByType image/webp "access plus 1 week"

# Set Cache-Control public for things that don't need to be confidential
SetEnvIfNoCase Request_URI \.(?:gif|jpe?g|png|webp|woff|css|js)$ static_content
Header append Cache-Control public env=static_content

# 500 errors aren't cacheable
Header set Cache-Control "no-store, no-cache, must-revalidate, post-check=0, pre-
check=0" "expr=%{(REQUEST_STATUS) -ge 500 && %(REQUEST_STATUS) -lt 600"
</IfModule>

# Various rewrite rules.
RewriteEngine on

# Block access to hidden files that can reveal other files/info about the system
# git
RewriteRule \.git/ - [forbidden,last]
RewriteRule \.gitignore$ - [forbidden,last]

# Macs create these
RewriteRule __MACOSX$ - [nocase,forbidden,last]
RewriteRule \.DS_Store$ - [nocase,forbidden,last]
RewriteRule \.FBIIndex$ - [nocase,forbidden,last]
# Windows creates these
RewriteRule Thumbs\..db$ - [nocase,forbidden,last]

# javascript
RewriteCond %(REQUEST_URI) ^/v-. */
RewriteRule ^v-. */(.*)$ /$1 [last]

# Remove trailing slashes ????
```

```
RewriteCond %{REQUEST_METHOD} =GET [nocase]  
RewriteRule ^(.*)/$ /$1 [last,redirect=301]
```

If the request is not for an existing file or directory ...

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

forward the request to index.php

```
RewriteRule ^ index.php [last]
```