

```

# Protect files and directories from prying eyes.
<FilesMatch "\.(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl|\.(php|
|xml|tpl)<(\.|sw[op]|\.bak|\.orig|\.save)?
$|^(\.|_|!|Entries|Repository|Root|Tag|Template)$|^#.*$|\.(php<(\.|sw[op]|\.bak|\.orig|\.save
    Order allow,deny
</FilesMatch>

# Allow cross domain requests
<IfModule mod_headers.c>
    Header add Access-Control-Allow-Origin "*"
</IfModule>

# Force Internet Explorer 8/9/10 to render pages in the highest mode
# available in the various cases when it may not.
<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"

# `mod_headers` cannot match based on the content-type, however,
# the `X-UA-Compatible` response header should be send only for
# HTML documents and not for the other resources.
<FilesMatch "\.(appcache|atom|bbaw|bmp|crx|css|curl|eot|f4[abpv]|flv|geojson|gif|htc|ico|j|
|gl|j|json|ld)?|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz|
|swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|webmanifest|woff2?|xloc|xsl|xpi)$">
    Header unset X-UA-Compatible
</FilesMatch>
</IfModule>

# Serve resources with the proper media types (f. k. a. MIME types).
<IfModule mod_mime.c>
    # Data interchange
    AddType application/atom+xml          atom
    AddType application/json              json map topojson
    AddType application/ld+json           jsonld
    AddType application/rss+xml           rss
    AddType application/vnd.geo+json      geojson
    AddType application/xml               rdf xml

    # JavaScript
    AddType application/javascript         js

    # Manifest files

```

*# Manifest files*

```
AddType application/manifest+json      webmanifest
AddType application/x-web-app-manifest+json  webapp
AddType text/cache-manifest             appcache
```

*# Media files*

```
AddType audio/mp4          f4a f4b m4a
AddType audio/ogg           oga ogg opus
AddType image/bmp           bmp
AddType image/svg+xml      svg svgz
AddType image/webp          webp
AddType video/mp4          f4v f4p m4v mp4
AddType video/ogg          ogv
AddType video/webm         webm
AddType video/x-flv        flv
```

*# Serving `.ico` image files with a different media type*

*# prevents Internet Explorer from displaying them as images:*

*# <https://github.com/h5bp/html5-boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8>*

```
AddType image/x-icon          cur ico
```

*# Web fonts*

```
AddType application/font-woff      woff
AddType application/font-woff2     woff2
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf      ttc ttf
AddType font/opentype              otf
```

*# Other*

```
AddType application/octet-stream    safariextz
AddType application/x-bb-appworld    bbaw
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall      xpi
AddType text/vcard                   vcard vcf
AddType text/vnd.rim.location.xloc    xloc
AddType text/vtt                      vtt
AddType text/x-component              htc
```

```
</IfModule>
```

*# PHP 5, Apache 1 and 2.*

```

<IfModule mod_php5.c>
    php_flag magic_quotes_gpc                off
    php_flag magic_quotes_sybase             off
    php_flag register_globals                 off
    php_flag session.auto_start              off
    php_value mbstring.http_input            pass
    php_value mbstring.http_output           pass
    php_flag mbstring.encoding_translation   off
</IfModule>

# BEGIN WordPress
<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
</IfModule>
# END WordPress

# BEGIN WordPress Multisite
# <IfModule mod_rewrite.c>
# RewriteEngine On
# RewriteBase /
# RewriteRule ^index\.php$ - [L]
#
# # add a trailing slash to /wp-admin
# RewriteRule ^wp-admin$ wp-admin/ [R=301,L]
#
# RewriteCond %{REQUEST_FILENAME} -f [OR]
# RewriteCond %{REQUEST_FILENAME} -d
# RewriteRule ^ - [L]
# RewriteRule ^(wp-(content|admin|includes).*) wp/$1 [L]
# RewriteRule ^(.*\.\.php)$ wp/$1 [L]
# RewriteRule . index.php [L]
# </IfModule>
# END WordPress Multisite

# Rules to correctly serve gzip compressed CSS and JS files.
# Requires both mod_rewrite and mod_headers to be enabled.

```

```

<IfModule mod_headers.c>
    # Serve gzip compressed CSS files if they exist and the client accepts gzip.
    RewriteCond %{HTTP:Accept-encoding} gzip
    RewriteCond %{REQUEST_FILENAME}\.gz -s
    RewriteRule ^(\.*)\.css$ $1\.css\.gz [QSA]

    # Serve gzip compressed JS files if they exist and the client accepts gzip.
    RewriteCond %{HTTP:Accept-encoding} gzip
    RewriteCond %{REQUEST_FILENAME}\.gz -s
    RewriteRule ^(\.*)\.js$ $1\.js\.gz [QSA]

    # Serve correct content types, and prevent mod_deflate double gzip.
    RewriteRule \.css\.gz$ - [T=text/css,E=no-gzip:1]
    RewriteRule \.js\.gz$ - [T=text/javascript,E=no-gzip:1]

<FilesMatch "(\.js\.gz|\.css\.gz)$">
    # Serve correct encoding type.
    Header set Content-Encoding gzip
    # Force proxies to cache gzipped & non-gzipped css/js files separately.
    Header append Vary Accept-Encoding
</FilesMatch>
</IfModule>

<IfModule mod_deflate.c>
    # Force compression for mangled `Accept-Encoding` request headers
    # https://developer.yahoo.com/blogs/ydn/pushing-beyond-gzipping-25601.html
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>

    # Gzip resources without a precreated gzip
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE "application/atom+xml" \
            "application/javascript" \
            "application/json" \
            "application/ld+json" \
            "application/manifest+json" \

```

```
"application/rdf+xml" \  
"application/rss+xml" \  
"application/schema+json" \  
"application/vnd.geo+json" \  
"application/vnd.ms-fontobject" \  
"application/x-font-ttf" \  
"application/x-javascript" \  
"application/x-web-app-manifest+json" \  
"application/xhtml+xml" \  
"application/xml" \  
"font/eot" \  
"font/opentype" \  
"image/bmp" \  
"image/svg+xml" \  
"image/vnd.microsoft.icon" \  
"image/x-icon" \  
"text/cache-manifest" \  
"text/css" \  
"text/html" \  
"text/javascript" \  
"text/plain" \  
"text/vcard" \  
"text/vnd.rim.location.xloc" \  
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
  AddEncoding gzip          svgz
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
  # Enable expirations.
```

```
  ExpiresActive On
```

```
  ExpiresDefault             "access plus 1 month"
```

```
  # CSS
```

```
  ExpiresByType text/css    "access plus 1 year"
```

### *# Data interchange*

ExpiresByType	application/atom+xml	"access plus 0 hour"
ExpiresByType	application/rdf+xml	"access plus 0 hour"
ExpiresByType	application/rss+xml	"access plus 0 hour"
ExpiresByType	application/json	"access plus 0 seconds"
ExpiresByType	application/ld+json	"access plus 0 seconds"
ExpiresByType	application/schema+json	"access plus 0 seconds"
ExpiresByType	application/vnd.geo+json	"access plus 0 seconds"
ExpiresByType	application/xml	"access plus 0 seconds"
ExpiresByType	text/xml	"access plus 0 seconds"

### *# Favicon (cannot be renamed!) and cursor images*

ExpiresByType	image/vnd.microsoft.icon	"access plus 1 month"
ExpiresByType	image/x-icon	"access plus 1 month"

### *# HTML*

ExpiresByType	text/html	"access plus 0 seconds"
---------------	-----------	-------------------------

### *# JavaScript*

ExpiresByType	application/javascript	"access plus 1 year"
ExpiresByType	application/x-javascript	"access plus 1 year"
ExpiresByType	text/javascript	"access plus 1 year"

### *# Manifest files*

ExpiresByType	application/manifest+json	"access plus 1 week"
ExpiresByType	application/x-web-app-manifest+json	"access plus 0 seconds"
ExpiresByType	text/cache-manifest	"access plus 0 seconds"

### *# Media files*

ExpiresByType	audio/ogg	"access plus 1 month"
ExpiresByType	image/bmp	"access plus 1 month"
ExpiresByType	image/gif	"access plus 1 month"
ExpiresByType	image/jpeg	"access plus 1 month"
ExpiresByType	image/png	"access plus 1 month"
ExpiresByType	image/svg+xml	"access plus 1 month"
ExpiresByType	image/webp	"access plus 1 month"
ExpiresByType	video/mp4	"access plus 1 month"
ExpiresByType	video/ogg	"access plus 1 month"
ExpiresByType	video/webm	"access plus 1 month"

### *# Web fonts*

```
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"
ExpiresByType application/font-woff2 "access plus 1 month"
```

### *# Other*

```
ExpiresByType text/x-cross-domain-policy "access plus 1 week"
```

```
<FilesMatch \.php$>
```

```
# Do not allow PHP scripts to be cached unless they explicitly send cache
# headers themselves. Otherwise all scripts would have to overwrite the
# headers set by mod_expires if they want another caching behavior. This may
# fail if an error occurs early in the bootstrap process, and it may cause
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```