

```

#
# Apache/PHP/Drupal settings:
#

allow from all

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xmp|svn-
base)$|^(\code-style\.|pl|Entries.*|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Cobalt handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start        0
    #php_value session.serialize_handler
    #php_value session.save_path

```

```
php_value mbstring.http_input      pass
php_value mbstring.http_output     pass
php_value mbstring.encoding_transl 0
</IfModule>
```

*# PHP 4, Apache 2.*

```
<IfModule sapi_apache2.c>
php_value magic_quotes_gpc         0
php_value register_globals         0
php_value session.auto_start       0
php_value mbstring.http_input      pass
php_value mbstring.http_output     pass
php_value mbstring.encoding_transl 0
</IfModule>
```

*# PHP 5, Apache 1 and 2.*

```
<IfModule mod_php5.c>
php_value magic_quotes_gpc         0
php_value register_globals         0
php_value session.auto_start       0
php_value mbstring.http_input      pass
php_value mbstring.http_output     pass
php_value mbstring.encoding_transl 0
</IfModule>
```

*# Requires mod\_expires to be enabled.*

```
<IfModule mod_expires.c>
```

```
  # Enable expirations.
```

```
  ExpiresActive On
```

```
  # Cache all files for 2 weeks after access (A).
```

```
  ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
  # Do not allow PHP scripts to be cached unless they explicitly send cache
  # headers themselves. Otherwise all scripts would have to overwrite the
  # headers set by mod_expires if they want another caching behavior. This may
  # fail if an error occurs early in the bootstrap process, and it may cause
  # problems if a non-Cobalt PHP file is installed in a subdirectory.
```

```
  ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```
# Various rewrite rules.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# If your site can be accessed both with and without the 'www.' prefix, you  
# can use one of the following settings to redirect users to your preferred  
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
```

```
#
```

```
# To redirect all users to access the site WITH the 'www.' prefix,  
# (http://example.com/... will be redirected to http://www.example.com/...)  
# adapt and uncomment the following:
```

```
# RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
```

```
# RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
```

```
#
```

```
# To redirect all users to access the site WITHOUT the 'www.' prefix,  
# (http://www.example.com/... will be redirected to http://example.com/...)  
# uncomment and adapt the following:
```

```
# RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
```

```
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]
```

```
# Modify the RewriteBase if you are using Cobalt in a subdirectory or in a  
# VirtualDocumentRoot and the rewrite rules are not working properly.  
# For example if your site is at http://example.com/cobalt uncomment and  
# modify the following line:
```

```
# RewriteBase /cobalt
```

```
#
```

```
# If your site is running in a VirtualDocumentRoot at http://example.com/,  
# uncomment the following line:
```

```
# RewriteBase /
```

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```

```
# $Id: .htaccess,v 1.90.2.5 2010/02/02 07:25:22 dries Exp $
```