

```

#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engineincl|incl|install|make|module|profile|test|po|sh|. *sql|themel|tpl(\. php)?
|xtmpl)$|^(\. *| Entries. *| Repository| Root| Tag| Template)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

#IE9 Support Added by LPCMS
#BrowserMatch MSIE best-standards-support
#Header set X-UA-Compatible IE=8 env=best-standards-support

# Set the default handler.
DirectoryIndex index.php index.html index.htm

# Override PHP settings that cannot be changed at runtime. See
# sites/default/default.settings.php and drupal_initialize_variables() in
# includes/bootstrap.inc for settings that can be changed at runtime.

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_flag magic_quotes_gpc          off
    php_flag magic_quotes_runtime      off

```

```
php_flag magic_quotes_sybase      off
php_flag register_globals         off
php_flag session.auto_start      off
php_value mbstring.http_input    pass
php_value mbstring.http_output   pass
php_flag mbstring.encoding_translation off
php_value memory_limit           "256M"
php_value post_max_size          "96M"
php_value upload_max_filesize    "64M"
```

```
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
# Enable expirations.
```

```
ExpiresActive On
```

```
# Cache all files for 2 weeks after access (A).
```

```
ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
# Do not allow PHP scripts to be cached unless they explicitly send cache
# headers themselves. Otherwise all scripts would have to overwrite the
# headers set by mod_expires if they want another caching behavior. This may
# fail if an error occurs early in the bootstrap process, and it may cause
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css
application/javascript
```

```
</IfModule>
```

```
# Various rewrite rules.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# Block access to "hidden" directories whose names begin with a period. This
# includes directories used by version control systems such as Subversion or
# Git to store control files. Files whose names begin with a period, as well
# as hidden files and directories, are excluded from the content of the site.
```

```
# as the control files used by CVS, are protected by the FilesMatch directive
# above.
#
# NOTE: This only works when mod_rewrite is loaded. Without mod_rewrite, it is
# not possible to block access to entire directories from .htaccess, because
# <DirectoryMatch> is not allowed here.
#
# If you do not have mod_rewrite installed, you should remove these
# directories from your webroot or otherwise protect them from being
# downloaded.
RewriteRule "(^/)\." - [F]
```

```
RewriteRule ^(.+)/anzeigervonsaanen.localpoint-cms.com/(.+) $ $1/avs/$2 [R=302,L]
RewriteRule ^(.+)/lagrugere.localpoint-cms.com/(.+) $ $1/gru/$2 [R=302,L]
RewriteRule ^(.+)/schaffhauserlandzeitung.localpoint-cms.com/(.+) $ $1/shlz/$2 [R=302,L]
RewriteRule ^(.+)/nfz.localpoint-cms.com/(.+) $ $1/nfz/$2 [R=302,L]
RewriteRule ^(.+)/engadiner.localpoint-cms.com/(.+) $ $1/epo/$2 [R=302,L]
RewriteRule ^(.+)/seetalerbote.localpoint-cms.com/(.+) $ $1/sb/$2 [R=302,L]
RewriteRule ^(.+)/wa-bba.localpoint-cms.com/(.+) $ $1/wabba/$2 [R=302,L]
RewriteRule ^(.+)/dregion.localpoint-cms.com/(.+) $ $1/reg/$2 [R=302,L]
RewriteRule ^(.+)/volksstimme.localpoint-cms.com/(.+) $ $1/vol/$2 [R=302,L]
RewriteRule ^(.+)/frutiglaender.localpoint-cms.com/(.+) $ $1/fru/$2 [R=302,L]
RewriteRule ^(.+)/wb.localpoint-cms.com/(.+) $ $1/wb/$2 [R=302,L]
RewriteRule ^(.+)/wow.localpoint-cms.com/(.+) $ $1/wow/$2 [R=302,L]
```

```
# If your site can be accessed both with and without the 'www.' prefix, you
# can use one of the following settings to redirect users to your preferred
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
#
```

```
# To redirect all users to access the site WITH the 'www.' prefix,
# (http://example.com/... will be redirected to http://www.example.com/...)
# uncomment the following:
```

```
#RewriteCond %{HTTP_HOST} !^www\. [NC]
# RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]
```

```
#
# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment the following:
```

```
# RewriteCond %{HTTP_HOST} ^www\. (.+) $ [NC]
# RewriteRule ^ http://%1%{REQUEST_URI} [L,R=301]
```

```

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /drupal
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /
#lagruyere

RewriteBase /
RewriteCond %{REQUEST_URI} ^(.+)/files/styles/adaptive/(.+$)
RewriteCond %{REQUEST_URI} !/modules/image/sample.png
RewriteCond %{HTTP_COOKIE} ais=([a-z0-9-]+)
RewriteRule ^(.+)/files/styles/adaptive/(.+$) $1/files/styles/%1/$2 [R=302,L]

# Pass all requests not referring directly to files in the filesystem to
# index.php. Clean URLs are handled in drupal_environment_initialize().
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^ index.php [L]

# Rules to correctly serve gzip compressed CSS and JS files.
# Requires both mod_rewrite and mod_headers to be enabled.

<filesmatch "\.(ico|flv|jpg|jpeg|png|gif|swf)$">
Header set Cache-Control "max-age=2678400, public"
</filesmatch>
# Cache HTML files for a couple hours
<filesmatch "\.(html|htm)$">
Header set Cache-Control "max-age=7200, private, must-revalidate"
</filesmatch>
# Cache PDFs for a day
<filesmatch "\.(pdf)$">
Header set Cache-Control "max-age=86400, public"
</filesmatch>
# Cache CSS for 5 days
<filesmatch "\.(css|css.gz)$">
Header set Cache-Control "max-age=518400, private"

```

```
</filematch>
# Cache Javascripts for 31 days
<filematch "\.(js|js.gz)$">
Header set Cache-Control "max-age=2678400, private"
</filematch>
```

```
Header append Vary Accept-Encoding
```

```
# Turn ETags Off
<IfModule mod_headers.c>
    Header unset ETag
</IfModule>
```

```
FileETag None
```

```
<IfModule mod_headers.c>
    # Serve gzip compressed CSS files if they exist and the client accepts gzip.
    RewriteCond %{HTTP:Accept-encoding} gzip
    RewriteCond %{REQUEST_FILENAME}\.gz -s
    RewriteRule ^(\.*)\.css$ $1\.css\.gz [QSA]

    # Serve gzip compressed JS files if they exist and the client accepts gzip.
    RewriteCond %{HTTP:Accept-encoding} gzip
    RewriteCond %{REQUEST_FILENAME}\.gz -s
    RewriteRule ^(\.*)\.js$ $1\.js\.gz [QSA]

    # Serve correct content types, and prevent mod_deflate double gzip.
    RewriteRule \.css\.gz$ - [T=text/css,E=no-gzip:1]
    RewriteRule \.js\.gz$ - [T=text/javascript,E=no-gzip:1]

    <FilesMatch "\.(js\.gz|css\.gz)$">
        # Serve correct encoding type.
        Header set Content-Encoding gzip
        # Force proxies to cache gzipped & non-gzipped css/js files separately.
        Header append Vary Accept-Encoding
    </FilesMatch>
</IfModule>
</IfModule>
```

```
RewriteCond %{HTTP_HOST} ^anzeigerburgdorf\.localpoint\-cms\.com$ [OR]
RewriteCond %{HTTP_HOST} ^www\.anzeigerburgdorf\.localpoint\-cms\.com$
```

RewriteRule ^/?\$ "http://www.anzengerburgdorf.ch/" [R=301,L]

RewriteCond %{HTTP\_HOST} ^lagruyere.localpoint-cms.com\$ [OR]

RewriteCond %{HTTP\_HOST} ^www.lagruyere.localpoint-cms.com\$

RewriteRule ^/?\$ "http://www.lagruyere.ch/" [R=301,L]

RewriteCond %{HTTP\_HOST} ^anzeigervonsaanen.localpoint-cms.com\$ [OR]

RewriteCond %{HTTP\_HOST} ^www.anzeigervonsaanen.localpoint-cms.com\$

RewriteRule ^/?\$ "http://www.anzeigervonsaanen.ch/" [R=301,L]

RewriteCond %{HTTP\_HOST} ^bregarterbezirksanzeiger.localpoint-cms.com\$ [OR]

RewriteCond %{HTTP\_HOST} ^www.bregarterbezirksanzeiger.localpoint-cms.com\$

RewriteRule ^/?\$ "http://www.bregarterbezirksanzeiger.ch/" [R=301,L]

RewriteCond %{HTTP\_HOST} ^dregion.localpoint-cms.com\$ [OR]

RewriteCond %{HTTP\_HOST} ^www.dregion.localpoint-cms.com\$

RewriteRule ^/?\$ "http://www.dregion.ch/" [R=301,L]