

```
#Order Deny, Allow
#Deny from All
#Allow from 188.138.167.142

# Hide Server signature
ServerSignature Off

# Proper svg serving, Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml svg svgz

AddEncoding gzip svgz

AddDefaultCharset utf-8

DefaultLanguage en-EN

AddCharset utf-8 .css .js .xml .json

IndexIgnore *

Options All -Indexes

DirectoryIndex index.php index.html

#LimitRequestBody 10240000 # Limit to 10M

<Files ~ "^(env(\.+)?)\.php$" >
    Order allow,deny
    Deny from all
</Files>

<Files ~ "^(nginx(-php)?\.*)\.conf\.*$" >
    Order allow,deny
    Deny from all
</Files>

<IfModule mod_deflate.c>
    # html, txt, css, js, json, xml, htc:
    AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
    # AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-javascript
```

```
    AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-  
javascript
```

```
    AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
```

```
    # webfonts and svg:
```

```
    <FilesMatch "\.(ttf|otf|eot|svg)$">
```

```
        SetOutputFilter DEFLATE
```

```
    </FilesMatch>
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
    ExpiresActive On
```

```
    ExpiresByType application/x-javascript "access 36000 seconds"
```

```
    ExpiresByType application/x-shockwave-flash "access 36000 seconds"
```

```
    ExpiresByType application/pdf "access 36000 seconds"
```

```
    ExpiresByType text/css "access 36000 seconds"
```

```
    ExpiresByType text/html "access 36000 seconds"
```

```
    ExpiresByType image/x-icon "access 36000 seconds"
```

```
    ExpiresByType image/gif "access 36000 seconds"
```

```
    ExpiresByType image/png "access 36000 seconds"
```

```
    ExpiresByType image/jpg "access 36000 seconds"
```

```
    ExpiresByType image/jpeg "access 36000 seconds"
```

```
    ExpiresByType text/plain "access 36000 seconds"
```

```
    ExpiresByType video/x-flv "access 36000 seconds"
```

```
    ExpiresDefault "access 36000 seconds"
```

```
    <FilesMatch "\.(pl|php|cgi|spl|scgi|fcgi)$">
```

```
        ExpiresActive Off
```

```
    </FilesMatch>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
    # Because X-UA-Compatible isn't sent to non-IE (to save header bytes),
```

```
    # We need to inform proxies that content changes based on UA
```

```
    Header append Vary User-Agent
```

```
    # Safely cache for 10 hours
```

```
    <FilesMatch "\.(css|txt|html)?$">
```

```
        Header unset Pragma
```

```
        ...
```

```
    #Header unset ETag
    Header set Cache-Control "max-age=36000"
    Header set Vary "Accept-Encoding"
</FilesMatch>

# Safely cache for 10 hours
<FilesMatch "\.(js)$">
    Header unset Pragma
    #Header unset ETag
    Header set Cache-Control "private, max-age=36000"
    Header set Vary "Accept-Encoding"
</FilesMatch>

# Safely cache for 10 hours
<FilesMatch "\.(flv|icol|png|jpe?g|gif|bmp|swf|pdf|woff|ttf|svg|eot|otf)$">
    Header unset Pragma
    #Header unset ETag
    Header set Cache-Control "max-age=36000"
    Header set Vary "Accept-Encoding"
</FilesMatch>

<FilesMatch "\.(pl|php|cgi|spl|scgi|fcgi)$">
    Header unset Cache-Control
</FilesMatch>

<FilesMatch "image\.php">
    Header unset Pragma
</FilesMatch>

# allow access from all domains for webfonts
# alternatively you could only whitelist
# your subdomains like "sub.domain.com"
<FilesMatch "\.(ttf|otf|eot|woff|font.css)$">
    Header set Access-Control-Allow-Origin "*"
</FilesMatch>

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk
<IfModule mod_setenvif.c>
    BrowserMatch MSIE ie
```

```

    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
</IfModule>
</IfModule>

<IfModule mod_gzip.c>
    mod_gzip_on Yes
    mod_gzip_dechunk Yes
    mod_gzip_item_include file \.(html?|txt|css|js|php|pl)$
    mod_gzip_item_include handler ^cgi-script$
    mod_gzip_item_include mime ^text/. *
    mod_gzip_item_include mime ^application/x-javascript.*
    mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*
</IfModule>

<IfModule mod_rewrite.c>
    # URL Rewriting
    RewriteEngine on

    # limit server request methods to GET and PUT
    # Options -ExecCGI
    RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK|OPTIONS|HEAD)
    RewriteRule .* - [F]

    # www to non-www
    RewriteCond %{HTTPS} off
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
    RewriteRule ^(.*)$ http://%1/%1 [R=301,L]

    # https www to non-www
    RewriteCond %{HTTPS} on
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
    RewriteRule ^(.*)$ https://%1/%1 [R=301,L]

    # Fix for infinite loops
    RewriteCond %{ENV:REDIRECT_STATUS} 200
    RewriteRule .* - [L]

    # Exclude existent files or folders from rewriting
    RewriteCond %{REQUEST_FILENAME} -f [OR]
    RewriteCond %{REQUEST_FILENAME} -l [OR]
    RewriteCond %{REQUEST_FILENAME} -d

```

```
RewriteRule .* - [NC,L]
```

```
# Image cache
```

```
RewriteCond %{REQUEST_URI} @.+\. (png|jpe?gl|gif)$
```

```
RewriteRule ^static(/.+ ) image.php?static=$1 [NC,L,QSA]
```

```
# Exclude images from rewriting if they are not exists
```

```
RewriteCond %{REQUEST_URI} !(\. (png|jpe?gl|gif|bmp|ico))$
```

```
RewriteRule .+ index.php [NC,L,QSA]
```

```
</IfModule>
```

```
<IfModule mod_speling.c>
```

```
    CheckSpelling On
```

```
</IfModule>
```