

```
#  
# Apache/PHP/Drupal settings:  
#  
  
# Protect files and directories from prying eyes.  
<Files ~ "^(\\. (incl module|el p1| sh1 sql1 themel enginel xtmpl)|Entries| Repositories| Root| Tag| Template| scripts| upc  
Order deny,allow  
Deny from all  
</Files>  
  
# Set some options.  
Options -Indexes  
Options +FollowSymLinks  
  
# Customized error messages.  
ErrorDocument 404 /index.php  
  
# Set the default handler.  
DirectoryIndex index.php  
  
# Override PHP settings. More exist in sites/default/settings.php, but  
# the following cannot be changed at runtime. The first IfModule is  
# for Apache 1.3, the second for Apache 2.  
<IfModule mod_php4.c>  
php_value magic_quotes_gpc          0  
php_value register_globals         0  
php_value session.auto_start       0  
</IfModule>  
  
<IfModule sapi_apache2.c>  
php_value magic_quotes_gpc          1  
php_value register_globals         0  
php_value session.auto_start       0  
php_value session.save_handler     user  
php_value sendmail_from           groeicurve@borstvoeding.com  
php_value session.name            PHPSESSIONID  
</IfModule>  
  
# Reduce the time dynamically generated pages are cache-able.  
#TimeOut - - - - -
```

```
<IfModule mod_expires.c>
    ExpiresByType text/html A1
</IfModule>

# Various rewrite rules.
<IfModule mod_rewrite.c>
    RewriteEngine on

    # Modify the RewriteBase if you are using Drupal in a subdirectory and
    # the rewrite rules are not working properly.
    #RewriteBase /drupal

    # Rewrite old-style URLs of the form 'node.php?id=x'.
    #RewriteCond %{REQUEST_FILENAME} !-f
    #RewriteCond %{REQUEST_FILENAME} !-d
    #RewriteCond %{QUERY_STRING} ^id=([^&]+)$
    #RewriteRule node.php index.php?q=node/view/%1 [L]

    # Rewrite old-style URLs of the form 'module.php?mod=x'.
    #RewriteCond %{REQUEST_FILENAME} !-f
    #RewriteCond %{REQUEST_FILENAME} !-d
    #RewriteCond %{QUERY_STRING} ^mod=([^&]+)$
    #RewriteRule module.php index.php?q=%1 [L]

    # Rewrite current-style URLs of the form 'index.php?q=x'.
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>

# $Id: .htaccess,v 1.66.2.1 2007/01/04 21:30:32 killies Exp $
```