

pass the default character set

AddDefaultCharset UTF-8

SetEnvIf Host ^staging\. (.*) APPLICATION_ENV=staging

SetEnvIf Host integration.grrr.nl\$ APPLICATION_ENV=integration

SetEnvIf Host ^localhost\. (.*) APPLICATION_ENV=development

php_value upload_max_filesize 30M

php_value post_max_size 30M

Proper MIME types

<IfModule mod_mime.c>

Audio

AddType audio/mp4 m4a f4a f4b

AddType audio/ogg oga ogg

JavaScript

Normalize to standard type (it's sniffed in IE anyways):

<http://tools.ietf.org/html/rfc4329#section-7.2>

AddType application/javascript js

AddType application/json json

Video

AddType video/mp4 mp4 m4v f4v f4p

AddType video/ogg ogv

AddType video/webm webm

AddType video/x-flv flv

Web fonts

AddType application/x-font-woff woff

AddType application/font-woff2 woff2

AddType application/vnd.ms-fontobject eot

Browsers usually ignore the font MIME types and sniff the content,

however, Chrome shows a warning if other MIME types are used for the

following fonts.

AddType application/x-font-ttf ttc ttf

AddType font/opentype otf

Make SVGZ fonts work on iPad:

<http://www.w3.org/Font-Working-Group/2011/04/11-130559-005-05>

```
# https://twitter.com/ronlsquire1/status/14655040545
```

```
AddType image/svg+xml svg svgz
```

```
AddEncoding gzip svgz
```

Other

```
AddType application/octet-stream safariextz
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension oex
```

```
AddType application/x-shockwave-flash swf
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType application/x-xpinstall xpi
```

```
AddType application/xml atom rdf rss xml
```

```
AddType image/webp webp
```

```
AddType image/x-icon ico
```

```
AddType text/cache-manifest appcache manifest
```

```
AddType text/vtt vtt
```

```
AddType text/x-component htc
```

```
AddType text/x-vcard vcf
```

```
</IfModule>
```

cache rules

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

rss feed

```
ExpiresByType application/rss+xml "access plus 1 hour"
```

favicon (cannot be renamed)

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

webfonts

```
ExpiresByType font/truetype "access plus 1 month"
```

```
ExpiresByType font/opentype "access plus 1 month"
```

```
ExpiresByType application/x-font-woff "access plus 1 month"
```

```
ExpiresByType image/svg+xml "access plus 1 month"
```

```
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
```

css and javascript

```
ExpiresByType text/css "access plus 1 month"
```

```
ExpiresByType application/javascript "access plus 1 month"
```

```
ExpiresByType application/x-javascript "access plus 1 month"
```

```

ExpiresByType text/javascript      "access plus 1 month"
ExpiresByType application/x-javascript  "access plus 1 month"

ExpiresByType image/x-icon        "access plus 1 day"
ExpiresByType application/xhtml+xml "access plus 300 seconds"
ExpiresByType text/html           "access plus 300 seconds"
ExpiresByType application/xml     "access plus 300 seconds"

Header append Cache-Control "public"
</IfModule>

# rewrite rules
<IfModule mod_rewrite.c>
    RewriteEngine On

    # allow versioning of asset files (e.g. /123/css/screen.css)
    RewriteRule ^(?: (nl|en|de|fr|us|it|hu) /?)?(?: [0-9a-z]+ /?)?(css|js|media) /(.*) $2/$3 [L]

    # require no-www
    # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
    # RewriteRule ^(.*)$ http://example.com/$1 [R=301,L]

    # Disregard slash at the end of request
    RewriteRule ^(.*)/$ /$1 [L]

    # Work with Zend static cache
    # Homepage
    RewriteCond %{REQUEST_METHOD} GET
    RewriteCond %{DOCUMENT_ROOT}/cached/index.html -f
    RewriteRule ^/*$ cached/index.html [L]

    # Pages with query string ?foo=bar
    RewriteCond %{QUERY_STRING} .+
    RewriteCond %{REQUEST_METHOD} GET
    RewriteCond %{DOCUMENT_ROOT}/cached/%{REQUEST_URI}\?%{QUERY_STRING}\.html -f
    RewriteRule .* cached/%{REQUEST_URI}\%3F%{QUERY_STRING}\.html [L]

    # Pages with query string and slash at the end /?foo=bar
    RewriteCond %{QUERY_STRING} .+
    RewriteCond %{REQUEST_METHOD} GET
    RewriteCond %{DOCUMENT_ROOT}/cached/%{REQUEST_URI}/\?%{QUERY_STRING}\.html -f

```

```
RewriteRule .* cached/%%(REQUEST_URI)/\%3F%(QUERY_STRING)\.html [L]
```

```
# Pages without query string
```

```
RewriteCond %(REQUEST_METHOD) GET
```

```
RewriteCond %(DOCUMENT_ROOT)/cached/%%(REQUEST_URI)\.html -f
```

```
RewriteRule .* cached/%%(REQUEST_URI)\.html [L]
```

```
RewriteCond %(REQUEST_FILENAME) -s [OR]
```

```
RewriteCond %(REQUEST_FILENAME) -l [OR]
```

```
RewriteCond %(REQUEST_FILENAME) -d
```

```
RewriteRule ^.*$ - [NC,L]
```

```
RewriteRule ^.*$ index.php [NC,L]
```

```
</IfModule>
```

```
<IfModule mod_deflate.c>
```

```
# compress text, html, javascript, css, xml, svg:
```

```
AddOutputFilterByType DEFLATE text/plain text/html text/xml text/css text/javascript  
image/svg+xml application/xml application/xhtml+xml application/rss+xml  
application/javascript application/x-javascript
```

```
</IfModule>
```