

```

<IfModule mod_rewrite.c>
  #AddDefaultCharset utf-8
  Options +FollowSymlinks
  #IndexIgnore /*
  RewriteEngine On
  # RewriteBase /

  # Make the backend accessible via url: http://localhost/eproc/backend.
  #RewriteRule ^backend backend.php

  # if a directory or a file exists, use it directly
  RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d

  # otherwise forward it to index.php
  RewriteRule . index.php

  #RewriteCond $1 !^(index\.php|assets|images|css|robots\.txt)
  #RewriteRule ^(.*+)$ index.php?$1 [PT,L,QSA]
</IfModule>

<ifModule mod_headers.c>
  <filesMatch "\.(ico|jpe?g|png|gif|swf)$">
    Header set Cache-Control "max-age=2592000, public"
  </filesMatch>
  <filesMatch "\.(css)$">
    Header set Cache-Control "max-age=604800, public"
  </filesMatch>
  <filesMatch "\.(js)$">
    Header set Cache-Control "max-age=604800, private"
  </filesMatch>
  <filesMatch "\.(woff)$">
    Header set Cache-Control "max-age=604800, private"
  </filesMatch>
  <filesMatch "\.(x?html?|php)$">
    Header set Cache-Control "max-age=600, private, must-revalidate"
  </filesMatch>
</ifModule>

<IfModule mod_deflate.c>
  # Insert filter
  SetOutputFilter DEFLATE

```

```

SetOutputFilter DEFLATE

#Baris berikut untuk compress .js and .css
AddOutputFilter DEFLATE js css

#Baris berikut juga mengcompress berdasarkan tipe file content, for the following list
of Content-Type: s
AddOutputFilterByType DEFLATE text/text text/html text/plain text/xml application/xml
text/css application/x-javascript application/javascript

#Baris berikut untuk mencegah bugs dari browser yang lain
BrowserMatch ^Mozilla/4 gzip-only-text/html
BrowserMatch ^Mozilla/4\.0[678] no-gzip
BrowserMatch \bMSIE !no-gzip !gzip-only-text/html

# Make sure proxies don't deliver the wrong content
Header append Vary User-Agent env=!dont-vary
</IfModule>

# Baris berikut untuk menambahkan vary: accept-encoding untuk GZIP Compression
<IfModule mod_headers.c>
  <FilesMatch "\.(js|css|xml|gz)$">
    Header append Vary: Accept-Encoding
  </FilesMatch>
</IfModule>

<IfModule mod_filter.c>
  AddOutputFilterByType DEFLATE "application/atom+xml" \
    "application/javascript" \
    "application/json" \
    "application/ld+json" \
    "application/manifest+json" \
    "application/rdf+xml" \
    "application/rss+xml" \
    "application/schema+json" \
    "application/vnd.geo+json" \
    "application/vnd.ms-fontobject" \
    "application/x-font-ttf" \
    "application/x-javascript" \
    "application/x-web-app-manifest+json" \
    "application/xhtml+xml" \
    "application/xml" \
    "application/xml+rss" \
    "text/css"

```

```
"application/xml" \  
"font/eot" \  
"font/opentype" \  
"image/bmp" \  
"image/svg+xml" \  
"image/vnd.microsoft.icon" \  
"image/x-icon" \  
"text/cache-manifest" \  
"text/css" \  
"text/html" \  
"text/javascript" \  
"text/plain" \  
"text/vcard" \  
"text/vnd.rim.location.xloc" \  
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

</IfModule>