

```
#
# Apache/PHP/Drupal settings:
#

# set the server timezone
SetEnv TZ Australia/Perth

# set the server administrator email
#SetEnv SERVER_ADMIN support@suarstudios.com

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xhtml|svn-
base)$|^(\code-style\.|Entries\.|Repository|Root|Tag|Template|all-
wcprops|entries|format|txt)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 403 /index.php
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresOn  On
```

```
ExpiresActive on
```

```
# Cache all files for 2 weeks after access (A).
```

```
# ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
# Do not allow PHP scripts to be cached unless they explicitly send cache  
# headers themselves. Otherwise all scripts would have to overwrite the  
# headers set by mod_expires if they want another caching behavior. This may  
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# Set "protoss1" to "s" if we were accessed via https://. This is used later  
# if you enable "www." stripping or enforcement, in order to ensure that  
# you don't bounce between http and https.
```

```
RewriteRule ^ - [E=protoss1]
```

```
RewriteCond %{HTTPS} on
```

```
RewriteRule ^ - [E=protoss1:s]
```

```
RewriteCond %{HTTP_HOST} !^(backdrop|ml|test|dev)?\.\?suarstudios\.com$ [NC]
```

```
RewriteCond %{HTTP_HOST} suarstudios\.com$ [NC]
```

```
RewriteRule ^(\. *)$ http%{ENV:protoss1}://suarstudios.com%{REQUEST_URI} [L,R]
```

```
# Rewrite URLs of the form 'x' to the form 'index.php?page=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(\. *)$ index.php?page=$1 [L,QSA]
```

```
</IfModule>
```