

```

AddType text/plain .phps
AddType application/x-tgz .tgz
AddType application/x-chrome-extension .crx
AddType application/x-web-app-manifest+json .webapp

<IfModule mod_rewrite.c>
RewriteEngine on

RewriteCond %{HTTP:X-Forwarded-Proto} ^https$
RewriteRule ^(.*) - [E=P_SUFFIX:s]

# Send bingbot a `noindex` header on every page.
RewriteCond %{HTTP_USER_AGENT} bingbot
RewriteRule ^(.*) - [E=BINGBOT:1]
Header set X-Robots-Tag "noindex" env=BINGBOT
Header unset Vary env=BINGBOT

RewriteCond %{HTTP_HOST} ^www\.play\.pokemonshowdown\.com$ [NC]
RewriteRule ^(.*) http%{ENV:P_SUFFIX}: //play.pokemonshowdown.com/$1 [R=301,L]

RewriteRule ^style/font/.+?\.(\.eot|.svg|.ttf|.woff)$ - [E=SAFE_RESOURCE:1]
Header set Access-Control-Allow-Origin * env=SAFE_RESOURCE

# Redirect old battles to their corresponding replay
RewriteCond %{HTTP_HOST} ^play\.pokemonshowdown\.com$ [NC]
RewriteRule ^battle-<[a-z0-9]+-3[0-3][0-9]<6>>$ http%
{ENV:P_SUFFIX}: //pokemonshowdown.com/replay/$1 [R=302,L]
RewriteCond %{HTTP_HOST} ^play\.pokemonshowdown\.com$ [NC]
RewriteRule ^battle-<[a-z0-9]+-?[1-2][0-9]<7>>$ http%
{ENV:P_SUFFIX}: //pokemonshowdown.com/replay/$1 [R=302,L]
RewriteCond %{HTTP_HOST} ^play\.pokemonshowdown\.com$ [NC]
RewriteRule ^battle-<[a-z]+[0-9]<1,7>>$ http%
{ENV:P_SUFFIX}: //pokemonshowdown.com/replay/$1 [R=302,L]

# TODO: fix bug where you can't join lobby directly
RewriteRule ^lobby/?$ / [R=301,L]

# roomid with a slash after it: remove the slash, unless the roomid
# is also an actual directory
RewriteCond %{DOCUMENT_ROOT}/$1 !-d
RewriteRule ^([0-9]+-?[0-9][0-9]-?[0-9][0-9])/$1 - [R=301,L]

```

```

RewriteRule ^([A-Za-z0-9])([A-Za-z0-9]*)/$ /$1 [R=301,L]

#RewriteCond %{ENV:P_SUFFIX} =s
#RewriteRule ^([A-Za-z0-9]*)$ http://play.pokemonshowdown.com/$1 [L=R03,L]

# Anything that looks like a roomid: connect to the server
RewriteRule ^$ - [E=INDEX_PAGE:1]
RewriteRule ^([A-Za-z0-9][A-Za-z0-9]*)$ ./ [L,E=INDEX_PAGE:1]

# Headers for the index page.
Header set Cache-Control "no-cache, no-store, must-revalidate" env=INDEX_PAGE
Header set Pragma "no-cache" env=INDEX_PAGE
Header set Expires "0" env=INDEX_PAGE
Header set X-Robots-Tag "noindex" env=INDEX_PAGE

# No direct linking to the lobby.
RewriteCond %{ENV:SCRIPT_URL} ^/(lobby/)??$
RewriteCond %{HTTP_REFERER} !^$
RewriteCond %{HTTP_REFERER} !^https?:\/\/\./([a-z0-9]+)\.(pokemonshowdown\.com|app.js)
RewriteCond %{HTTP_HOST} ^play\.pokemonshowdown\.com$
RewriteCond %{REMOTE_ADDR} !=127.0.0.1
RewriteCond %{HTTP:CF-Connecting-IP} !=173.252.196.254
RewriteCond %{HTTP:CF-Connecting-IP} !=198.27.67.31
RewriteRule .* - [E=LOBBY_REDIRECT:1]

RewriteCond %{ENV:LOBBY_REDIRECT}%{ENV:P_SUFFIX} =1
RewriteRule ^.* http://pokemonshowdown.com/ [R=303,L]

RewriteCond %{ENV:LOBBY_REDIRECT}%{ENV:P_SUFFIX} =1s
RewriteRule ^.* http://pokemonshowdown.com/secure [R=303,L]

RewriteRule ^replay/battle-([A-Za-z0-9-]*)$ http%
{ENV:P_SUFFIX}://pokemonshowdown.com/replay/$1 [R=302,L]
RewriteRule ^replay/turn_(.+)\.png$ replay/turn-image.php?data=$1 [L,QSA]

RewriteCond %{QUERY_STRING} !output=html
RewriteRule ^ladder\.php$ http%{ENV:P_SUFFIX}://pokemonshowdown.com/ladder/ [R=301,L]

RewriteRule ^{([^/])}(:([0-9])*)?/action\.php$ action.php?serverid=$1 [L,QSA]
RewriteRule ^{([^/])}(/.*)?$ http://$1.psim.us$2 [R=301,L]
RewriteRule ^{([^/])}(:([0-9])*)(/.*)?$ http://$1-$2.psim.us$3 [R=301,L]

```

```
RewriteRule ^backup/ - [F]
RewriteRule ^\.git/ - [F]
RewriteRule ^lib/ - [F]
RewriteRule ^githooks/ - [F]

RewriteRule ^\.gitignore$ - [F]
RewriteRule ^README\.md$ - [F]
RewriteRule ^index\.template\.html$ - [F]
RewriteRule ^testclient\.html$ - [F]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule ^(apple-touch-icon-precomposed\.png)$ - [R=404,L]

</IfModule>
```