

```
# Rewrite
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteRule ^(\w+)$ $1.php [NC]
</IfModule>

# Download MP3
SetEnvIfNoCase Request_URI ^/download\.php no-gzip dont-vary

# Index
DirectoryIndex index.html index.htm index.php

# AddType TYPE/SUBTYPE EXTENSION
AddType audio/mpeg mp3
AddType audio/mp4 m4a
AddType audio/ogg ogg
AddType audio/ogg oga
AddType audio/webm webma
AddType audio/wav wav
AddType application/x-httpd-php .json

<IfModule mod_setenvif.c>
    SetEnv TZ Europe/Kiev
</IfModule>

ServerSignature Off
AddDefaultCharset UTF-8

DirectoryIndex index.html

<ifModule mod_php.c>
    php_value upload_max_filesize 100M
    php_value post_max_size 100M
    php_value default_charset utf-8
    php_value max_execution_time 120
    php_value memory_limit 256M
    php_value max_input_vars 10000
    php_value suhosin.post.max_vars 10000
    php_value suhosin.request.max_vars 10000
</ifModule>
```

```
# gzip
<ifModule mod_gzip.c>
  mod_gzip_on Yes
  mod_gzip_dechunk Yes
  mod_gzip_item_include file \.(html?|txt|css|js|php|pl)$
  mod_gzip_item_include handler ^cgi-script$
  mod_gzip_item_include mime ^text/. *
  mod_gzip_item_include mime ^application/x-javascript.*
  mod_gzip_item_exclude mime ^image/. *
  mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*
</ifModule>
```

```
AddOutputFilterByType DEFLATE text/plain
AddOutputFilterByType DEFLATE text/html
AddOutputFilterByType DEFLATE text/xml
AddOutputFilterByType DEFLATE text/css
AddOutputFilterByType DEFLATE application/xml
AddOutputFilterByType DEFLATE application/xhtml+xml
AddOutputFilterByType DEFLATE application/rss+xml
AddOutputFilterByType DEFLATE application/javascript
AddOutputFilterByType DEFLATE application/x-javascript
```

```
<ifModule mod_deflate.c>
  AddOutputFilterByType DEFLATE text/html text/plain text/xml application/xml
  application/xhtml+xml text/css text/javascript application/javascript application/x-
  javascript
  AddOutputFilterByType DEFLATE application/x-font-ttf application/x-font-opentype
  image/svg+xml
</ifModule>
```

```
<ifModule mod_expires.c>
  # Add correct content-type for fonts
  AddType application/vnd.ms-fontobject .eot
  AddType application/x-font-ttf .ttf
  AddType application/x-font-opentype .otf
  AddType application/x-font-woff .woff
  AddType image/svg+xml .svg

  # Compress compressible fonts
  AddOutputFilterByType DEFLATE application/x-font-ttf application/x-font-opentype
```

image/svg+xml

ExpiresActive On

ExpiresDefault "access plus 2592000 seconds"

ExpiresByType image/x-icon "access plus 2592000 seconds"

ExpiresByType image/jpeg "access plus 2592000 seconds"

ExpiresByType image/png "access plus 2592000 seconds"

ExpiresByType image/gif "access plus 2592000 seconds"

ExpiresByType application/x-font-ttf "access plus 2592000 seconds"

ExpiresByType application/x-woff "access plus 2592000 seconds"

ExpiresByType application/vnd.ms-fontobject "access plus 2592000 seconds"

ExpiresByType image/svg+xml "access plus 2592000 seconds"

ExpiresByType application/x-font-opentype "access plus 2592000 seconds"

ExpiresByType application/x-shockwave-flash "access plus 2592000 seconds"

ExpiresByType text/css "access plus 604800 seconds"

ExpiresByType text/javascript "access plus 2592000 seconds"

ExpiresByType application/javascript "access plus 2592000 seconds"

ExpiresByType application/x-javascript "access plus 2592000 seconds"

ExpiresByType text/html "access plus 600 seconds"

ExpiresByType application/xhtml+xml "access plus 600 seconds"

</ifModule>