

```
# In case you want to add a .htpasswd authentication
# you'll have to add the host of the shop as an allowed entity,
# so that calls from the host skip the authentication
# Example:
# Order Deny, Allow
# Deny from All
# AuthType Basic
# AuthName "Access not allowed"
# AuthUserFile path_to_htpasswd_file/.htpasswd
# Require valid-user
# Allow from localhost
# Satisfy Any
```

```
<IfModule mod_rewrite.c>
Options +FollowSymLinks
RewriteEngine On
RewriteBase /
```

```
RewriteCond %{REQUEST_METHOD} ^(TRACE|TRACK)
RewriteRule .* - [F]
```

```
RewriteCond %{REQUEST_URI} oxseo\.php$
RewriteCond %{QUERY_STRING} mod_rewrite_module_is=off
RewriteRule oxseo\.php$ oxseo.php?mod_rewrite_module_is=on [L]
```

```
RewriteCond %{REQUEST_URI} !
(&\/admin\/&\/core\/&\/application\/&\/export\/&\/modules\/&\/out\/&\/setup\/&\/tmp\/&\/views:
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule !(\/.html|\/\.(j|p|g|l|c|s|s|l|p|d|f|d|o|c|l|g|f|l|p|n|g|l|j|s|l|t|c|)$) %{REQUEST_URI}/
[R=301,L]
```

```
RewriteCond %{REQUEST_URI} !
(&\/admin\/&\/core\/&\/application\/&\/export\/&\/modules\/&\/out\/&\/setup\/&\/tmp\/&\/views:
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\/.html|\/)$ oxseo.php
```

```
RewriteCond %{REQUEST_URI} (&\/out\/pictures\/)
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule (\.jpe?gl\.gif|\.png)$ core/utis/getimg.php

</IfModule>

# disabling log file access from outside
<FilesMatch "(EXCEPTION_LOG\.txt|\.log$|\.tpl$|pkg\.rev)">
order allow,deny
deny from all
</FilesMatch>

Options -Indexes
DirectoryIndex index.php index.html
```