

```
Options +FollowSymLinks -Indexes
```

```
<IfModule mod_env.c>
```

```
# No GZIP for script-based file downloads.
```

```
SetEnv no-gzip 1
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
# Enable rewrite and configure base.
```

```
RewriteEngine On
```

```
RewriteBase /~kwiseorg/main/
```

```
# Initialize all environment variables we're using below.
```

```
RewriteCond %{ENV:s2member_file_download_setup} !^complete$
```

```
RewriteRule ^(.*)$ -
```

```
[E=s2member_file_download_up_vdir: 0,E=s2member_file_download: $1,E=s2member_file_stream: 0,E=:
```

```
# Handle virtual directories, common on multisite networks.
```

```
RewriteCond %{ENV:s2member_file_download_up_vdir_check} !^complete$
```

```
RewriteCond %{THE_REQUEST} ^(?: GET| HEAD)(?: [\ ]+)(?: /~kwiseorg/main/)([ _0-9a-zA-Z\ ]+)(?:
```

```
RewriteRule ^(.*)$ - [E=s2member_file_download_up_vdir: ,E=s2member_file_download_up_vdir: :
```

```
# Handle streaming download requests via the rewrite engine.
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream/)(.+) $
```

```
RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream-(.+)/)(.+) $
```

```
RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member
```

```
# Handle inline file requests via the rewrite engine.
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline/)(.+) $
```

```
RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline-(.+)/)(.+) $
```

```
RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member
```

```
# Handle storage specifications via the rewrite engine.
```

```
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-storage-(.+)/)(.+) $
```

```
RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member
```

```
# Handle requests without the rewrite engine via the rewrite engine.
```

```

# handle remote authorization requests via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-remote/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-remote-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Handle SSL file requests via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-ssl/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-ssl-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Handle file download keys via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-file-download-key-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Handle confirmations having been skipped via the rewrite engine.
RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-skip-confirmation/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%2,E=s2member

RewriteCond %{ENV:s2member_file_download} ^(.*)?(?:s2member-skip-confirmation-(.+)/)(.+)
RewriteRule ^(.*)$ - [N,E=s2member_file_download:,E=s2member_file_download:%1%3,E=s2member

# Cleanup variables not used in this request. Looking for `0` values.
RewriteCond %{ENV:s2member_file_download_wp_vdir} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_download_wp_vdir:]

RewriteCond %{ENV:s2member_file_stream} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_stream:]

RewriteCond %{ENV:s2member_file_inline} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_inline:]

RewriteCond %{ENV:s2member_file_storage} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_storage:]

RewriteCond %{ENV:s2member_file_remote} ^0$
RewriteRule ^(.*)$ - [E=s2member_file_remote:]

```

```
RewriteCond %(ENV: s2member_file_ssl) ^0$
```

```
RewriteRule ^(.*)$ - [E=s2member_file_ssl: ]
```

```
RewriteCond %(ENV: s2member_file_download_key) ^0$
```

```
RewriteRule ^(.*)$ - [E=s2member_file_download_key: ]
```

```
RewriteCond %(ENV: s2member_skip_confirmation) ^0$
```

```
RewriteRule ^(.*)$ - [E=s2member_skip_confirmation: ]
```

```
# Put everything together now and process the internal rewrite.
```

```
RewriteRule ^(.*)$ %(ENV: s2member_file_download_wp_vdir)?s2member_file_download=%(ENV: s2m  
(ENV: s2member_skip_confirmation) [QSA, L]
```

```
</IfModule>
```

```
<IfModule !mod_rewrite.c>
```

```
deny from all
```

```
</IfModule>
```