

```
# -----
# / Concrete5 default rewrites /
# -----

# This is part of enabling pretty urls in C5

<IfModule mod_rewrite.c>
RewriteEngine On
RewriteBase /
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME}/index.html !-f
RewriteCond %{REQUEST_FILENAME}/index.php !-f
RewriteRule . index.php [L]
</IfModule>

# -----
# / Web fonts access /
# -----

# Allow access from all domains for web fonts

<IfModule mod_headers.c>
  <FilesMatch "\.(eot|font. css| otf| ttf| woff)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>

# #####
# # MIME TYPES AND ENCODING #
# #####

# -----
# / Proper MIME types for all files /
# -----

<IfModule mod_mime.c>

# Audio
AddType audio/mp4 m4a f4a f4b
AddType audio/ogg oga ogg
```

```

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways):
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js jsonp
AddType application/json            json

# Video
AddType video/mp4                   mp4 m4v f4v f4p
AddType video/ogg                    ogv
AddType video/webm                   webm
AddType video/x-flv                  flv

# Web fonts
AddType application/font-woff        woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font MIME types and sniff the content,
# however, Chrome shows a warning if other MIME types are used for the
# following fonts.
AddType application/x-font-ttf       ttc ttf
AddType font/opentype                otf

# Make SVGZ fonts work on iPad:
# https://twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml               svg svgz
AddEncoding gzip                     svgz

# Other
AddType application/octet-stream     safariextz
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-shockwave-flash swf
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall      xpi
AddType application/xml              atom rdf rss xml
AddType image/webp                   webp
AddType image/x-icon                  ico
AddType text/cache-manifest           appcache manifest
AddType text/vtt                      vtt
AddType text/x-component              htc

```

AddType text/x-vcard

vcf

</IfModule>

```
# -----  
# | UTF-8 encoding |  
# -----
```

```
# Use UTF-8 encoding for anything served as `text/html` or `text/plain`.  
AddDefaultCharset utf-8
```

```
# Force UTF-8 for certain file formats.
```

<IfModule mod_mime.c>

```
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
```

</IfModule>

```
# -----  
# | Suppressing / Forcing the "www." at the beginning of URLs |  
# -----
```

```
# Option 1: rewrite www.example.com → example.com
```

<IfModule mod_rewrite.c>

```
    RewriteCond %{HTTPS} !=on  
    RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]  
    RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
```

</IfModule>

```
# -----
```

```
# Option 2: rewrite example.com → www.example.com
```

```
# Be aware that the following might not be a good idea if you use "real"  
# subdomains for certain parts of your website.
```

```
# <IfModule mod_rewrite.c>
```

```
#     RewriteCond %{HTTPS} !=on  
#     RewriteCond %{HTTP_HOST} !^www\..+$ [NC]  
#     RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
```

```

# </IfModule>

# #####
# # SECURITY #
# #####

# -----
# | File access |
# -----

# Block access to directories without a default document.
# Usually you should leave this uncommented because you shouldn't allow anyone
# to surf through every directory on your server (which may includes rather
# private places like the CMS's directories).

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----

# Block access to hidden files and directories.
# This includes directories used by version control systems such as Git and SVN.

<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^|/)\." - [F]
</IfModule>

# -----

# Block access to backup and source files.
# These files may be left by some text editors and can pose a great security
# danger when anyone has access to them.

<FilesMatch "(^#.*# \.(bak|config|dist|fla|incl|ini|log|psd|shl|sql|sw[op])|~)$">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

```

