

```
AddType application/vnd.ms-fontobject .eot
AddType font/ttf .ttf
AddType font/otf .otf
AddType application/x-font-woff .woff

<FilesMatch "\.
(enginel incl infol installl makel modulel profilel testl pol shl . *sql1 themel tpl(\. php)?|xtmpl1 svn-
base)$|^((code-style\.\. pl|Entries. *| Repositoryl Root| Tagl Template| all-
wcprops| entries| format)$">
    Order allow,deny
</FilesMatch>

Options +Indexes

Options +FollowSymLinks

ErrorDocument 404 /index.php

<Files favicon.ico>
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

<IfModule mod_php4.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start        0
    php_value mbstring.http_input       pass
    php_value mbstring.http_output      pass
    php_value mbstring.encoding_translation 0
</IfModule>

# PHP 4, Apache 2.
<IfModule sapi_apache2.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start        0
    php_value mbstring.http_input       pass
    -----
```

```
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_value magic_quotes_gpc 0
    php_value register_globals 0
    php_value session.auto_start 0
    php_value mbstring.http_input pass
    php_value mbstring.http_output pass
    php_value mbstring.encoding_translation 0
</IfModule>

<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresDefault A1209600

    <FilesMatch \.php$>
        ExpiresActive Off
    </FilesMatch>
</IfModule>

<IfModule mod_rewrite.c>
    RewriteEngine on
    RewriteCond %{REQUEST_FILENAME} !-f
    RewriteCond %{REQUEST_FILENAME} !-d
    RewriteCond %{REQUEST_URI} !=/favicon.ico
    RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
</IfModule>
```