

```
SetEnv PHP_VER 5
```

```
SetEnv REGISTER_GLOBALS 0
```

```
SetEnv ZEND_OPTIMIZER 1
```

```
SetEnv MAGIC_QUOTES 0
```

```
RewriteEngine on
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteRule ^medias/(.*)$ /datas/medias/$1 [QSA,L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f [NC]
```

```
RewriteRule ^blog/(.*)\.(gif|jpg|png)$ /datas/medias/$1 [QSA,L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f [NC]
```

```
RewriteRule ^(.*)\.(gif|jpg|png)$ /datas/medias/$1 [QSA,L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f [NC]
```

```
RewriteRule ^softwares/(.*)$ /$1 [QSA,L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f [NC]
```

```
RewriteCond %{REQUEST_URI} !^/owncloud [NC]
```

```
RewriteRule ^(.*) /index.php?path=$1 [E=REMOTE_USER:%{HTTP:Authorization},L]
```

```
# -----
```

```
# Proper MIME type for all files
```

```
# -----
```

```
# JavaScript
```

```
# Normalize to standard type (it's sniffed in IE anyways)
```

```
# tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript js jsonp
```

```
AddType application/json json
```

```
# Audio
```

```
AddType audio/ogg oga ogg
```

```
AddType audio/mp4 m4a f4a f4b
```

```
# Video
```

```
AddType video/ogg ogv
```

```
AddType video/mp4 mp4 m4v f4v f4p
```

```
AddType video/webm webm
```

```

AddType video/webm                webm
AddType video/x-flv                flv

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType    image/svg+xml          svg svgz
AddEncoding gzip                  svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf        ttf ttc
AddType font/opentype                 otf
AddType application/x-font-woff       woff

# Assorted types
AddType image/x-icon                  ico
AddType image/webp                    webp
AddType text/cache-manifest           appcache manifest
AddType text/x-component              htc
AddType application/xml               rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall        xpi
AddType application/octet-stream       safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard                   vcf
AddType application/x-shockwave-flash  swf
AddType text/vtt                       vtt

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>

    # Force deflate for mangled headers developer.yahoo.com/blogs/ymn/posts/2010/12/pushing-
    beyond-gzipping/
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)l ~(15)l -(15))$

```

```

^((gzip|deflate)\s*, ?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding
    RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# Compress all output labeled with one of the following MIME-types
<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/x-component \
        text/xml

</IfModule>

</IfModule>

# -----
# Expires headers (for better cache control)
# -----

# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/

# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week".

<IfModule mod_expires.c>
    ExpiresActive on

```

```
# Perhaps better to whitelist expires rules? Perhaps.
ExpiresDefault "access plus 1 month"

# cache, apcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
ExpiresByType text/cache-manifest "access plus 0 seconds"

# Your document html
ExpiresByType text/html "access plus 0 seconds"

# Data
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 week"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
```

```
# CSS and JavaScript
ExpiresByType text/css          "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"

</IfModule>

# -----
# Prevent mobile network providers from modifying your site
# -----

# The following header prevents modification of your code over 3G on some
# European providers.
# This is the official 'bypass' suggested by O2 in the UK.

# <IfModule mod_headers.c>
# Header set Cache-Control "no-transform"
# </IfModule>

# -----
# ETag removal
# -----

# FileETag None is not enough for every server.
<IfModule mod_headers.c>
  Header unset ETag
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
# developer.yahoo.com/performance/rules.html#etags
FileETag None

# -----
# Set Keep-Alive Header
# -----

# Keep-Alive allows the server to send multiple requests through one
# TCP-connection. Be aware of possible disadvantages of this setting. Turn on
# if you serve a lot of static content.

<IfModule mod_headers.c>
```

```
Header set Connection Keep-Alive
</IfModule>

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml
```