

```
#

# @copyright Copyright 2003-2011 Zen Cart Development Team

# @license http://www.zen-cart.com/license/2_0.txt GNU Public License V2.0

# @version $Id: .htaccess 18695 2011-05-04 05:24:19Z drbyte $

#

AuthType Basic

AuthName "No access"

AuthUserFile .htnopasswd

AuthGroupFile /dev/null

#Require valid-user

#####

#

# This is used with Apache WebServers

#

# The following blocks direct HTTP requests to all filetypes in this directory
recursively, except certain approved exceptions

# It also prevents the ability of any scripts to run. No type of script, be it PHP, PERL
or whatever, can normally be executed if ExecCGI is disabled.

# Will also prevent people from seeing what is in the dir. and any sub-directories

#

# For this to work, you must include either 'All' or at least: 'Limit' and 'Indexes'
parameters to the AllowOverride configuration in your apache/conf/httpd.conf file.
```

Additionally, if you want the added protection offered by the OPTIONS directive below, you'll need to add 'Options' to the AllowOverride list, if 'All' is not specified.

Example:

```
#<Directory "/usr/local/apache/htdocs">
```

```
# AllowOverride Limit Options Indexes
```

```
#</Directory>
```

```
#####
```

```
# deny *everything*
```

```
<FilesMatch ".*">
```

```
    Order Allow,Deny
```

```
    Deny from all
```

```
</FilesMatch>
```

```
# but now allow just *certain* necessary files:
```

```
<FilesMatch ".*\.(zip|ZIP|gzip|pdf|PDF|mp3|MP3|swf|SWF|wm|WMA|wml|WML|wav|epub)$">
```

```
    Order Allow,Deny
```

```
    Allow from all
```

```
</FilesMatch>
```

```
<IfModule mod_headers.c>
```

```
    <FilesMatch ".*\.(zip|ZIP|pdf|PDF|mp3|MP3|swf|SWF|wm|WMA|wml|WML|wav|epub)$">
```

```
        # tell all downloads to automatically be treated as "save as" instead of launching in an application directly
```

ALERT: ForceType requires Apache2 or later. If using older version of Apache, it will need mod_mime installed. Or just comment out the ForceType line below

(to disable, just comment the next 2 lines by adding a '#' at the beginning of each):

```
ForceType application/octet-stream
```

```
Header set Content-Disposition attachment
```

```
</FilesMatch>
```

```
</IfModule>
```

```
IndexIgnore /*
```

NOTE: If you want even greater security to prevent hackers from running scripts in this folder, uncomment the following line (if your hosting company will allow you to use OPTIONS):

```
# OPTIONS -Indexes -ExecCGI
```