

```

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    BrowserMatch MSIE ie
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
  </IfModule>
</IfModule>

<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>

# video
AddType video/ogg ogg ogv
AddType video/mp4 mp4
AddType video/webm webm

# Proper svg serving. Required for svg webfonts on iPad
AddType image/svg+xml          svg svgz

# webfonts
AddType application/vnd.ms-fontobject eot
AddType font/ttf                      ttf
AddType font/otf                      otf
AddType font/x-woff                  woff

AddType text/cache-manifest          manifest

# gzip compression.
<IfModule mod_deflate.c>

# html, xml, css, and js:
  AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css application/x-
  javascript text/javascript application/javascript application/json

# webfonts and svg:
  <FilesMatch "\.(ttf|otf|eot|svg)$" >
    SetOutputFilter DEFLATE
  </FilesMatch>
</IfModule>

```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
Header set cache-control: public
```

```
ExpiresActive on
```

```
# Perhaps better to whitelist expires rules? Perhaps.
```

```
ExpiresDefault "access plus 1 month"
```

```
# cache.manifest needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
# your document html
```

```
ExpiresByType text/html "access"
```

```
# rss feed
```

```
ExpiresByType application/rss+xml "access plus 1 hour"
```

```
# favicon (cannot be renamed)
```

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
```

```
# media: images, video, audio
```

```
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType image/jpg "access plus 1 month"
```

```
ExpiresByType image/jpeg "access plus 1 month"
```

```
ExpiresByType video/ogg "access plus 1 month"
```

```
ExpiresByType audio/ogg "access plus 1 month"
```

```
ExpiresByType video/mp4 "access plus 1 month"
```

```
# webfonts
```

```
ExpiresByType font/ttf "access plus 1 month"
```

```
ExpiresByType font/woff "access plus 1 month"
```

```
ExpiresByType image/svg+xml "access plus 1 month"
```

```
# css and javascript
```

```
ExpiresByType text/css "access plus 1 month"
```

```
ExpiresByType application/javascript "access plus 1 month"
```

```
ExpiresByType text/javascript "access plus 1 month"
```

```
</IfModule>
```

```
# Since we're sending far-future expires, we don't need ETags for
```

```
these files
```

static content.

FileETag None

you probably want www.example.com to forward to example.com -- shorter URLs are sexier.

no-www.org/faq.php?q=class_b

#RewriteEngine On

#RewriteCond %{HTTP_HOST} ^www\.(.+\$) [NC]

#RewriteRule ^(.*)\$ http://%1/\$1 [R=301,L]

without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name does not exist (e.g. "/blog/hello")

Options -MultiViews

-Indexes will have Apache block users from browsing folders without a default document

Options -Indexes

use utf-8 encoding for anything served text/plain or text/html

AddDefaultCharset utf-8

force utf-8 for a number of file formats

AddCharset utf-8 .html .css .js .xml .json .rss