

```
# Set default charset utf-8
AddDefaultCharset UTF-8

# Block access to directories without a default document.
# You should leave the following uncommented, as you shouldn't allow anyone to
# surf through every directory on your server (which may includes rather private
# places such as the CMS's directories).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# PHP 5, Apache 1 and 2
<IfModule mod_php5.c>
    php_flag magic_quotes_gpc off
    php_flag magic_quotes_sybase off
    php_flag register_globals off
</IfModule>

# Force Internet Explorer to render pages in the highest available mode
# in the various cases when it may not.
# http://hsivonen.iki.fi/doctype/ie-mode.pdf
<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"
    # `mod_headers` cannot match based on the content-type, however, this
    # header should be send only for HTML pages and not for the other resources
    <FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpv]|flv|gif|html|icol|jpe?
gl|js|json|ld)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|tt[cf]|vcf|vtt|webapp|web[mp]|woff|xml|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# Prevent viewing of .htaccess file
<Files ~ "\.ht">
    Order allow,deny
    Deny from all
    Satisfy all
</Files>

# ---
```

```
# gzip
<ifModule mod_gzip.c>
    mod_gzip_on Yes
    mod_gzip_dechunk Yes
    mod_gzip_item_include file \.(archivel|cachel|cssl|eotl|holdl|html?l|jsl|jsonp?l|mdl|phpl|pll|ttfl|txtl|xml)$
    mod_gzip_item_include handler ^cgi-script$
    mod_gzip_item_include mime ^text/. *
    mod_gzip_item_include mime ^application/. *
    mod_gzip_item_exclude mime ^image/. *
    mod_gzip_item_exclude file \.woff2?$
    mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*
</ifModule>
```

```
# The following expires headers are set pretty far in the future. If you
# don't control versioning with filename-based cache busting, consider
# lowering the cache time for resources such as style sheets and JavaScript
# files to something like one week.
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/ld+json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"
```

```
# Favicon (cannot be renamed!) and cursor images
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```
# HTML components (HTCs)
```

```
ExpiresByType text/x-component "access plus 1 month"
```

```
# HTML
```

```
ExpiresByType text/html "access plus 0 seconds"
```

```
...

```

### # JavaScript

ExpiresByType application/javascript "access plus 1 year"

### # Manifest files

ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"

ExpiresByType text/cache-manifest "access plus 0 seconds"

### # Media

ExpiresByType audio/ogg "access plus 1 month"

ExpiresByType image/gif "access plus 1 month"

ExpiresByType image/jpeg "access plus 1 month"

ExpiresByType image/png "access plus 1 month"

ExpiresByType video/mp4 "access plus 1 month"

ExpiresByType video/ogg "access plus 1 month"

ExpiresByType video/webm "access plus 1 month"

### # Web feeds

ExpiresByType application/atom+xml "access plus 1 hour"

ExpiresByType application/rss+xml "access plus 1 hour"

### # Web fonts

ExpiresByType application/font-woff "access plus 10 year"

ExpiresByType application/vnd.ms-fontobject "access plus 10 year"

ExpiresByType application/x-font-woff "access plus 10 year"

ExpiresByType application/x-font-ttf "access plus 10 year"

ExpiresByType font/opentype "access plus 10 year"

ExpiresByType image/svg+xml "access plus 10 year"

</IfModule>

<IfModule mod\_rewrite.c>

RewriteEngine on

RewriteCond %{REQUEST\_FILENAME} !-f

RewriteCond %{REQUEST\_FILENAME} !-d

RewriteRule ^(.\*)\$ index.php?\$1 [L,QSA]

</IfModule>