

```

# Apache Server Configs v2.1.0 | MIT License
# https://github.com/h5bp/server-configs-apache

# (!) Using `.htaccess` files slows down Apache, therefore, if you have access
# to the main server config file (usually called `httpd.conf`), you should add
# this logic there: http://httpd.apache.org/docs/current/howto/htaccess.html.

### PRERENDER.ID
<IfModule mod_headers.c>
    RequestHeader set X-Prerender-Token "2Kt3kdKm7ZAKKaPCYypi"
</IfModule>

#<ifModule mod_rewrite.c>
# RewriteEngine On
# RewriteCond %{REQUEST_FILENAME} !-f
# RewriteCond %{REQUEST_FILENAME} !-d
# RewriteCond %{REQUEST_URI} !index
# RewriteCond %{REQUEST_URI} !API
# RewriteCond %{REQUEST_URI} !.*\.(css|js|html|png|svg|json)
# RewriteRule (.*) index.html [L]
#</ifModule>

#<IfModule mod_rewrite.c>
# RewriteEngine On Options +FollowSymLinks
# RewriteCond %{REQUEST_URI} ^/$
# RewriteCond %{QUERY_STRING} ^_escaped_fragment_=??(.*)$
# RewriteRule ^(.*)$ /snapshots/%1? [NC,L]
#</IfModule>

<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        <FilesMatch "\.(curl|gif|ico|jpe?g|png|svgz?|webp)$">
            SetEnvIf Origin ":" IS_CORS
            Header set Access-Control-Allow-Origin "*" env=IS_CORS
        </FilesMatch>
    </IfModule>
</IfModule>

<IfModule mod_headers.c>
    <FilesMatch "\.(eot|otf|ttf|woff)$">
        Header set Access-Control-Allow-Origin "*"
    </FilesMatch>
</IfModule>

```

```

    Header set Access-Control-Allow-Origin *
  </FilesMatch>
</IfModule>

Options -MultiViews
ErrorDocument 404 /404.html

<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=edge"
  # `mod_headers` can't match based on the content-type, however, we only
  # want to send this header for HTML pages and not for the other resources
  <FilesMatch "\.(appcache|crx|css|curl|eot|gif|htc|ico|jpe?
gl|jst|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogv|opus|otf|pdf|png|safariextz|svgz?
|ttf|vcf|webapp|webm|webpl|woff|xml|xpi)$">
    Header unset X-UA-Compatible
  </FilesMatch>
</IfModule>

<IfModule mod_mime.c>

  # Audio
  AddType audio/mp4          m4a f4a f4b
  AddType audio/ogg          oga ogg opus

  # Data interchange
  AddType application/json   json map

  # JavaScript
  # Normalize to standard type (it's sniffed in IE anyways):
  # http://tools.ietf.org/html/rfc4329#section-7.2
  AddType application/javascript    js

  # Video
  AddType video/mp4          f4v f4p m4v mp4
  AddType video/ogg          ogv
  AddType video/webm         webm
  AddType video/x-flv        flv

  # Web fonts
  AddType application/font-woff    woff
  AddType application/vnd.ms-fontobject    eot

```

```
# Browsers usually ignore the font MIME types and sniff the content,  
# however, Chrome shows a warning if other MIME types are used for the  
# following fonts.
```

```
AddType application/x-font-ttf          ttc ttf  
AddType font/opentype                   otf
```

```
# Make SVGZ fonts work on iPad:  
# https://twitter.com/FontSquirrel/status/14855840545
```

```
AddType    image/svg+xml                svgz  
AddEncoding gzip                        svgz
```

```
# Other
```

```
AddType application/octet-stream       safariextz  
AddType application/x-chrome-extension  crx  
AddType application/x-opera-extension   oex  
AddType application/x-web-app-manifest+json webapp  
AddType application/x-xpinstall         xpi  
AddType application/xml                 atom rdf rss xml  
AddType image/webp                      webp  
AddType image/x-icon                    cur  
AddType text/cache-manifest              appcache manifest  
AddType text/vtt                         vtt  
AddType text/x-component                 htc  
AddType text/x-vcard                     vcf
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
    AddCharset utf-8 .atom .css .js .json .rss .vtt .webapp .xml
```

```
</IfModule>
```

```
<IfModule mod_rewrite.c>
```

```
    Options +FollowSymlinks
```

```
    # Options +SymLinksIfOwnerMatch
```

```
    RewriteEngine On
```

```
    # RewriteBase /
```

```
</IfModule>
```

```
<IfModule mod_autoindex.c>
```

```
    Options -Indexes
```

```
</IfModule>
```

```

<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "^(\/)\." - [F]
</IfModule>

<FilesMatch "(^#.#|\. (bak|config|dist|fla|incl|ini|log|psd|sh|sql|sw[op])|")$" >

    # Apache < 2.3
    <IfModule !mod_authz_core.c>
        Order allow,deny
        Deny from all
        Satisfy All
    </IfModule>

    # Apache ≥ 2.3
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>

</FilesMatch>

<IfModule mod_deflate.c>
    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*, ?\s*)+ [X"-]{4,13}$ HAVE_Accept-Encoding
            RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
        </IfModule>
    </IfModule>
    <IfModule mod_filter.c>
        AddOutputFilterByType DEFLATE application/atom+xml \
            application/javascript \
            application/json \
            application/rss+xml \
            application/vnd.ms-fontobject \
            application/x-font-ttf \
            application/x-web-app-manifest+json \
            application/xhtml+xml \
            application/xml \

```

```
font/opentype \  
image/svg+xml \  
image/x-icon \  
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
ExpiresDefault "access plus 1 month"
```

```
# CSS
```

```
ExpiresByType text/css "access plus 1 year"
```

```
# Data interchange
```

```
ExpiresByType application/json "access plus 0 seconds"
```

```
ExpiresByType application/xml "access plus 0 seconds"
```

```
ExpiresByType text/xml "access plus 0 seconds"
```

```
# Favicon (cannot be renamed!) and cursor images
```

```
ExpiresByType image/x-icon "access plus 1 week"
```

```
# HTML components (HTCs)
```

```
ExpiresByType text/x-component "access plus 1 month"
```

```
# HTML
```

```
ExpiresByType text/html "access plus 0 seconds"
```

```
# JavaScript
```

```
ExpiresByType application/javascript "access plus 1 year"
```

```
# Manifest files
```

```
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

Media

```
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
```

Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

```
</IfModule>
```