

```
#####  
# Do not allow the listing of directories  
#####
```

Options -Indexes

```
#####  
# Mime-type, Encoding, ...  
#####
```

AddDefaultCharset UTF-8

```
AddType 'text/html; charset=UTF-8' .html  
AddType 'text/css; charset=UTF-8' .css  
AddType 'application/x-javascript; charset=UTF-8' .js  
AddType 'image/gif; charset=UTF-8' .gif  
AddType 'image/jpeg; charset=UTF-8' .jpeg  
AddType 'image/jpeg; charset=UTF-8' .jpg  
AddType 'image/png; charset=UTF-8' .png  
AddType 'application/vnd.ms-fontobject; charset=UTF-8' .eot  
AddType 'font/ttf; charset=UTF-8' .ttf  
AddType 'font/otf; charset=UTF-8' .otf  
AddType 'font/x-woff; charset=UTF-8' .woff  
AddType 'image/svg+xml; charset=UTF-8' .svg  
AddType 'video/ogg; charset=UTF-8' .ogv  
AddType 'video/webm; charset=UTF-8' .webm  
AddType 'video/mp4; charset=UTF-8' .mp4
```

<IfModule mod_headers.c>

Header always set X-Powered-By "Irish Leprechauns"

Header always unset X-Pingback

</IfModule>

```
#####  
# ETags  
#####
```

<IfModule mod_headers.c>

Header always unset ETag

</IfModule>

FileETag None

```

#####
# GZIP
#####

<IfModule mod_deflate.c>
    SetOutputFilter deflate
    SetEnvIfNoCase Request_URI \.(gif|jpe?g|png|ico|zip|pdf|docx?|xlsx?|pptx?|eot|ttf|otf|woff
</IfModule>

#####
# HTTP Cache
#####

# Resources
<FilesMatch "\.(css|js|gif|jpe?g|png|ico|zip|pdf|docx?|xlsx?|pptx?|eot|ttf|otf|woff|svg|ogv|
    # One year cache
    Header always set Cache-Control "max-age=31536000"
</FilesMatch>

# Non-resources
<FilesMatch "(?!\.css|\.js|\.gif|\.jpg|\.jpeg|\.png|\.ico|\.zip|\.pdf|\.doc|\.docx|\.xlsx|\.
    # Five minutes cache
    Header always set Cache-Control "max-age=300"
</FilesMatch>

#####
# Rewrites
#####

<IfModule mod_rewrite.c>
    RewriteEngine On

    #@TODO-YOUR-REDIRECTS
</IfModule>

#####
# Prerender.io
#####

<IfModule mod_headers.c>
    Header always set Cache-Control "max-age=31536000"

```

```
RequestHeader set X-Prerender-Token "@TODO-YOUR-PRENDERIO-TOKEN"
</IfModule>

<IfModule mod_rewrite.c>
    RewriteEngine On

    <IfModule mod_proxy_http.c>
        RewriteCond %{HTTP_USER_AGENT} baiduspider|facebookexternalhit|twitterbot|rogerbot|link:
        RewriteCond %{QUERY_STRING} _escaped_fragment_

        # Only proxy the request to Prerender if it's a request for HTML
        RewriteRule ^(?!.*?
(\.js|\.css|\.xml|\.less|\.png|\.jpg|\.jpeg|\.gif|\.pdf|\.doc|\.txt|\.ico|\.rss|\.zip|\.mp3|
(.*) http://service.prerender.io/http://@TODO-YOUR-HOST/$2 [P,L]
    </IfModule>
</IfModule>
```