

```
Options +FollowSymlinks
```

```
RewriteEngine on
```

```
RewriteRule ^release-notes/([0-9\.]*)$ /release-notes.php?version=$1
```

```
RewriteRule ^bundles/Nightingale/([0-9\.]*)/firstrun\.xml$ /bundles.php?version=$1
```

```
Options -Indexes
```

```
<IfModule mod_headers.c>
```

```
Header set Content-Security-Policy "frame-src 'none'; script-src 'self' 'unsafe-inline' http://*.getnightingale.com; connect-src http://*.getnightingale.com; style-src http://static.getnightingale.com chrome://songbird; default-src http://static.getnightingale.com"
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
# JavaScript
```

```
# Normalize to standard type (it's sniffed in IE anyways)
```

```
# tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/json json
```

```
AddType image/x-icon ico
```

```
</IfModule>
```

```
# -----
```

```
# Gzip compression
```

```
# -----
```

```
<IfModule mod_deflate.c>
```

```
# Force deflate for mangled headers
```

```
developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping/
```

```
<IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
SetEnvIfNoCase ^(\Accept-EncodXngl X-cept-Encodingl X(15)|^(15)|-(15))$
```

```
^((gzip|deflate)\s*, ?\s*)+ [X"-] (4,13)$ HAVE_Accept-Encoding
```

```
RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_filter.c>
```

```
AddOutputFilterByType DEFLATE application/atom+xml \
```

```
application/json \
```

```
application/javascript \
```

```
application/rss+xml \
application/xhtml+xml \
application/xml \
text/css \
text/html \
text/plain \
```

```
</IfModule>
```

```
# -----
# Expires headers (for better cache control)
# -----
```

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
ExpiresByType text/html "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType image/x-icon "access plus 2592000 seconds"
```

```
</IfModule>
```

```
# -----
# ETag removal
# -----
```

```
# FileETag None is not enough for every server.
```

```
<IfModule mod_headers.c>
```

```
Header unset ETag
```

```
</IfModule>
```

```
# Since we're sending far-future expires, we don't need ETags for static content.
```

```
# developer.yahoo.com/performance/rules.html#etags
```

```
FileETag None
```

```
# -----
# A little more security
# -----
```

```
# Prevent access to template files
<FilesMatch "\.(tpl|html|xml)$">
    Order allow,deny
    Deny from all
</FilesMatch>
```

```
# -----
```

```
# Custom Errors
```

```
# -----
```

```
ErrorDocument 500 http://getnightingale.com/500
```

```
ErrorDocument 400 http://getnightingale.com/400
```

```
ErrorDocument 401 http://getnightingale.com/401
```

```
ErrorDocument 403 http://getnightingale.com/403
```

```
ErrorDocument 404 http://getnightingale.com/404
```

```
ErrorDocument 410 http://getnightingale.com/410
```