

```

# -----
# Based on the Contao CMS (contao.org)
# and H5BP (h5bp.com) .htaccess templates
#
# H5BP is licensed under the MIT License (opensource.org/licenses/MIT)
# Contao is licensed under the LGPL (gnu.org/licenses/lgpl-3.0.html)
# -----
<IfModule mod_headers.c>
    # -----
    # CORS
    # -----
    SetEnvIf Origin "^(([a-z0-9\-\]*\.\?getnightingale\.com))$" ORIGIN_SUB_DOMAIN=$1
    Header set Access-Control-Allow-Origin "%{ORIGIN_SUB_DOMAIN}" env=ORIGIN_SUB_DOMAIN

    # -----
    # Prevent framing
    # -----
    Header set X-Frame-Options "ALLOW-FROM %{ORIGIN_SUB_DOMAIN}" env=ORIGIN_SUB_DOMAIN
    Header set Content-Security-Policy "frame-ancestors http://*.getnightingale.com
http://getnightingale.com"
</IfModule>

# -----
# Better website experience for IE users
# -----

# Force the latest IE version, in various cases when it may fall back to IE7 mode
# github.com/rails/rails/commit/123eb25#commitcomment-118920
# Use ChromeFrame if it's installed for a better experience for the poor IE folk
#
# Will not work on fCGI scripts
<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=Edge,chrome=1"
    <FilesMatch "\.(appcache|crx|css|eot|gif|htc|ico|jpe?
gl|js|m4a|m4v|manifest|mp4|oex|ogal|oggl|ogvl|otf|pdf|png|safariextz|svg|svgz|tfl|vcf|webm|webpl
Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# -----
# Disable MIME type sniffing

```

```
# Proper MIME type for all files
```

```
# -----
```

```
<IfModule mod_mime.c>
```

```
  # JavaScript
```

```
  # Normalize to standard type (it's sniffed in IE anyways)
```

```
  # tools.ietf.org/html/rfc4329#section-7.2
```

```
AddType application/javascript      js jsonp
```

```
AddType application/json            json
```

```
  # Audio
```

```
AddType audio/mp4                   m4a f4a f4b
```

```
AddType audio/ogg                   oga ogg
```

```
  # Video
```

```
AddType video/mp4                   mp4 m4v f4v f4p
```

```
AddType video/ogg                   ogv
```

```
AddType video/webm                  webm
```

```
AddType video/x-flv                 flv
```

```
  # SVG
```

```
  # Required for svg webfonts on iPad
```

```
  # twitter.com/FontSquirrel/status/14855840545
```

```
AddType image/svg+xml               svg svgz
```

```
AddEncoding gzip                    svgz
```

```
  # Webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType application/x-font-ttf       ttf ttc
```

```
AddType application/x-font-woff      woff
```

```
AddType font/opentype                otf
```

```
  # Assorted types
```

```
AddType application/octet-stream     safariextz
```

```
AddType application/x-chrome-extension crx
```

```
AddType application/x-opera-extension oex
```

```
AddType application/x-shockwave-flash swf
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType application/x-xpinstall      xpi
```

```
AddType application/xml              rss atom xml rdf
```

```
AddType image/webp                   webp
```

```
-----
```

```
AddType image/x-icon                ico
AddType text/cache-manifest          appcache manifest
AddType text/vtt                     vtt
AddType text/x-component             htc
AddType text/x-vcard                 vcf

AddType application/110n             ini
AddType application/110n             properties
</IfModule>

# BEGIN Turn ETags Off
FileETag None
# END Turn ETags Off

# -----
# Gzip compression
# -----

<IfModule mod_deflate.c>
  # Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-
  <IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
      SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|defl
[X"-]{4,13})$ HAVE_Accept-Encoding
      RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
    </IfModule>
  </IfModule>
</IfModule>

<IfModule mod_filter.c>
  AddOutputFilterByType DEFLATE application/atom+xml \
    application/javascript \
    application/x-javascript \
    application/json \
    application/rss+xml \
    application/vnd.ms-fontobject \
    application/x-font-ttf \
    application/xhtml+xml \
    application/xml \
    font/opentype \
    image/svg+xml \
    image/x-icon \
```

```
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml \  
text/javascript \  
application/110n \  

```

```
</IfModule>
```

```
</IfModule>
```

### *# BEGIN Expire headers*

```
<ifModule mod_expires.c>
```

```
ExpiresActive On
```

```
ExpiresDefault "access plus 5 seconds"
```

```
ExpiresByType image/x-icon "access plus 2592000 seconds"
```

```
ExpiresByType image/jpeg "access plus 2592000 seconds"
```

```
ExpiresByType image/png "access plus 2592000 seconds"
```

```
ExpiresByType image/gif "access plus 2592000 seconds"
```

```
ExpiresByType application/x-shockwave-flash "access plus 2592000 seconds"
```

```
ExpiresByType text/css "access plus 604800 seconds"
```

```
ExpiresByType text/javascript "access plus 216000 seconds"
```

```
ExpiresByType application/javascript "access plus 216000 seconds"
```

```
ExpiresByType application/x-javascript "access plus 216000 seconds"
```

```
ExpiresByType text/html "access plus 600 seconds"
```

```
ExpiresByType application/xhtml+xml "access plus 600 seconds"
```

```
</ifModule>
```

### *# END Expire headers*

### *# BEGIN Cache-Control Headers*

```
<ifModule mod_headers.c>
```

```
<filesMatch "\.(ico|jpe?g|png|gif|swf)$">
```

```
Header set Cache-Control "public"
```

```
</filesMatch>
```

```
<filesMatch "\.(css)$">
```

```
Header set Cache-Control "public"
```

```
</filesMatch>
```

```
<filesMatch "\.(js)$">
```

```
Header set Cache-Control "private"
```

```
</filesMatch>
```

```
<filesMatch "\.(x?html?|php)$">
```

```
Header set Cache-Control "private, must-revalidate"
```

```
</filesMatch>
</ifModule>
# END Cache-Control Headers

# -----
# UTF-8 encoding
# -----

# Use UTF-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force UTF-8 for a number of file formats
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

# -----
# No folder overviews
# -----
Options -Indexes

# -----
# Further header adjustments
# -----

<IfModule mod_headers.c>
    # Add a Vary Accept-Encoding header for the compressed resources. If you
    # modify the file types above, make sure to change them here accordingly.
    # developer.yahoo.com/performance/rules.html#gzip
    <FilesMatch "\.(js|css|xml|gz)$">
        Header append Vary Accept-Encoding
    </FilesMatch>
</IfModule>

# -----
# Custom Errors
# -----
ErrorDocument 500 http://getnightingale.com/500
ErrorDocument 400 http://getnightingale.com/400
ErrorDocument 401 http://getnightingale.com/401
ErrorDocument 403 http://getnightingale.com/403
ErrorDocument 404 http://getnightingale.com/404
ErrorDocument 410 http://getnightingale.com/410
```

