

```
<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    BrowserMatch MSIE ie
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
  </IfModule>
</IfModule>
```

```
<IfModule mod_headers.c>
  Header append Vary User-Agent
</IfModule>
```

```
<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
  <IfModule mod_headers.c>
    Header set Access-Control-Allow-Origin "*"
  </IfModule>
</FilesMatch>
```

Video

```
AddType video/ogg          ogg ogv
AddType video/mp4          mp4
AddType video/webm         webm
```

Proper svg serving. Required for svg webfonts on iPad

```
AddType image/svg+xml     svg svgz
AddEncoding gzip           svgz
```

Webfonts

```
AddType application/vnd.ms-fontobject eot
AddType font/truetype                 ttf
AddType font/opentype                 otf
AddType font/woff                     woff
```

Assorted types

```
AddType image/vnd.microsoft.icon     ico
AddType image/webp                    webp
AddType text/cache-manifest           manifest
AddType text/x-component              htc
AddType application/x-chrome-extension crx
```

GZip compression

```
<IfModule mod_deflate.c>
```

```

<IfModule mod_deflate.c>
    AddOutputFilterByType DEFLATE text/html text/plain text/css application/json
    AddOutputFilterByType DEFLATE text/javascript application/javascript application/x-
javascript
    AddOutputFilterByType DEFLATE text/xml application/xml text/x-component
    <FilesMatch "\.(ttf|otf|eot|svg)$" >
        SetOutputFilter DEFLATE
    </FilesMatch>
</IfModule>

<IfModule mod_expires.c>
    Header set Cache-Control "public"
    ExpiresActive on

# Perhaps better to whitelist expires rules? Perhaps.
    ExpiresDefault                                "access plus 1 month"

# cache.manifest needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
    ExpiresByType text/cache-manifest            "access plus 0 seconds"

# your document html
    ExpiresByType text/html                       "access plus 0 seconds"

# data
    ExpiresByType text/xml                        "access plus 0 seconds"
    ExpiresByType application/xml                 "access plus 0 seconds"
    ExpiresByType application/json               "access plus 0 seconds"

# rss feed
    ExpiresByType application/rss+xml            "access plus 1 hour"

# favicon (cannot be renamed)
    ExpiresByType image/vnd.microsoft.icon       "access plus 1 week"

# media: images, video, audio
    ExpiresByType image/gif                      "access plus 1 month"
    ExpiresByType image/png                      "access plus 1 month"
    ExpiresByType image/jpg                      "access plus 1 month"
    ExpiresByType image/jpeg                    "access plus 1 month"
    ExpiresByType video/ogg                      "access plus 1 month"
    ExpiresByType audio/ogg                     "access plus 1 month"
    ExpiresByType application/javascript         "access plus 1 month"

```

```
ExpiresByType video/mp4                "access plus 1 month"
ExpiresByType video/webm               "access plus 1 month"

# webfonts
ExpiresByType font/truetype            "access plus 1 month"
ExpiresByType font/opentype           "access plus 1 month"
ExpiresByType font/woff                "access plus 1 month"
ExpiresByType image/svg+xml           "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# css and javascript
ExpiresByType text/css                 "access plus 1 month"
ExpiresByType application/javascript   "access plus 1 month"
ExpiresByType text/javascript          "access plus 1 month"
</IfModule>

# Since we're sending far-future expires, we don't need ETags for
# static content.
FileETag None

# Use utf-8 encoding for anything served text/plain or text/html
AddDefaultCharset utf-8

# Force utf-8 for a number of file formats
AddCharset utf-8 .html .css .js .xml .json .rss

# We don't need to tell everyone we're apache.
ServerSignature Off

# Set the application's environment (context). The default one is 'production'
# SetEnv APPLICATION_ENV production

# Enable URL rewriting
RewriteEngine On

# Stop rewrite processing no matter if a resource, robots.txt etc. exists or not
RewriteRule ^(css/|img/|js/|robots\.txt|favicon\.ico|crossdomain\.xml) - [L]

# Stop rewrite process if the path points to a static file/directory anyway
RewriteCond %{REQUEST_FILENAME} -s [OR]
RewriteCond %{REQUEST_FILENAME} -l [OR]
```

```
RewriteCond %{REQUEST_FILENAME} -d  
RewriteRule ^.*$ - [NC,L]
```

Continue only if the file/symlink/directory does not exist

```
RewriteRule ^.*$ index.php [NC,L]
```

```
<IfModule mod_php5.c>
```

```
php_flag magic_quotes_runtime off
```

```
php_flag magic_quotes_gpc off
```

```
php_flag html_errors off
```

```
php_value session.auto_start 0
```

```
php_value output_buffering 4096
```

```
php_value short_open_tag on
```

```
php_value max_execution_time 30
```

```
php_value memory_limit 128M
```

```
php_value default_socket_timeout 60
```

```
</IfModule>
```