

```
php_flag display_errors on
php_flag display_startup_errors on
```

```
AddDefaultCharset utf-8
```

```
<IfModule mod_deflate.c>
  AddOutputFilterByType DEFLATE text/html
  <IfModule mod_setenvif.c>
    BrowserMatch ^Mozilla/4 gzip-only-text/html
    BrowserMatch ^Mozilla/4\.0[678] no-gzip
    BrowserMatch \bMSIE !no-gzip !gzip-only-text/html
  </IfModule>
</IfModule>
```

```
#Использование кеша браузеров;
```

```
FileETag MTime Size
```

```
<IfModule mod_expires.c>
  #Подключение модуля "expires";
  ExpiresActive on
  #ExpiresDefault "access plus 1 month"
  ExpiresByType image/gif "access plus 2 months"
    ExpiresByType image/jpeg "access plus 2 months"
  ExpiresByType image/png "access plus 2 months"
  ExpiresByType image/x-icon "access plus 2 months"
    ExpiresByType text/css "access plus 2 months"
    ExpiresByType text/javascript "access plus 2 months"
</IfModule>
```

```
#Запрет отдачи HTTP-заголовков Vary браузерам семейства MSIE;
```

```
<IfModule mod_setenvif.c>
  BrowserMatch "MSIE" force-no-vary
  BrowserMatch "Mozilla/4.[0-9]{2}" force-no-vary
</IfModule>
```

```
# Перенаправление на gzip файлы
```

```
# gzip watch
```

```
AddEncoding gzip .gz
```

```
<FilesMatch "^\.(\.)*\.js\.gz$">
  ForceType text/javascript
  Header set Content-Encoding gzip
```

```
    header set Content-Encoding: gzip
</FilesMatch>

<FilesMatch "^(.*)\.css\.gz$" >
    ForceType text/css
    Header set Content-Encoding: gzip
</FilesMatch>

<FilesMatch "^(.*)\.js$" >
    RewriteEngine On
    RewriteCond %{HTTP_USER_AGENT} !".*Safari.*"
    RewriteCond %{HTTP:Accept-Encoding} gzip
    RewriteCond %{REQUEST_FILENAME}.gz -f
    RewriteRule ^(.*)\.js$ $1\.js\.gz [L]
    ForceType text/javascript
</FilesMatch>

<FilesMatch "^(.*)\.css$" >
    RewriteEngine On
    RewriteCond %{HTTP_USER_AGENT} !".*Safari.*"
    RewriteCond %{HTTP:Accept-Encoding} gzip
    RewriteCond %{REQUEST_FILENAME}.gz -f
    RewriteRule ^(.*)\.css$ $1\.css\.gz [L]
    ForceType text/css
</FilesMatch>

# =====
```