

[DirectoryIndex](#) index.php

```
<IfModule sapi_apache2.c>
    php_value register_globals      0
    php_value magic_quotes_gpc      0
    php_value magic_quotes_runtime  0
    php_value magic_quotes_sybase   0
    php_value arg_separator.output  "&"
    php_value default_charset       "utf-8"
    php_value session.name          "AK_SESSID"
</IfModule>
```

```
<IfModule mod_php4.c>
    php_value register_globals      0
    php_value magic_quotes_gpc      0
    php_value magic_quotes_runtime  0
    php_value magic_quotes_sybase   0
    php_value arg_separator.output  "&"
    php_value default_charset       "utf-8"
    php_value session.name          "AK_SESSID"
</IfModule>
```

```
# On some servers this directive might be needed
# Options +FollowSymLinks
```

```
# Various rewrite rules
```

```
<IfModule mod_rewrite.c>
    RewriteEngine on
```

```
# If your Akelos Framework application is accessed via an Alias directive,
# then you MUST also set the RewriteBase in this htaccess file.
#
```

```
# Example:
# Alias /myakelosapp /path/to/myakelosapp/public
# RewriteBase /test/fixtures/public
```

```
# If you don't want The Akelos Framework to look in certain directories,
# use the following rewrite rules so that Apache won't rewrite certain requests
#
```

```
# Example:
# RewriteCond %{REQUEST_URI} ^/test/fixtures/
```

```
# RewriteCond %{REQUEST_URI} /notakeios.*  
# RewriteRule .* - [L]
```

```
RewriteRule ^mod_rewrite_test$ mod_rewrite_test_file.txt [L]
```

```
# Rewrite URLs of the form 'index.php?ak=x':
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^(.*)$ index.php?ak=$1 [L,QSA]
```

```
</IfModule>
```

```
ErrorDocument 400 /400.html
```

```
ErrorDocument 500 /500.html
```