

```

<IfModule env_module>
# No GZIP for script-based file downloads.
  SetEnv no-gzip 1
</IfModule>

<IfModule rewrite_module>
# Enable symlinks (required for rewrites).
  Options +FollowSymLinks

# Enable rewrite and configure base.
  RewriteEngine On
  RewriteBase /pab44/

# Initialize all environment variables we're using below.
  RewriteCond %{ENV:s2member_file_download_setup} !^complete$
  RewriteRule ^(.*)$ -
[E=s2member_file_download_wp_vdir: 0,E=s2member_file_download: $1,E=s2member_file_stream: 0,E=:]

# Handle virtual directories, common on multisite networks.
  RewriteCond %{ENV:s2member_file_download_wp_vdir_check} !^complete$
  RewriteCond %{THE_REQUEST} ^(\?: GET| HEAD)(\?: [\ ]+)(\?: /pab44/)([ _0-9a-zA-Z\-\ ]+)(\?: wp-conter
  RewriteRule ^(.*)$ - [E=s2member_file_download_wp_vdir: ,E=s2member_file_download_wp_vdir: ]

# Handle streaming download requests via the rewrite engine.
  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream/)(.+) $
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member

  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-stream-(.+)/)(.+) $
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

# Handle inline file requests via the rewrite engine.
  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline/)(.+) $
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%2,E=s2member

  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-inline-(.+)/)(.+) $
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

# Handle storage specifications via the rewrite engine.
  RewriteCond %{ENV:s2member_file_download} ^(.*)?(?: s2member-file-storage-(.+)/)(.+) $
  RewriteRule ^(.*)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1%3,E=s2member

```

*# Handle remote authorization requests via the rewrite engine.*

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-file-remote/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %2,E=s2member
```

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-file-remote-(. +?)/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %3,E=s2member
```

*# Handle SSL file requests via the rewrite engine.*

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-file-ssl/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %2,E=s2member
```

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-file-ssl-(. +?)/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %3,E=s2member
```

*# Handle file download keys via the rewrite engine.*

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-file-download-key-(. +?)/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %3,E=s2member
```

*# Handle confirmations having been skipped via the rewrite engine.*

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-skip-confirmation/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %2,E=s2member
```

```
RewriteCond %(ENV:s2member_file_download) ^(. *?)(?: s2member-skip-confirmation-(. +?)/)(. +)$  
RewriteRule ^(. *)$ - [N,E=s2member_file_download: ,E=s2member_file_download: %1 %3,E=s2member
```

*# Cleanup variables not used in this request. Looking for `0` values.*

```
RewriteCond %(ENV:s2member_file_download_wp_vdir) ^0$  
RewriteRule ^(. *)$ - [E=s2member_file_download_wp_vdir: ]
```

```
RewriteCond %(ENV:s2member_file_stream) ^0$  
RewriteRule ^(. *)$ - [E=s2member_file_stream: ]
```

```
RewriteCond %(ENV:s2member_file_inline) ^0$  
RewriteRule ^(. *)$ - [E=s2member_file_inline: ]
```

```
RewriteCond %(ENV:s2member_file_storage) ^0$  
RewriteRule ^(. *)$ - [E=s2member_file_storage: ]
```

```
RewriteCond %(ENV:s2member_file_remote) ^0$  
RewriteRule ^(. *)$ - [E=s2member_file_remote: ]
```

```
RewriteCond %(ENV: s2member_file_ssl) ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_ssl: ]
```

```
RewriteCond %(ENV: s2member_file_download_key) ^0$  
RewriteRule ^(.*)$ - [E=s2member_file_download_key: ]
```

```
RewriteCond %(ENV: s2member_skip_confirmation) ^0$  
RewriteRule ^(.*)$ - [E=s2member_skip_confirmation: ]
```

*# Put everything together now and process the internal rewrite.*

```
  RewriteRule ^(.*)$ %(ENV: s2member_file_download_wp_vdir)?s2member_file_download=%(ENV: s2m  
(ENV: s2member_skip_confirmation) [QSA, L]  
</IfModule>
```

```
<IfModule !rewrite_module>  
  <IfModule authz_core_module>  
    Require all denied  
  </IfModule>  
  <IfModule !authz_core_module>  
    deny from all  
  </IfModule>  
</IfModule>
```