

```

#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engine|incl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?|xhtml|svn-
base)$|^(\code-style\.|Entries\.|Repository|Root|Tag|Template|all-
wcprops|entries|format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
    # There is no end quote below, for compatibility with Apache 1.3.
    ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
    php_value magic_quotes_gpc          0
    php_value register_globals          0
    php_value session.auto_start       0
    php_value mbstring.http_input      pass
    php_value mbstring.http_output     pass
    php_value mbstring.encoding_translation 0

```

```
php_value mbstring.encoding_translation 0
</IfModule>
```

*# PHP 4, Apache 2.*

```
<IfModule sapi_apache2.c>
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# PHP 5, Apache 1 and 2.*

```
<IfModule mod_php5.c>
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>
```

*# Requires mod\_expires to be enabled.*

```
<IfModule mod_expires.c>
```

*# Enable expirations.*

```
ExpiresActive On
```

*# Cache all files for 2 weeks after access (A).*

```
ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

*# Do not allow PHP scripts to be cached unless they explicitly send cache  
# headers themselves. Otherwise all scripts would have to overwrite the  
# headers set by mod\_expires if they want another caching behavior. This may  
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.*

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

... ..

```

# Various rewrite rules.
<IfModule mod_rewrite.c>
    RewriteEngine on

    # If your site can be accessed both with and without the 'www.' prefix, you
    # can use one of the following settings to redirect users to your preferred
    # URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
    #
    # To redirect all users to access the site WITH the 'www.' prefix,
    # (http://example.com/... will be redirected to http://www.example.com/...)
    # adapt and uncomment the following:
    # RewriteCond %{HTTP_HOST} ^example\.com$ [NC]
    # RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]
    #
    # To redirect all users to access the site WITHOUT the 'www.' prefix,
    # (http://www.example.com/... will be redirected to http://example.com/...)
    # uncomment and adapt the following:
    # RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]
    # RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]

    # Modify the RewriteBase if you are using Drupal in a subdirectory or in a
    # VirtualDocumentRoot and the rewrite rules are not working properly.
    # For example if your site is at http://example.com/drupal uncomment and
    # modify the following line:
    # RewriteBase /drupal
    #
    # If your site is running in a VirtualDocumentRoot at http://example.com/,
    # uncomment the following line:
RewriteBase /

### BOOST START ###
AddDefaultCharset utf-8
<FilesMatch "(\\.html\\.html\\.gz\\.xml\\.xml\\.gz\\.json\\.json\\.gz)$">
    <IfModule mod_headers.c>
        Header set Expires "Sun, 19 Nov 1978 05:00:00 GMT"
        Header set Cache-Control "no-store, no-cache, must-revalidate, post-check=0, pre-
check=0"
    </IfModule>
</FilesMatch>
<IfModule mod_mime.c>
    AddCharset utf-8 .html

```

```

    AddCharset utf-8 .xml
    AddCharset utf-8 .css
    AddCharset utf-8 .js
    AddCharset utf-8 .json
    AddEncoding gzip .gz
</IfModule>
<FilesMatch "(\\.html|\\.html\\.gz)$">
    ForceType text/html
</FilesMatch>
<FilesMatch "(\\.xml|\\.xml\\.gz)$">
    ForceType text/xml
</FilesMatch>
<FilesMatch "(\\.json|\\.json\\.gz|\\.js|\\.js\\.gz)$">
    ForceType text/javascript
</FilesMatch>
<FilesMatch "(\\.css|\\.css\\.gz)$">
    ForceType text/css
</FilesMatch>

# Gzip Cookie Test
RewriteRule boost-gzip-cookie-test\\.html cache/perm/boost-gzip-cookie-test\\.html\\.gz
[L, T=text/html]

# GZIP - Cached css & js files
RewriteCond %{HTTP_COOKIE} !(boost-gzip)
RewriteCond %{HTTP: Accept-encoding} !gzip
RewriteRule .* - [S=2]
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.css\\.gz -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.css\\.gz [L, QSA, T=text/css]
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.js\\.gz -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.js\\.gz [L, QSA, T=text/javascript]

# NORMAL - Cached css & js files
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.css -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.css [L, QSA, T=text/css]
RewriteCond %{DOCUMENT_ROOT}/cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.js -s
RewriteRule .* cache/perm/%{SERVER_NAME}%{REQUEST_URI}_\\.js [L, QSA, T=text/javascript]

# Caching for anonymous users
# Skip boost IF not get request OR uri has wrong dir OR cookie is set OR request came
from this server OR https request

```

```

RewriteCond %{REQUEST_METHOD} !^(GET|HEAD)$ [OR]
RewriteCond %{REQUEST_URI}
(^/(admin|cache|misc|modules|sites|system|openid|themes|node/add)|
/(comment/reply|edit|user/user/(login|password|register)))$ [OR]
RewriteCond %{HTTP_COOKIE} DRUPAL_UID [OR]
RewriteCond %{HTTP:Pragma} no-cache [OR]
RewriteCond %{HTTP:Cache-Control} no-cache [OR]
RewriteCond %{HTTPS} on
RewriteRule .* - [S=7]

# GZIP
RewriteCond %{HTTP_COOKIE} !(boost-gzip)
RewriteCond %{HTTP:Accept-encoding} !gzip
RewriteRule .* - [S=3]
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{
QUERY_STRING}\.html\..gz -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html\..gz
[L,T=text/html]
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{
QUERY_STRING}\.xml\..gz -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.xml\..gz
[L,T=text/xml]
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{
QUERY_STRING}\.json\..gz -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.json\..gz
[L,T=text/javascript]

# NORMAL
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{
QUERY_STRING}\.html -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.html
[L,T=text/html]
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{
QUERY_STRING}\.xml -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.xml
[L,T=text/xml]
RewriteCond %{DOCUMENT_ROOT}/cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{
QUERY_STRING}\.json -s
RewriteRule .* cache/normal/%{SERVER_NAME}%{REQUEST_URI}_%{QUERY_STRING}\.json
[L,T=text/javascript]

```

```
### BOOST END ###
```

```
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !=/favicon.ico
```

```
RewriteRule ^(.*)$ index.php?q=$1 [L,QSA]
```

```
</IfModule>
```

```
# $Id: .htaccess,v 1.90.2.5 2010/02/02 07:25:22 dries Exp $
```