```
#   BULLETPROOF .47.8 MAINTENANCE  .HTACCESS

# BEGIN WordPress

RewriteEngine On
RewriteBase /

# REQUEST METHODS FILTERED
RewriteEngine On
RewriteCond %{REQUEST_METHOD} ^(HEAD|TRACE|DELETE|TRACK|DEBUG) [NC]
RewriteRule ^(.*)$ - [F,L]

# TIMTHUMB FORBID RFI BY HOST NAME BUT ALLOW INTERNAL REQUESTS
RewriteCond %{QUERY_STRING} ^.*(http|https|ftp)(%3A|:)(%2F|/)(%2F|/)(w){0,3}.?
(blogger|picasa|blogspot|tsunami|petapolitik|photobucket|imgur|imageshack|wordpress\.com|img
thegame).*$ [NC,OR]
RewriteCond %{THE_REQUEST} ^.*(http|https|ftp)(%3A|:)(%2F|/)(%2F|/)(w){0,3}.?
(blogger|picasa|blogspot|tsunami|petapolitik|photobucket|imgur|imageshack|wordpress\.com|img
thegame).*$ [NC]
RewriteRule .* index.php [F,L]
RewriteCond %{REQUEST_URI} (timthumb\.php|phpthumb\.php|thumb\.php|thumbs\.php) [NC]
RewriteRule . - [S=1]

# BPSQSE BPS QUERY STRING EXPLOITS
RewriteCond %{HTTP_USER_AGENT} (%0A|%0D|%27|%3C|%3E|%00) [NC,OR]
RewriteCond %{HTTP_USER_AGENT} (libwww-
perl|wget|python|nikto|curl|scan|java|winhttp|HTTrack|clshttp|archiver|loader|email|harvest|
RewriteCond %{THE_REQUEST} \?\ HTTP/ [NC,OR]
RewriteCond %{THE_REQUEST} \/\*\ HTTP/ [NC,OR]
RewriteCond %{THE_REQUEST} etc/passwd [NC,OR]
RewriteCond %{THE_REQUEST} cgi-bin [NC,OR]
RewriteCond %{THE_REQUEST} (%0A|%0D) [NC,OR]
RewriteCond %{REQUEST_URI} owssvr\.dll [NC,OR]
RewriteCond %{HTTP_REFERER} (%0A|%0D|%27|%3C|%3E|%00) [NC,OR]
RewriteCond %{HTTP_REFERER} \.opendirviewer\. [NC,OR]
RewriteCond %{HTTP_REFERER} users\.skynet\.be.* [NC,OR]
RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=http:// [OR]
RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=(\.\.//?)+ [OR]
RewriteCond %{QUERY_STRING} [a-zA-Z0-9_]=/([a-z0-9_.]//?)+ [NC,OR]
RewriteCond %{QUERY_STRING} \=PHP[0-9a-f]{8}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{4}-[0-9a-f]{12
RewriteCond %{QUERY_STRING} (\.\.//?)+ [OR]
```

```
RewriteCond %{QUERY_STRING} \.\.//|\.\.) [OR]
RewriteCond %{QUERY_STRING} ftp\: [NC,OR]
RewriteCond %{QUERY_STRING} http\: [NC,OR]
RewriteCond %{QUERY_STRING} https\: [NC,OR]
RewriteCond %{QUERY_STRING} \=\|w\| [NC,OR]
RewriteCond %{QUERY_STRING} ^(.*)/self/(.*)$ [NC,OR]
RewriteCond %{QUERY_STRING} ^(.*)cPath=http://(.*)$ [NC,OR]
RewriteCond %{QUERY_STRING} (\<|%3C).*script.*(\>|%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|%3C)([^s]*s)+cript.*(>|%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (\<|%3C).*iframe.*(\>|%3E) [NC,OR]
RewriteCond %{QUERY_STRING} (<|%3C)([^i]*i)+frame.*(>|%3E) [NC,OR]
RewriteCond %{QUERY_STRING} base64_encode.*\(.*\) [NC,OR]
RewriteCond %{QUERY_STRING} base64_(en|de)code[^(]*\([^)]*\) [NC,OR]
RewriteCond %{QUERY_STRING} GLOBALS(=|\[|\%[0-9A-Z]{0,2}) [OR]
RewriteCond %{QUERY_STRING} _REQUEST(=|\[|\%[0-9A-Z]{0,2}) [OR]
RewriteCond %{QUERY_STRING} ^.*(\(|\)|<|>).* [NC,OR]
RewriteCond %{QUERY_STRING} (NULL|OUTFILE|LOAD_FILE) [OR]
RewriteCond %{QUERY_STRING} (\./|\../|\.../)+(motd|etc|bin) [NC,OR]
RewriteCond %{QUERY_STRING} (localhost|loopback|127\.0\.0\.1) [NC,OR]
RewriteCond %{QUERY_STRING} (<|>|'|%0A|%0D|%27|%3C|%3E|%00) [NC,OR]
RewriteCond %{QUERY_STRING} concat[^\(]*\( [NC,OR]
RewriteCond %{QUERY_STRING} union([^s]*s)+elect [NC,OR]
RewriteCond %{QUERY_STRING} union([^a]*a)+ll([^s]*s)+elect [NC,OR]
RewriteCond %{QUERY_STRING} (;|<|>|'|"|\)|%0A|%0D|%22|%27|%3C|%3E|%00).*
(/\*|union|select|insert|drop|delete|update|cast|create|char|convert|alter|declare|order|scr
RewriteCond %{QUERY_STRING} (sp_executesql) [NC]
RewriteRule ^(.*)$ - [F,L]

RewriteCond %{REMOTE_ADDR} !^88\.55\.66\.200$
RewriteCond %{REQUEST_URI} !^/bp-maintenance\.php$
RewriteCond %{REQUEST_URI} !^/wp-content/plugins/bulletproof-security/abstract-blue-bg\.pngS
RewriteRule ^(.*)$ /bp-maintenance.php [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
```