

```
#####
# This file is part of the CarteBlanche PHP framework.
#
# (c) Pierre Cassat <me@e-piwi.fr> and contributors
#
# License Apache-2.0 <http://github.com/php-carteblanche/carteblanche/blob/master/LICENSE>
# For the full copyright and license information, please view the LICENSE
# file that was distributed with this source code.
#####

# try to extract relative path from DOCUMENT_ROOT
<IfModule env_module>
    SetEnv RelativePath %{REQUEST_URI}
</IfModule>

# no indexing
<IfModule mod_autoindex.c>
    Options All -Indexes
</IfModule>

# force directory index to PHP index
<IfModule dir_module>
    DirectoryIndex index.php index.html
</IfModule>

# default charset is UTF-8
AddDefaultCharset utf-8

# follow symbolic links
Options +FollowSymLinks

# setting authentication
<IfModule auth>
    AuthType Basic
    AuthName "CarteBlanche Authentication"

    # 'secure.php' will be secured by htpasswd if you define the good path here:
    # see <http://httpd.apache.org/docs/2.0/mod/mod_auth.html>
    AuthUserFile carteblanche/www/.htpasswd
    AuthGroupFile /dev/null
    <File "secure.php">
```

```
<files secure.php >
    AuthName "CarteBlanche Secured Authentication"
    require valid-user
</Files>
</IfModule>

# setting the error pages
ErrorDocument 403 /index.php?forbidden
ErrorDocument 404 /index.php?not_found
ErrorDocument 500 /index.php?error

# php settings
<IfModule mod_php5.c>
    php_value upload_max_filesize 513M
    php_value post_max_size 513M
    php_value memory_limit 512M
    php_value mbstring.func_overload 0
    <IfModule env_module>
        SetEnv htaccessWorking true
    </IfModule>
</IfModule>

# the rewrite URLs rules
<IfModule mod_rewrite.c>
    RewriteEngine On
    #RewriteBase /

    # no access to anything beginning with a dot
    RewriteRule ^(, */)?\.(, *)/ - [F]

    # Explicitly disable rewriting for front controllers
    RewriteRule ^(dev|index|webservices|dev_webservices|secure).php - [L]

    # Explicitly disable rewriting for assets
    RewriteRule ^(assets\|vendor\|) - [L]

    # special Apache environment variables debugger
    Options +ExecCGI
    AddHandler cgi-script .sh
    RewriteRule ^apache-debug /WORK/carteblanche_test/www/cgi-scripts/apacheDebugger.sh [L]

    # ...

```

```
# skip all this if the file or the dir exists
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
# rebuild `xxx.php/myreq` to `xxx.php?myreq`
RewriteRule ^([a-zA-Z0-9\-\_]+)\.php\/(.*)$ $1.php?$2 [QSA,L]
# `index.php` will handle all requests
RewriteRule ^(.*)$ index.php?$1 [QSA,L]
#RewriteRule ^(.*)$ dev.php?$1 [QSA,L]
#RewriteRule ^(.*)$ webservice.php?$1 [QSA,L]
#RewriteRule ^(.*)$ dev_webservice.php?$1 [QSA,L]
</IfModule>
```