

```

# $Id: .htaccess,v 1.5 2005/05/19 17:09:19 Administrator Exp $
#
# This is used with Apache WebServers
#
# For this to work, you must include the parameter 'Options' to
# the AllowOverride configuration
#
# Example:
#
#<Directory "/usr/local/apache/htdocs">
#   AllowOverride Options
#</Directory>
#
# 'All' will also work. (This configuration is in the
# apache/conf/httpd.conf file)
# The following makes adjustments to the SSL protocol for Internet
# Explorer browsers

<IfModule mod_setenvif.c>
  <IfDefine SSL>
    SetEnvIf User-Agent ". *MSIE. *" \
      nokeepalive ssl-unclean-shutdown \
      downgrade-1.0 force-response-1.0
  </IfDefine>
</IfModule>

# Fix certain PHP values
# (commented out by default to prevent errors occurring on certain
# servers)
#<IfModule mod_php4.c>
#   php_value session.use_trans_sid 0
#   php_value register_globals 1
#</IfModule>

# -----
# Proper MIME type for all files
# -----

# JavaScript
#   Normalize to standard type (it's sniffed in IE anyways)
#   text/javascript; charset=utf-8; access=deny

```

```

# tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript      js

# Audio
AddType audio/ogg                   oga ogg
AddType audio/mp4                    m4a

# Video
AddType video/ogg                     ogv
AddType video/mp4                     mp4 m4v
AddType video/webm                     webm

# SVG
# Required for svg webfonts on iPad
# twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml                 svg svgz
AddEncoding gzip                       svgz

# Webfonts
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf         ttf ttc
AddType font/opentype                  otf
AddType application/x-font-woff        woff

# Assorted types
AddType image/x-icon                   ico
AddType image/webp                     webp
AddType text/cache-manifest            appcache manifest
AddType text/x-component               htc
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall        xpi
AddType application/octet-stream       safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard                   vcf

<IfModule mod_gzip.c>
    mod_gzip_on      Yes
    mod_gzip_dechunk Yes
    mod_gzip_item_include file      \.(html?|txt|css|js|php|pl)$
    mod_gzip_item_include handler    ^cgi-script$
    . . . . .
    ^ . . .

```



```

ExpiresByType application/json "access plus 0 seconds"

# Feed
ExpiresByType application/rss+xml "access plus 1 hour"
ExpiresByType application/atom+xml "access plus 1 hour"

# Favicon (cannot be renamed)
ExpiresByType image/x-icon "access plus 1 month"

# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpg "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType font/truetype "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css "access plus 0 seconds"
ExpiresByType application/javascript "access plus 0 seconds"

<IfModule mod_headers.c>
    Header append Cache-Control "public"
</IfModule>

</IfModule>

# BEGIN Turn E-Tags Off
<IfModule mod_headers.c>

```

```
Header unset ETag
</IfModule>

# Speed up caching
FileETag MTime Size
# END Turn E-Tags Off

RewriteEngine on

RewriteCond %{REQUEST_FILENAME} ^(\.)*\.(php|css|js|gif|jpg|jpeg|png)$ [NC]
RewriteRule ^(\.+) - [L]

RewriteCond %{REQUEST_URI} (.*)?/admin/(.*)
RewriteRule ^(\.+) - [L]

RewriteCond %{REQUEST_URI} (.*)?/images/(.*)
RewriteRule ^(\.+) - [L]

RewriteCond %{REQUEST_URI} (.*)?/templates/(.*)
RewriteRule ^(\.+) - [L]

RewriteCond %{REQUEST_FILENAME} -d
RewriteRule ^(\.+) - [L]

RewriteCond %{REQUEST_FILENAME} -f
RewriteRule ^(\.+) - [L]

RewriteCond %{REQUEST_FILENAME} -l
RewriteRule ^(\.+) - [L]

##boosted CONTENT
RewriteRule (.*)?info/([A-Za-z0-9_-]+)\.html.*shop_content.php?gm_boosted_content=$2&%
{QUERY_STRING} [PT,L]

##boosted PRODUCTS
RewriteRule (.*)?([A-Za-z0-9_-]+)\.html_product_info.php?gm_boosted_product=$2&%
{QUERY_STRING} [PT,L]

##boosted CATEGORIES
RewriteRule (.*)?([A-Za-z0-9_-]+)/?.*index.php?gm_boosted_category=$2&%(QUERY_STRING)
[L]
```

