

```
# Apache configuration file
```

```
# Serve this site as PHP 5 - Media Temple requirement
```

```
AddHandler php5-script .php
```

```
# Force the latest IE version
```

```
<IfModule mod_setenvif.c>
```

```
  <IfModule mod_headers.c>
```

```
    BrowserMatch MSIE ie
```

```
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
```

```
  </IfModule>
```

```
</IfModule>
```

```
# allow access from all domains for webfonts
```

```
<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
```

```
  <IfModule mod_headers.c>
```

```
    Header set Access-Control-Allow-Origin "*"
```

```
  </IfModule>
```

```
</FilesMatch>
```

```
# video
```

```
AddType video/ogg ogg ogv
```

```
AddType video/mp4 mp4
```

```
AddType video/webm webm
```

```
# Proper svg serving. Required for svg webfonts on iPad
```

```
AddType image/svg+xml          svg svgz
```

```
# webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType font/ttf                    ttf
```

```
AddType font/otf                    otf
```

```
AddType font/x-woff                 woff
```

```
AddType text/cache-manifest         manifest
```

```
# gzip compression.
```

```
<IfModule mod_deflate.c>
```

```
# html, xml, css, and js:
```

```
  AddOutputFilterByType DEFLATE text/html text/css text/javascript
```

```
Header set cache-control: public
Header set expires: 30
Header set expires-active: on
Header set expires-default: "access plus 1 month"
Header set expires-by-type: text/html "access"
Header set expires-by-type: text/css "access plus 1 month"
Header set expires-by-type: application/javascript "access plus 1 month"
Header set expires-by-type: application/json
```

```
# webfonts and svg:
```

```
<FilesMatch "\.(ttf|otf|eot|svg)$" >
    SetOutputFilter DEFLATE
</FilesMatch>
</IfModule>
```

```
# Expiration headers
```

```
<IfModule mod_expires.c>
    Header set cache-control: public
    ExpiresActive on
    ExpiresDefault "access plus 1 month"
```

```
# cache.manifest needs re-requests in FF 3.6 (thx Remy "Introducing HTML5")
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

```
# your document html
```

```
ExpiresByType text/html "access"
```

```
# rss feed
```

```
ExpiresByType application/rss+xml "access plus 1 hour"
```

```
# favicon (cannot be renamed)
```

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
```

```
# media: images, video, audio
```

```
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType image/jpg "access plus 1 month"
```

```
ExpiresByType image/jpeg "access plus 1 month"
```

```
ExpiresByType video/ogg "access plus 1 month"
```

```
ExpiresByType audio/ogg "access plus 1 month"
```

```
ExpiresByType video/mp4 "access plus 1 month"
```

```
# webfonts
```

```
ExpiresByType font/ttf "access plus 1 month"
```

```
ExpiresByType font/woff "access plus 1 month"
```

```
ExpiresByType image/svg+xml "access plus 1 month"
```

```
# css and javascript
```

```
ExpiresByType text/css "access plus 1 month"
```

```
ExpiresByType text/css                "access plus 1 month"
ExpiresByType application/javascript  "access plus 1 month"
ExpiresByType text/javascript         "access plus 1 month"
</IfModule>
```

```
# Don't need ETags for static content.
FileETag None
```

```
# no www
```

```
RewriteEngine On
```

```
# RewriteCond %{HTTP_HOST} ^www\. (.+)$ [NC]
```

```
# RewriteRule ^(.*)$ http://%1/$1 [R=301,L]
```

```
# sexy URLs aka http://example.com/page instead of page.php
```

```
Options +FollowSymLinks
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteBase /
```

```
RewriteRule ^(\w+)$ $1.php [L]
```

```
# without -MultiViews, Apache will give a 404 for a rewrite if a folder of the same name
does not exist (e.g. "/blog/hello")
```

```
Options -MultiViews
```

```
# block users from browsing folders without a default document
```

```
Options -Indexes
```

```
# custom 404 page
```

```
# ErrorDocument 404 /404.html
```

```
# use utf-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# force utf-8 for a number of file formats
```

```
AddCharset utf-8 .html .css .js .xml .json .rss
```