

```

# Set default charset utf-8
AddDefaultCharset UTF-8

# Block access to directories without a default document.
# You should leave the following uncommented, as you shouldn't allow anyone to
# surf through every directory on your server (which may includes rather private
# places such as the CMS's directories).
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# PHP 5, Apache 1 and 2
<IfModule mod_php5.c>
    php_flag magic_quotes_gpc off
    php_flag magic_quotes_sybase off
    php_flag register_globals off
</IfModule>

# Force Internet Explorer to render pages in the highest available mode
# in the various cases when it may not.
# http://hsivonen.iki.fi/doctype/ie-mode.pdf
<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"
    # `mod_headers` cannot match based on the content-type, however, this
    # header should be send only for HTML pages and not for the other resources
    <FilesMatch "\.(appcache|atom|crx|css|curl|eot|f4[abpv]|flv|gif|html|icol|jpe?
gl|js|json|ld)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rssi|safariextz|svgz?
|swf|tt[cf]|vcf|vtt|webapp|web[mp]|woff|xml|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# Prevent viewing of .htaccess file
<Files ~ "^\.ht">
    Order allow,deny
    Deny from all
    Satisfy all
</Files>

# ---

```

```
# gzip
<ifModule mod_gzip.c>
    mod_gzip_on Yes
    mod_gzip_dechunk Yes
    mod_gzip_item_include file \.(css|eot|html?|js|md|php|pl|ttf|txt|woff)$
    mod_gzip_item_include handler ^cgi-script$
    mod_gzip_item_include mime ^text/. *
    mod_gzip_item_include mime ^application/. *
    mod_gzip_item_exclude mime ^image/. *
    mod_gzip_item_exclude rspheader ^Content-Encoding:.*gzip.*
</ifModule>
```

```
# The following expires headers are set pretty far in the future. If you
# don't control versioning with filename-based cache busting, consider
# lowering the cache time for resources such as style sheets and JavaScript
# files to something like one week.
```

```
<IfModule mod_expires.c>

    ExpiresActive on
    ExpiresDefault "access plus 1 month"

# CSS
    ExpiresByType text/css "access plus 1 year"

# Data interchange
    ExpiresByType application/json "access plus 0 seconds"
    ExpiresByType application/ld+json "access plus 0 seconds"
    ExpiresByType application/xml "access plus 0 seconds"
    ExpiresByType text/xml "access plus 0 seconds"

# Favicon (cannot be renamed!) and cursor images
    ExpiresByType image/x-icon "access plus 1 week"

# HTML components (HTCs)
    ExpiresByType text/x-component "access plus 1 month"

# HTML
    ExpiresByType text/html "access plus 0 seconds"

# JavaScript
    ExpiresByType application/javascript "access plus 1 year"
```

### # Manifest files

```
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"  
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

### # Media

```
ExpiresByType audio/ogg "access plus 1 month"  
ExpiresByType image/gif "access plus 1 month"  
ExpiresByType image/jpeg "access plus 1 month"  
ExpiresByType image/png "access plus 1 month"  
ExpiresByType video/mp4 "access plus 1 month"  
ExpiresByType video/ogg "access plus 1 month"  
ExpiresByType video/webm "access plus 1 month"
```

### # Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"  
ExpiresByType application/rss+xml "access plus 1 hour"
```

### # Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"  
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"  
ExpiresByType application/x-font-ttf "access plus 1 month"  
ExpiresByType font/opentype "access plus 1 month"  
ExpiresByType image/svg+xml "access plus 1 month"
```

</IfModule>

<IfModule mod\_rewrite.c>

```
RewriteEngine on  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteRule ^(.*)$ index.php?$1 [L, QSA]
```

</IfModule>