

```
## Help our users by allowing them to write sample names and forward them to our
Sample.html file.
# Parts of this excerpted from _ michael @
# http://www.zeilenwechsel.de/it/articles/8/Using-mod_rewrite-in-.htaccess-files-without-
knowing-the-RewriteBase.html
<IfModule rewrite_module>
RewriteEngine on
RewriteBase /

# Store the current location in an environment variable CWD
RewriteCond $0#%(REQUEST_URI) ([^#]*)#(.*)\1$
RewriteRule ^.*$ - [E=CWD:%2]

RewriteCond %(REQUEST_FILENAME) !-f
RewriteRule ^index\..html?$ %(ENV:CWD)Sample.html?All [R,QSA,L]

RewriteCond %(REQUEST_FILENAME) -d
RewriteCond %(REQUEST_FILENAME)index.html !-f [NC]
RewriteRule .* %(ENV:CWD)Sample.html?All [R,QSA,L]

# verify that we're only looking for files ending in htm(1) that don't exist
RewriteCond %(REQUEST_FILENAME) !-f
RewriteCond %(REQUEST_FILENAME) \..html?$ [or]
RewriteCond %(REQUEST_FILENAME) !\.

# Just by prefixing the environment variable, we can safely rewrite anything now
RewriteRule ([^/]+?)(\..html)?$ %(ENV:CWD)Sample.html?$1 [R,L]
</IfModule>
```