

```
#  
# Flow context setting  
#  
  
# You can specify a default context by activating this option:  
# SetEnv FLOW_CONTEXT Production  
  
# If the root path is not the parent of the Web directory,  
# Flow's root path must be specified manually:  
# SetEnv FLOW_ROOTPATH /var/www/myapp/  
  
#  
# mod_rewrite configuration  
#  
<IfModule mod_rewrite.c>  
  
# Enable URL rewriting  
RewriteEngine On  
  
# Set flag so we know URL rewriting is available  
SetEnv FLOW_REWRITEURLS 1  
  
# You will have to change the path in the following option if you  
# experience problems while your installation is located in a subdirectory  
# of the website root.  
RewriteBase /  
  
# Stop rewrite processing no matter if a package resource, robots.txt etc. exists or not  
RewriteRule ^(_Resources/Packages/|robots\.txt|favicon\.ico) - [L]  
  
# Stop rewrite process if the path points to a static file anyway  
RewriteCond %{REQUEST_FILENAME} -f [OR]  
RewriteCond %{REQUEST_FILENAME} -l [OR]  
RewriteCond %{REQUEST_FILENAME} -d  
RewriteRule .* - [L]  
  
# Make sure that not existing resources don't execute Flow  
RewriteRule ^_Resources/. * - [L]  
  
# Continue only if the file/symlink/directory does not exist  
RewriteRule /.* -> /index.php
```

```
    RewriteRule (.*) index.php
```

```
</IfModule>
```

```
<IfModule mod_negotiation.c>
```

```
    # prevents Apache's automatic file negotiation, it breaks resource URLs
```

```
    Options -MultiViews
```

```
</IfModule>
```

```
<IfModule mod_setenvif.c>
```

```
    # Redirect authorization header when PHP is running as CGI
```

```
    SetEnvIfNoCase Authorization "Basic ([a-zA-Z0-9\+/=]+)" REMOTE_AUTHORIZATION=$0
```

```
</IfModule>
```

```
ErrorDocument 500 "<h1>Application Error</h1><p>The TYPO3 Flow application could not be  
launched.</p>"
```