

```
# vim: syntax=apache tabstop=4 softtabstop=0 noexpandtab laststatus=1 ruler
```

```
# suppress php errors
```

```
php_flag display_startup_errors off
```

```
php_flag display_errors off
```

```
php_flag html_errors off
```

```
# enable PHP error logging
```

```
php_flag log_errors on
```

```
php_value error_log /opt/unetlab/data/Logs/php_errors.txt
```

```
# PHP settings
```

```
php_value session.gc_maxlifetime 86400
```

```
# TODO
```

```
# ErrorDocument 403 /error.php
```

```
<IfModule mod_rewrite.c>
```

```
# http://httpd.apache.org/docs/2.4/rewrite/flags.html
```

```
RewriteEngine On
```

```
RewriteBase /
```

```
# If starts with /api, call API router
```

```
RewriteCond %{REQUEST_URI} ^/api/
```

```
RewriteRule ^(.*)$ /api.php [B,L,QSA]
```

```
# If starts with /auth, call Dpauth
```

```
RewriteCond %{REQUEST_URI} ^/auth/
```

```
RewriteRule ^(.*)$ /auth.php [B,L,QSA]
```

```
# If not an auth call, if not a dir and if not a file, call the theme
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteRule ^(.*)$ /themes/default/$1 [B,L,QSA]
```

```
# If URL is empty, call the theme
```

```
RewriteRule ^$ /themes/default/ [B,L,QSA]
```

```
</IfModule>
```