```
#######################################################
#
#   THIS FILE SHOULD BE PLACED IN YOUR CSS DIRECTORY
#
#######################################################

<IfModule mod_deflate.c>
  SetOutputFilter DEFLATE
</IfModule>

<IfModule mod_expires.c>
  ExpiresActive on
  ExpiresDefault "access plus 10 years"
</IfModule>

# To enable invisible parsing of your css, you need to change the path
# below to find your scaffold/index.php file.
#
# By default, Scaffold should be placed in your CSS directory. You should
# place this .htaccess file in the same directory. If you're setup is
# fairly average, this should work out of the box.
#
# Now, rather than calling http://site.com/css/scaffold/index.php?request=css/master.css
# you can just call http://site.com/css/master.css and this htaccess file will
# take care of the routing for you.

<IfModule mod_rewrite.c>
  RewriteEngine  on

  # Anything after .css is used as the output=
  RewriteCond %{REQUEST_URI}         ^.*css$
  RewriteRule ^(.+)/([^/]+)/?$       scaffold/index.php?request=%{REQUEST_URI}&output=$2&%
{QUERY_STRING}

  RewriteCond %{REQUEST_FILENAME}    -f
  RewriteCond %{REQUEST_URI}         ^.*css$
  RewriteRule ^(.+)$                 scaffold/index.php?request=%{REQUEST_URI}&%
{QUERY_STRING}
</IfModule>
```