

```

RewriteEngine on
#Force non-www:
RewriteCond %{HTTP_HOST} www.(.*)$ [NC]
RewriteRule ^(.*)$ https://stripecon.eu/$1 [R=301,L]

RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]

<IfModule mod_setenvif.c>
  <IfModule mod_headers.c>
    <FilesMatch "\.(bmp|curl|gif|ico|jpe?g|png|svgz?|webp)$">
      SetEnvIf Origin ":" IS_CORS
      Header set Access-Control-Allow-Origin "*" env=IS_CORS
    </FilesMatch>
  </IfModule>
</IfModule>
<IfModule mod_headers.c>
  <FilesMatch "\.(eot|otf|tt[cf]|woff2?)$">
    Header set Access-Control-Allow-Origin "*"
  </FilesMatch>
</IfModule>
<IfModule mod_headers.c>
  Header set X-UA-Compatible "IE=edge"
  <FilesMatch "\.
  (appcache|atom|bbaw|bmp|crx|css|curl|eot|f4[abpv]|flv|geojson|gif|htc|ico|jpe?
  g|jsl|json|ld)?
  |m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdfl|rss|safariextz|svgz?
  |swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|webmanifest|woff2?|xloc|xml|xpi)$">
    Header unset X-UA-Compatible
  </FilesMatch>
</IfModule>
<IfModule mod_mime.c>

# Data interchange

AddType application/atom+xml atom
AddType application/json json map topojson
AddType application/ld+json jsonld
AddType application/rss+xml rss
AddType application/vnd.geo+json geojson
AddType application/xml rdf xml

```

JavaScript

Normalize to standard type.

<https://tools.ietf.org/html/rfc4329#section-7.2>

```
AddType application/javascript js
```

Manifest files

```
AddType application/manifest+json webmanifest
```

```
AddType application/x-web-app-manifest+json webapp
```

```
AddType text/cache-manifest appcache
```

Media files

```
AddType audio/mp4 f4a f4b m4a
```

```
AddType audio/ogg oga ogg opus
```

```
AddType image/bmp bmp
```

```
AddType image/svg+xml svg svgz
```

```
AddType image/webp webp
```

```
AddType video/mp4 f4v f4p m4v mp4
```

```
AddType video/ogg ogv
```

```
AddType video/webm webm
```

```
AddType video/x-flv flv
```

Serving `.ico` image files with a different media type

prevents Internet Explorer from displaying them as images:

[https://github.com/h5bp/html5-](https://github.com/h5bp/html5-boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee)

[boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee](https://github.com/h5bp/html5-boilerplate/commit/37b5fec090d00f38de64b591bcddcb205aadf8ee)

```
AddType image/x-icon cur ico
```

Web fonts

```
AddType application/font-woff woff
```

```
AddType application/font-woff2 woff2
```

```
AddType application/vnd.ms-fontobject eot
```

Browsers usually ignore the font media types and simply sniff

the bytes to figure out the font type.

""" https://www.ietf.org/rfc/rfc4329.html#section-7.2 """

```
# https://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern
#
# However, Blink and WebKit based browsers will show a warning
# in the console if the following font types are served with any
# other media types.
```

```
AddType application/x-font-ttf          ttc ttf
AddType font/opentype                    otf
```

```
# Other
```

```
AddType application/octet-stream       safariextz
AddType application/x-bb-appworld       bbaw
AddType application/x-chrome-extension  crx
AddType application/x-opera-extension   oex
AddType application/x-xpinstall         xpi
AddType text/vcard                       vcard vcf
AddType text/vnd.rim.location.xloc      xloc
AddType text/vtt                          vtt
AddType text/x-component                 htc
```

```
</IfModule>
```

```
AddDefaultCharset utf-8
```

```
<IfModule mod_mime.c>
```

```
    AddCharset utf-8 .atom \
                .bbaw \
                .css \
                .geojson \
                .js \
                .json \
                .jsonld \
                .manifest \
                .rdf \
                .rss \
                .topojson \
                .vtt \
                .webapp \
                .webmanifest \
                .xloc \
                .xml
```

```
</IfModule>
```

```

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>
<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteCond %{REQUEST_URI} "!(^/)\.well-known/([^. /]+/?)+$" [NC]
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>
<FilesMatch "(^#\.#\.(bak|conf|dist|fla|in[ci]|log|psd|sh|sql|sw[op])|")$">

    # Apache < 2.3
    <IfModule !mod_authz_core.c>
        Order allow,deny
        Deny from all
        Satisfy All
    </IfModule>

    # Apache ≥ 2.3
    <IfModule mod_authz_core.c>
        Require all denied
    </IfModule>

</FilesMatch>
<IfModule mod_headers.c>
    Header set X-Content-Type-Options "nosniff"
</IfModule>
<IfModule mod_headers.c>
    Header unset X-Powered-By
</IfModule>
ServerSignature Off
<IfModule mod_deflate.c>

    # Force compression for mangled `Accept-Encoding` request headers
    # https://developer.yahoo.com/blogs/ydn/pushing-beyond-gzipping-25601.html

    <IfModule mod_setenvif.c>
        <IfModule mod_headers.c>
            SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
            ^((gzip|deflate)\s*,?\s*)+([X"]-){4,13}$ HAVE_Accept-Encoding

```

```
RequestHeader append Accept-Encoding "gzip, deflate" env=HAVE_Accept-Encoding
</IfModule>
</IfModule>

# -----

# Compress all output labeled with one of the following media types.
#
# (!) For Apache versions below version 2.3.7 you don't need to
# enable `mod_filter` and can remove the `<IfModule mod_filter.c>`
# and `</IfModule>` lines as `AddOutputFilterByType` is still in
# the core directives.
#
# https://httpd.apache.org/docs/current/mod/mod\_filter.html#addoutputfilterbytype

<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE "application/atom+xml" \
        "application/javascript" \
        "application/json" \
        "application/ld+json" \
        "application/manifest+json" \
        "application/rdf+xml" \
        "application/rss+xml" \
        "application/schema+json" \
        "application/vnd.geo+json" \
        "application/vnd.ms-fontobject" \
        "application/x-font-ttf" \
        "application/x-javascript" \
        "application/x-web-app-manifest+json" \
        "application/xhtml+xml" \
        "application/xml" \
        "font/eot" \
        "font/opentype" \
        "image/bmp" \
        "image/svg+xml" \
        "image/vnd.microsoft.icon" \
        "image/x-icon" \
        "text/cache-manifest" \
        "text/css" \
        "text/html" \
        "text/javascript" \
```

```
"text/plain" \  
"text/vcard" \  
"text/vnd.rim.location.xloc" \  
"text/vtt" \  
"text/x-component" \  
"text/x-cross-domain-policy" \  
"text/xml"
```

```
</IfModule>
```

```
<IfModule mod_mime.c>
```

```
    AddEncoding gzip          svgz
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
    Header unset ETag
```

```
</IfModule>
```

```
FileETag None
```

```
<IfModule mod_expires.c>
```

```
    ExpiresActive on
```

```
    ExpiresDefault          "access plus 1 month"
```

```
# CSS
```

```
    ExpiresByType text/css          "access plus 1 year"
```

```
# Data interchange
```

```
    ExpiresByType application/atom+xml          "access plus 1 hour"
```

```
    ExpiresByType application/rdf+xml          "access plus 1 hour"
```

```
    ExpiresByType application/rss+xml          "access plus 1 hour"
```

```
    ExpiresByType application/json             "access plus 0 seconds"
```

```
    ExpiresByType application/ld+json          "access plus 0 seconds"
```

```
    ExpiresByType application/schema+json      "access plus 0 seconds"
```

```
    ExpiresByType application/vnd.geo+json     "access plus 0 seconds"
```

```
    ExpiresByType application/xml              "access plus 0 seconds"
```

```
    ExpiresByType text/xml                     "access plus 0 seconds"
```

Favicon (cannot be renamed!) and cursor images

```
ExpiresByType image/vnd.microsoft.icon "access plus 1 week"
ExpiresByType image/x-icon "access plus 1 week"
```

HTML

```
ExpiresByType text/html "access plus 0 seconds"
```

JavaScript

```
ExpiresByType application/javascript "access plus 1 year"
ExpiresByType application/x-javascript "access plus 1 year"
ExpiresByType text/javascript "access plus 1 year"
```

Manifest files

```
ExpiresByType application/manifest+json "access plus 1 week"
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

Media files

```
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/bmp "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType image/webp "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web fonts

Embedded OpenType (EOT)

```
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType font/eot "access plus 1 month"
```

OpenType

```

ExpiresByType font/opentype "access plus 1 month"

# TrueType
ExpiresByType application/x-font-ttf "access plus 1 month"

# Web Open Font Format (WOFF) 1.0
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType font/woff "access plus 1 month"

# Web Open Font Format (WOFF) 2.0
ExpiresByType application/font-woff2 "access plus 1 month"

# Other

ExpiresByType text/x-cross-domain-policy "access plus 1 week"

</IfModule>
### SILVERSTRIPE START ###
<Files *.ss>
    Order deny,allow
    Deny from all
    Allow from 127.0.0.1
</Files>

<Files web.config>
    Order deny,allow
    Deny from all
</Files>

<Files README.md>
    Order deny,allow
    Deny from all
</Files>

# This denies access to all yaml files, since developers might include sensitive
# information in them. See the docs for work-arounds to serve some yaml files
<Files ~ "\.ya?ml$" >
    Order allow,deny
    Deny from all
</Files>

```

ErrorDocument 404 /assets/error-404.html

ErrorDocument 500 /assets/error-500.html

<IfModule mod_rewrite.c>

SetEnv HTTP_MOD_REWRITE On

RewriteEngine On

RewriteRule ^vendor(/|\$) - [F,L,NC]

RewriteRule silverstripe-cache(/|\$) - [F,L,NC]

RewriteRule composer\. (json|lock) - [F,L,NC]

RewriteRule (error|silverstripe|debug)\. (log) - [F,L,NC]

RewriteCond %{REQUEST_URI} ^(\.)*\$

RewriteCond %{REQUEST_FILENAME} !-f

RewriteRule .* index.php?url=%1 [QSA]

</IfModule>

SILVERSTRIPE END