

```
RewriteEngine on
```

```
RewriteBase /
```

```
# if a directory or a file exists, use it directly
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule .* index.php [L]
```

```
# use utf-8 encoding for anything served text/plain or text/html
```

```
AddDefaultCharset utf-8
```

```
# force utf-8 for a number of file formats
```

```
AddCharset utf-8 .html .css .js .xml .json .rss
```

```
php_value default_charset utf-8
```

```
# Force the latest IE version, in various cases when it may fall back to IE7 mode
```

```
# github.com/rails/rails/commit/123eb25#commitcomment-118920
```

```
# Use ChromeFrame if it's installed for a better experience for the poor IE folk
```

```
<IfModule mod_setenvif.c>
```

```
  <IfModule mod_headers.c>
```

```
    BrowserMatch MSIE ie
```

```
    Header set X-UA-Compatible "IE=Edge,chrome=1" env=ie
```

```
  </IfModule>
```

```
</IfModule>
```

```
# allow access from all domains for webfonts
```

```
# alternatively you could only whitelist
```

```
# your subdomains like "sub.domain.com"
```

```
<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
```

```
  <IfModule mod_headers.c>
```

```
    Header set Access-Control-Allow-Origin "lessontrax.com"
```

```
  </IfModule>
```

```
</FilesMatch>
```

```
# webfonts
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType font/truetype ttf
```

```
AddType font/opentype otf
```

```
AddType font/woff woff
```

```
# these are pretty far-future expires headers
```

```
# they cause you content rendered with cachebuster every seven 11ks
```

```
# they assume you control versioning with cachebusting query params like
# <script src="application.js?20100608">
# additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/
```

```
# if you don't use filenames to version, lower the css and js to something like
# "access plus 1 week" or so
```

```
<IfModule mod_expires.c>
  Header set Cache-Control "no-cache, no-store, must-revalidate"
  Header set Pragma "no-cache"
  Header set Expires 0
</IfModule>
```

```
# Since we're sending far-future expires, we don't need ETags for
# static content.
```

```
# developer.yahoo.com/performance/rules.html#etags
```

```
FileETag None
```

```
# We don't need to tell everyone we're apache.
```

```
ServerSignature Off
```