

```
Options -Indexes
```

```
Header unset Pragma
```

```
FileETag None
```

```
Header unset ETag
```

```
Header set Vary Accept-Encoding
```

```
# no-www.org/faq.php?q=class_b
```

```
RewriteEngine On
```

```
RewriteCond %{HTTP_HOST} ^www\. (.+)$ [NC]
```

```
RewriteRule ^(.*)$ http://%1/%1 [R=301,L]
```

```
# allow access from all domains for webfonts
```

```
<FilesMatch "\.(ttf|otf|eot|woff|font. css)$">
```

```
  <IfModule mod_headers.c>
```

```
    Header set Access-Control-Allow-Origin "sparanoid.com"
```

```
  </IfModule>
```

```
</FilesMatch>
```

```
# add file types
```

```
AddType application/vnd.ms-fontobject eot
```

```
AddType font/ttf ttf
```

```
AddType font/otf otf
```

```
AddType font/x-woff woff
```

```
AddType image/svg+xml svg svgz
```

```
AddType video/ogg ogg ogv
```

```
AddType video/mp4 mp4
```

```
# HTML5 cache
```

```
# AddType text/cache-manifest manifest
```

```
# gzip compression.
```

```
<IfModule mod_deflate.c>
```

```
  # html, xml, css, and js:
```

```
  AddOutputFilterByType DEFLATE text/html text/plain text/xml text/css application/x-javascript text/javascript application/javascript application/json application/atom+xml
```

```
  # webfonts and svg:
```

```
  <FilesMatch "\.(ttf|otf|woff|eot|svg|svgz)$" >
```

```
    SetOutputFilter DEFLATE
```

```
  </FilesMatch>
```

```
</IfModule>
```

```

</IfModule>

# global expires header
<IfModule mod_expires.c>
    ExpiresActive On
    ExpiresDefault "access plus 10 years"
</IfModule>

# 10 years
<FilesMatch "\.(ico|pdf|flv|jpg|jpeg|png|gif|js|css|swf|tiff|otf|svg|svgz|eot)$">
    Header set Cache-Control "max-age=31536000"
    Header unset Last-Modified
</FilesMatch>

# 1 year
<FilesMatch "\.(html|html|xml|txt|sh)$">
    Header set Cache-Control "max-age=31536000, must-revalidate"
</FilesMatch>

# custom error pages
ErrorDocument 403 http://sparanoid.com/
ErrorDocument 404 http://sparanoid.com/
ErrorDocument 500 "Error 500"
ErrorDocument 503 "Error 503"

#ErrorDocument 403 /error/403.php
#ErrorDocument 404 /error/404.php
#ErrorDocument 500 /error/500.php
#ErrorDocument 503 /error/503.php

# old posts
Redirect 301 /blog/feed/ http://sparanoid.com/feed/
Redirect 301 /blog http://sparanoid.com
Redirect 302 /lab/7z/archive/ http://code.google.com/p/7-zip/downloads/list
Redirect 301 /4/12-eminem-mockingbird.mp3 http://sparanoid.com/
Redirect 301 /4/06-fort_minor-where'd_you_go_(feat._holly_brook_and_jonah_matranga).mp3
http://sparanoid.com/

# from wordpress to stacey
Redirect 301 /artwork/hello-world /news/hello-world
Redirect 301 /game/logging-cwow-with-us-client /notebook/logging-cwow-
...

```

```
with-us-client
Redirect 301 /project/igoogle-theme-somilody-2 /notebook/igoogle-theme-
somilody-2
Redirect 301 /project/7-zip-chinese-simplified-language-file-revision-1 /project/7z-
language-revision
Redirect 301 /project/judgment-screensaver-icon-from-academy-city
/project/judgment-screensaver-icon
Redirect 301 /project/angel-beats-girls-dead-monster-logo /project/angel-beats-
and-girls-dead-monster
Redirect 301 /project/lucky-star-skin-qq-sogou-pinyin /project/lucky-star-
ime-theme
```

```
# BEGIN Stacey
```

```
RewriteEngine on
```

```
# Some hosts require a rewritebase rule, if so, uncomment the RewriteBase line below. If
you are running from a subdirectory, your rewritebase should match the name of the path to
where stacey is stored.
```

```
# ie. if in a folder named 'stacey', RewriteBase /stacey
```

```
#RewriteBase /
```

```
# Rewrite any calls to *.html, *.json, *.xml, *.atom, *.rss, *.rdf or *.txt if a folder
matching * exists
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_URI} !public/
```

```
RewriteCond %{DOCUMENT_ROOT}/public/$1.$2 !-f
```

```
RewriteRule (.+)\.(html|json|xml|atom|rss|rdf|txt)$ $1/ [L]
```

```
# Add a trailing slash to directories
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteCond %{REQUEST_URI} !(\.)
```

```
RewriteCond %{REQUEST_URI} !(\. *)/$
```

```
RewriteRule ([^/]+)$ $1/ [L]
```

```
# Rewrite any calls to /* or /app to the index.php file
```

```
RewriteCond %{REQUEST_URI} /app/$
```

```
RewriteRule ^app/ index.php [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
```

```
RewriteCond %{REQUEST_FILENAME} !-d
```

```
RewriteRule ^(\. *)/$ index.php?$1 [L]
```

Rewrite any file calls to the public directory

RewriteCond %{REQUEST_FILENAME} !-f

RewriteCond %{REQUEST_FILENAME} !-d

RewriteCond %{REQUEST_URI} !public/

RewriteRule ^(.+)\$ public/\$1 [L]