

```
SetEnv HTTP_MOD_REWRITE On
RewriteEngine On
RewriteBase /
```

```
### SILVERSTRIPE START ###
```

```
<Files *.ss>
  Order deny,allow
  Deny from all
  Allow from 127.0.0.1
</Files>
```

```
<Files web.config>
  Order deny,allow
  Deny from all
</Files>
```

```
# This denies access to all yml files, since developers might include sensitive
# information in them. See the docs for work-arounds to serve some yaml files
```

```
<Files *.yml>
  Order allow,deny
  Deny from all
</Files>
```

```
ErrorDocument 404 /assets/error-404.html
ErrorDocument 500 /assets/error-500.html
```

```
<IfModule mod_rewrite.c>
  SetEnv HTTP_MOD_REWRITE On
  RewriteEngine On
  RewriteBase '/'
```

```
# SilverStripe HashPath rewrites for breaking cache
```

```
RewriteCond %{REQUEST_FILENAME} !-f
  RewriteCond %{REQUEST_FILENAME} !-d
  RewriteRule ^(.+)\.(v[A-Za-z0-9]+)\.(css|png|jpg|gif|jpeg)$ $1.$3 [L]
```

```
RewriteRule ^vendor(/|$) - [F,L,NC]
RewriteRule silverstripe-cache(/|$) - [F,L,NC]
RewriteRule composer\.(json|lock) - [F,L,NC]
```

```
RewriteCond %{REQUEST_URI} ^/.*$
```

```
RewriteCond %{REQUEST_URI} (.*)$
RewriteCond %{REQUEST_FILENAME} !-f
RewriteRule .* framework/main.php?url=%1&%(QUERY_STRING) [L]
</IfModule>
### SILVERSTRIPE END ###
```