

```
#  
# Hey! Everything in here is better suited to httpd.conf, since  
# we get a performance boost if we can turn off AllowOverride and  
# not have to stat the webroot for every request. On the other  
# hand, this means we never have to touch apache once it's up.  
# Flexibility over performance.  
#  
# In an ideal world, you'd stick it in here on dev and your build  
# system would bundle the changes into (a file included in) httpd.conf  
# for your production deployment, perhaps wrapped in a <VirtualHost>  
# block.  
#
```

```
# ETags are a bad idea if you have multiple web servers. We'll do  
# more explicit caching with Expires headers anyway.
```

```
FileETag none
```

```
# The base set of sensible PHP options. You could put these in your  
# php.ini file too, but having them in your Apache config puts  
# everything in one place. Magic quotes off because they are stupid.  
# Register globals off for the same reason. Track errors is so that  
# we can at least get at the error messages we hide using @func().  
# last_modified is a bad idea if we have any dynamic content. Short  
# tags make for a few saved bytes of cruft and are fine unless you're  
# running another XML preprocessor over your code (wtf?).
```

```
php_value magic_quotes_gpc 0  
php_value register_globals 0  
php_value magic_quotes_runtime 0  
php_value track_errors 1  
php_value last_modified off  
php_value short_open_tag on
```

```
# This value is very useful for development, but should be disabled  
# on production deployments (by setting the value to 'off')
```

```
php_flag display_errors on
```

```
# this sets all current and future error flags on, except for E_NOTICE  
# which can go fuck itself. we have some separate code for checking the  
# one notice we do care about.
```

```
php_value error_reporting 2147483639
```

```

# Some basic pointers to php files
DirectoryIndex index.php
ErrorDocument 404 /404.php
ErrorDocument 403 /403.php

# Get mod_rewrite fired up
RewriteEngine on

# See all this stuff that's been commented out? It's a lot of hoop-jumping
# to separate API calls (api.example.com/rest) from all the other user-level
# administrative pages (example.com/api/methods) and to make sure things that
# need to be done over SSL are (like OAuth2). By default it's all commented out
# because what do I know about your webserver is configured. So spend a
# couple minutes looking at all this stuff and thinking about it and adjusting
# accordingly. Also: remember all the security around OAuth2 is predicated
# around the use of SSL. (20121103/straup)

# The API (as in both api.example.com and example.com/api)
# Ensure that all traffic to the API proper is over HTTPS
# Note that this is a api.example.com host not example.com
# (20121025/straup)

# RewriteCond %{HTTP_HOST}    ^api.(.*)$
# RewriteCond %{HTTPS} off
# RewriteRule (.*) https://%{HTTP_HOST}/$1?%{QUERY_STRING} [R,L]

# The most basic rewrite, as this is the actual API

# RewriteCond %{HTTP_HOST}    ^api.(.*)$
# RewriteRule ^rest/?$    api_rest.php?%{QUERY_STRING} [L]

# This one says: If we're the API and we're not hanging off /rest
# redirect to the site itself - note the %1% for capturing the domain
# sans 'api.' (20121025/straup)

# RewriteCond %{REQUEST_URI} !rest(.*)
# RewriteCond %{HTTP_HOST}    ^api.(.*)$ [NC]
# RewriteRule .?    http://%1%{REQUEST_URI} [R,L]

# RewriteCond %{HTTP_HOST}    !^api.(.*)$
# RewriteRule ^(.*)$ http://example.com/$1 [R,L]

```

```
# RewriteRule ^api/rest/(.*)/?$ https://api.%(HTTP_HOST)/rest/?method=$1&%(QUERY_STRING)  
[R,L]
```

```
# RewriteCond %(HTTP_HOST) !=^api.(.*)$
```

```
# RewriteRule ^rest/(.*)/?$ https://api.%(HTTP_HOST)/rest/?method=$1&%(QUERY_STRING)  
[R,L]
```

```
# The rest of the user/admin interfaces for doing API stuff
```

```
# This all (especially the oauth2 auth/token stuff) relies on the
```

```
# HTTPS rules for logged in users (20121024/straup)
```

```
RewriteRule ^api/?$ api.php [L]
```

```
RewriteRule ^api/methods/?$ api_methods.php [L]
```

```
RewriteRule ^api/methods/print/?$ api_methods.php?print=1 [L, QSA]
```

```
RewriteRule ^api/methods/(.*)/?$ api_method.php?method=$1&%(QUERY_STRING) [L]
```

```
RewriteRule ^api/keys/?$ api_keys.php?(QUERY_STRING) [L]
```

```
RewriteRule ^api/keys/register/?$ api_keys_register.php?(QUERY_STRING) [L]
```

```
RewriteRule ^api/keys/([a-zA-Z0-9]+)/?$ api_key.php?api_key=$1&%(QUERY_STRING) [L]
```

```
RewriteRule ^api/keys/([a-zA-Z0-9]+)/tokens(/page([0-9]+))/?$ api_key_tokens.php?  
api_key=$1&page=$3&%(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/?$ api_oauth2.php?(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/howto/?$ api_oauth2_howto.php?(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/authenticate/?$ api_oauth2_authenticate.php?  
(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/authenticate/like-magic/?$  
api_oauth2_authenticate_like_magic.php?(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/access_token/?$ api_oauth2_access_token.php?  
(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/tokens(/page([0-9]+))/?$ api_oauth2_tokens.php?page=$2&  
(QUERY_STRING) [L]
```

```
RewriteRule ^api/oauth2/tokens/([a-zA-Z0-9]+)/?$ api_oauth2_token.php?api_key=$1&  
(QUERY_STRING) [L]
```

```
RewriteRule ^api/rest/?$ api_rest.php?(QUERY_STRING) [L]
```

```
# Login stuff
```

```
RewriteRule ^signup/?$ signup.php [L]
```

```
RewriteRule ^signin/?$      signin.php    [L]
RewriteRule ^signout/?$     signout.php   [L]
RewriteRule ^checkcookie/?$ checkcookie.php [L]
```

Password retrieval stuff

```
RewriteRule ^forgot/?$      forgot.php    [L]
RewriteRule ^reset/([a-zA-Z0-9]+)/?$ reset.php?reset=$1 [L, QSA]
```

Account stuff

```
RewriteRule ^account/?$     account.php   [L]
RewriteRule ^account/password/?$ account_password.php [L]
RewriteRule ^account/delete/?$ account_delete.php [L]
```

General pages

```
RewriteRule ^about/?$      about.php     [L, QSA]
RewriteRule ^contact/?$    contact.php   [L, QSA]
```

Reading lists and documents

```
RewriteRule ^upload/?$      upload.php    [L, QSA]

RewriteRule ^documents(/page([0-9]+))/??$ user_documents.php?page=$2 [L, QSA]
RewriteRule ^documents/offline/?$      user_documents_offline.php [L, QSA]

RewriteRule ^documents/([0-9]+)/?$      user_document.php?document_id=$1 [L, QSA]

RewriteRule ^highlights(/page([0-9]+))/??$ user_highlights.php?page=$2 [L, QSA]
RewriteRule ^highlights/pending/?$      user_highlights_pending.php [L, QSA]
RewriteRule ^highlights/([0-9]+)/?$      user_highlight.php?id=$1 [L, QSA]

RewriteRule ^notepad/?$      user_notepad.php [L, QSA]
```

Apache / manifest stuff

```
RewriteRule (.*)?manifest.appcache$      appcache_manifest.php [L, QSA]
RewriteRule (.*)?manifest/?$              appcache_manifest.php [L, QSA]
```