

```
# The base set of sensible PHP options. You could put these in your
# php.ini file too, but having them in your Apache config puts
# everything in one place. Magic quotes off because they are stupid.
# Register globals off for the same reason. Track errors is so that
# we can at least get at the error messages we hide using @func(),
# last_modified is a bad idea if we have any dynamic content. Short
# tags make for a few saved bytes of cruft and are fine unless you're
# running another XML preprocessor over your code (wtf?).
```

```
# Experimental: Will add notes about this if it actually works; if not
# it never happened...
```

```
<IfModule mod_php5.c>
```

```
php_value magic_quotes_gpc 0
php_value register_globals 0
php_value magic_quotes_runtime 0
php_value track_errors 1
php_value last_modified off
php_value short_open_tag on
```

```
php_flag display_errors on
```

```
# this sets all current and future error flags on, except for E_NOTICE
# which can go fuck itself. we have some separate code for checking the
# one notice we do care about.
```

```
php_value error_reporting 2147483639
```

```
</IfModule>
```

```
#
# Hey! Everything in here is better suited to httpd.conf, since
# we get a performance boost if we can turn off AllowOverride and
# not have to stat the webroot for every request. On the other
# hand, this means we never have to touch apache once it's up.
# Flexibility over performance.
```

```
#
# In an ideal world, you'd stick it in here on dev and your build
# system would bundle the changes into (a file included in) httpd.conf
# for your production deployment. Yeah. Do that.
```

```
"
```

#

# ETags are a bad idea if you have multiple web servers. We'll do  
# more explicit caching with Expires headers anyway.

FileETag none

# The base set of sensible PHP options have moved; they now live in www/php.ini.

# Some basic pointers to php files

DirectoryIndex index.php

ErrorDocument 404 /404.php

ErrorDocument 403 /403.php

# Get mod\_rewrite fired up

RewriteEngine on

# See also: the 'php-ini' command in the root Makefile

RewriteRule ^php.ini - [R=404,L]

# Images

RewriteRule ^favicon.ico images/favicon.ico [L]

RewriteRule ^apple-touch-icon.png images/apple-touch-icon.png [L]

# Login stuff

RewriteRule ^signout/?\$ signout.php [L]

RewriteRule ^checkcookie/?\$ checkcookie.php [L]

RewriteRule ^auth/?\$ auth\_callback\_foursquare\_oauth.php?%{QUERY\_STRING} [L]

RewriteRule ^signin/?\$ signin\_foursquare\_oauth.php?%{QUERY\_STRING} [L]

RewriteRule ^signup/email/?\$ signup\_email.php?%{QUERY\_STRING} [L]

RewriteRule ^signin/email/?\$ signin\_email.php?%{QUERY\_STRING} [L]

# Password retrieval stuff

# RewriteRule ^forgot/?\$ forgot.php [L]

# RewriteRule ^reset/([a-zA-Z0-9]+)/\*\$ reset.php?reset=\$1 [L,QSA]

# Account stuff

```
RewriteRule ^account/?$ account.php [L]
# RewriteRule ^account/password/?$ account_password.php [L]
# RewriteRule ^account/delete/?$ account_delete.php [L]

RewriteRule ^account/bergcloud/?$ account_bergcloud.php [L]
RewriteRule ^account/foursquare-sync/?$ account_foursquare_sync.php?%{QUERY_STRING} [L]

# API

RewriteRule ^api/?$ api_rest.php [L]
RewriteRule ^api/methods/?$ api_methods.php [L]
RewriteRule ^api/methods/(.+)/?$ api_method.php?method=$1&%{QUERY_STRING} [L]
RewriteRule ^api/rest/(.+)/?$ api_rest.php?method=$1&%{QUERY_STRING} [L]

# foursquare stuff

RewriteRule ^me(/(.+))/?/?$ me.php?path=$2&%{QUERY_STRING} [L]

RewriteRule ^want(/([a-f0-9]+))/?/?$ venue_i_want_to_go_there.php?venue_id=$2&%{QUERY_STRING} [L]

RewriteRule ^venues?/([a-z]+)(/page([0-9]+))/?/?$ venues_provider.php?provider=$1&page=$3&%{QUERY_STRING} [L]

RewriteRule ^privatesquare/create/?$ privatesquare_create.php?%{QUERY_STRING} [L]
RewriteRule ^privatesquare/venues(/page([0-9]+))/?/?$ privatesquare_venues.php?page=$2&%{QUERY_STRING} [L]

RewriteRule ^venue/([0-9]+)/?$ venue.php?venue_id=$1&%{QUERY_STRING} [L]
RewriteRule ^venue/([a-z]+)([a-f0-9]+)/?$ venue.php?provider=$1&venue_id=$2&%{QUERY_STRING} [L]

RewriteRule ^venue/([0-9]+)/visits(/page([0-9]+))/?/?$ venue_visits.php?venue_id=$1&page=$3&%{QUERY_STRING} [L]
RewriteRule ^venue/([a-z]+)([a-f0-9]+)/visits(/page([0-9]+))/?/?$ venue_visits.php?provider=$1&venue_id=$2&page=$4&%{QUERY_STRING} [L]

RewriteRule ^user/([0-9]+)/checkin(/([0-9a-f]+))/?$ user_checkin.php?foursquare_id=$1&checkin_id=$3&%{QUERY_STRING} [L]
```

```
RewriteRule ^user/([0-9]+)/places(/page([0-9]+))??$ user_places.php?  
foursquare_id=$1&page=$3&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/places/([0-9]+)(/page([0-9]+))??$ user_place.php?  
foursquare_id=$1&woeid=$2&page=$4&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/atlas/?$ user_atlas_of_desire.php?  
foursquare_id=$1&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/atlas/(([0-9]+)([a-z]+))/nearby(/page([0-9]+))??$  
user_atlas_nearby.php?foursquare_id=$1&status_id=$3&status_label=$4&page=$6&%  
{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/atlas/(([0-9]+)([a-z]+))/([0-9]+)(/page([0-9]+))??$  
user_atlas.php?foursquare_id=$1&status_id=$3&status_label=$4&woeid=$5&page=$7&%  
{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/atlas/(([0-9]+)([a-z]+))(/page([0-9]+))??$  
user_atlas.php?foursquare_id=$1&status_id=$3&status_label=$4&page=$6&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/history/nearby/?$ user_history_nearby.php?  
foursquare_id=$1&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/history/export(\.([a-z]+))??$ user_history_export.php?  
foursquare_id=$1&format=$3&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/history/([a-zA-Z]+)(/page([0-9]+))??$ user_history_dow.php?  
foursquare_id=$1&dow=$2&page=$4&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/history(/page([0-9]+))??$ user_history.php?  
foursquare_id=$1&page=$3&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/history/([0-9\-\;\:\;T]+)(/page([0-9]+))??$ user_history.php?  
foursquare_id=$1&when=$2&page=$4&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/pending/?$ user_pending_checkins.php?foursquare_id=$1&%  
{QUERY_STRING} [L]  
  
# TBD... (20140119/straup)  
# RewriteRule ^user/([0-9]+)/trips/geocode/?$ user_trips_add_geocode.php?%  
{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/trips/add/?$ user_trips_add.php?foursquare_id=$1&%  
{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips(/page([0-9]+))??$ user_trips.php?foursquare_id=$1&%  
{QUERY_STRING} [L]
```

```
RewriteRule ^user/([0-9]+)/trips/past(/page([0-9]+))??/?$ user_trips_past.php?  
foursquare_id=$1&page=$3&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/trips/archives/?$ user_trips_archives.php?  
foursquare_id=$1&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/archives/([0-9]+)(/page([0-9]+))??/?$  
user_trips_archive.php?foursquare_id=$1&year=$2&page=$4&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/archives/([0-9]+)([0-9]+)(/page([0-9]+))??/?$  
user_trips_archive.php?foursquare_id=$1&year=$2&month=$3&page=$5&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/trips/archives/([0-9]+)/places/([0-9]+)(/page([0-9]+))??/?$  
user_trips_archive_place.php?foursquare_id=$1&year=$2&woeid=$3&page=$5&%{QUERY_STRING}  
[L]  
  
RewriteRule ^user/([0-9]+)/trips/places(/page([0-9]+))??/?$ user_trips_places.php?  
foursquare_id=$1&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/places/([0-9]+)(/page([0-9]+))??/?$  
user_trips_place.php?foursquare_id=$1&woeid=$2&page=$4&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/trips/([0-9]+)/?$ user_trip.php?  
foursquare_id=$1&trip_id=$2&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/([0-9]+)/checkins(/page([0-9]+))??/?$  
user_trip_checkins.php?foursquare_id=$1&trip_id=$2&page=$4&%{QUERY_STRING} [L]  
  
RewriteRule ^user/([0-9]+)/trips/calendars(/page([0-9]+))??/?$  
user_trips_calendars.php?foursquare_id=$1&page=$3&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/calendars/add/?$ user_trips_calendars_add.php?  
foursquare_id=$1&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/calendars/([0-9]+)/?$ user_trips_calendar.php?  
foursquare_id=$1&id=$2&%{QUERY_STRING} [L]  
RewriteRule ^user/([0-9]+)/trips/calendars/([0-9]+)/share/?$  
user_trips_calendar_share.php?foursquare_id=$1&id=$2&%{QUERY_STRING} [L]  
  
# Include user ID at all? (20140305/straup)  
# See also: Github issue #42 (20140420/straup)  
RewriteRule ^user/([0-9]+)/trips/calendars\..ics$ user_trips_calendar_ics.php?  
foursquare_id=$1&%{QUERY_STRING} [L]  
RewriteRule ^calendars/?$ user_trips_calendar_ics.php?%{QUERY_STRING} [L]  
  
# See this. It's the *last* rule because it basically catches everything
```

```
RewriteRule ^4sq/?$ index.php?provider=foursquare&%{QUERY_STRING} [L]
RewriteRule ^([a-z]+)/$ index.php?provider=$1&%{QUERY_STRING} [L]
```