

```
<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

<IfModule mod_headers.c>
    Header set X-UA-Compatible "IE=edge"
    <FilesMatch "\.
(appcache|atom|bbaw|bml|crl|css|curl|eot|f4[abpv]|flv|geojson|gif|htcl|icol|jpe?
gl|jsl|json|ld)?
|m4[av]|manifest|map|mp4|oex|og[agv]|opus|otf|pdf|png|rdf|rss|safariextz|svgz?
|swf|topojson|tt[cf]|txt|vcard|vcf|vtt|webapp|web[mp]|webmanifest|woff2?|xloc|xml|xpi)$">
        Header unset X-UA-Compatible
    </FilesMatch>
</IfModule>

# BEGIN h5bp
# https://github.com/h5bp/server-configs
<IfModule mod_mime.c>

    # Audio
    AddType audio/mp4 m4a f4a f4b
    AddType audio/ogg oga ogg opus

    # Data interchange
    AddType application/json json map
    AddType application/ld+json jsonld

    # JavaScript
    # Normalize to standard type.
    # http://tools.ietf.org/html/rfc4329#section-7.2
    AddType application/javascript js

    # Manifest files

    # <Files "manifest.json">
    # AddType application/manifest+json json
    # </Files>

    AddType application/x-web-app-manifest+json webapp
    AddType text/cache-manifest appcache manifest
```

Video

```
AddType video/mp4 f4v f4p m4v mp4
AddType video/ogg ogv
AddType video/webm webm
AddType video/x-flv flv
```

Web fonts

```
AddType application/font-woff woff
AddType application/vnd.ms-fontobject eot
```

*# Browsers usually ignore the font media types and simply sniff
the bytes to figure out the font type.
<http://mimesniff.spec.whatwg.org/#matching-a-font-type-pattern>*

*# Chrome however, shows a warning if any other media types are used
for the following fonts.*

```
AddType application/x-font-ttf ttc ttf
AddType font/opentype otf
```

*# Make SVGZ fonts work on the iPad.
<https://twitter.com/FontSquirrel/status/14855840545>*

```
AddType image/svg+xml svg svgz
AddEncoding gzip svgz
```

Other

```
AddType application/octet-stream safariextz
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall xpi
AddType application/xml atom rdf rss xml
AddType image/webp webp
AddType image/x-icon cur ico
AddType text/vtt vtt
AddType text/x-component htc
AddType text/x-vcard vcf
```

</IfModule>

<IfModule mod_deflate.c>

```

# Force compression for mangled headers.
# http://developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-beyond-gzipping
<IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
        SetEnvIfNoCase ^(\Accept-EncodXng|X-cept-Encoding|X(15)|^(15)|-(15))$
^((gzip|deflate)\s*,?\s*)+([X"-]{4,13})$ HAVE_Accept-Encoding
        RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
</IfModule>

# Compress all output labeled with one of the following media types
# (for Apache versions below 2.3.7, you don't need to enable `mod_filter`
# and can remove the `<IfModule mod_filter.c>` and `</IfModule>` lines
# as `AddOutputFilterByType` is still in the core directives).
#<IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
        application/javascript \
        application/json \
        application/ld+json \
        application/manifest+json \
        application/rss+xml \
        application/vnd.ms-fontobject \
        application/x-font-ttf \
        application/x-web-app-manifest+json \
        application/xhtml+xml \
        application/xml \
        font/opentype \
        image/svg+xml \
        image/x-icon \
        text/css \
        text/html \
        text/plain \
        text/vtt \
        text/x-component \
        text/xml

#</IfModule>

</IfModule>

<IfModule mod_headers.c>

```

```
Header unset ETag
</IfModule>
```

FileETag None

```
<IfModule mod_expires.c>
```

```
ExpiresActive on
ExpiresDefault "access plus 1 month"
```

CSS

```
ExpiresByType text/css "access plus 1 year"
```

Data interchange

```
ExpiresByType application/json "access plus 0 seconds"
ExpiresByType application/ld+json "access plus 0 seconds"
ExpiresByType application/xml "access plus 0 seconds"
ExpiresByType text/xml "access plus 0 seconds"
```

Favicon (cannot be renamed!) and cursor images

```
ExpiresByType image/x-icon "access plus 1 week"
```

HTML components (HTCs)

```
ExpiresByType text/x-component "access plus 1 month"
```

HTML

```
ExpiresByType text/html "access plus 0 seconds"
```

JavaScript

```
ExpiresByType application/javascript "access plus 1 year"
```

Manifest files

```
ExpiresByType application/manifest+json "access plus 1 year"
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

Media

```
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
```

```
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"
```

Web feeds

```
ExpiresByType application/atom+xml "access plus 1 hour"
ExpiresByType application/rss+xml "access plus 1 hour"
```

Web fonts

```
ExpiresByType application/font-woff "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
```

</IfModule>

END h5bp

BEGIN WordPress

<IfModule mod_rewrite.c>

```
RewriteEngine On
RewriteBase /
RewriteRule ^index\.php$ - [L]
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . /index.php [L]
```

</IfModule>

END WordPress