

```

# -----
# /PUBLIC folder .htaccess
# -----
# This .htaccess file is recommended
# to be placed at root/public folder
# of your Laravel powered application
# -----
# This file works with Laravel 3 and 4
# -----
# Turning on the rewrite engine is necessary for the following rules and
# features. "+FollowSymLinks" must be enabled for this to work symbolically.
# -----

<IfModule mod_rewrite.c>
    Options +FollowSymLinks
    DirectoryIndex index.php
    RewriteEngine On
</IfModule>

RewriteEngine On
RewriteBase /
RewriteCond %{THE_REQUEST} ^[A-Z]{3,9}\ /index\.php HTTP/
RewriteRule ^index\.php$ / [R=301,L]

RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . / [L]

AddDefaultCharset utf-8
AddCharset utf-8 .atom .css .js .json .rss .vtt .xml

# -----
# A little more security
# -----
# To avoid displaying the exact version number of Apache being used, add the
# following to httpd.conf (it will not work in .htaccess):
# ServerTokens Prod
# -----
# "-Indexes" will have Apache block users from browsing folders without a
# default document Usually you should leave this activated, because you
# should delete all your subdirectories through every folder of your server (what

```

```
# show on t allow everybody to surf through every folder on your server (which
# includes rather private places like CMS system folders).
# -----

<IfModule mod_autoindex.c>
    Options -Indexes
</IfModule>

# -----
# Block access to "hidden" directories or files whose names begin with a
# period. This includes directories used by version control systems such as
# Subversion or Git.
# -----

<IfModule mod_rewrite.c>
    RewriteCond %{SCRIPT_FILENAME} -d [OR]
    RewriteCond %{SCRIPT_FILENAME} -f
    RewriteRule "(^/)\." - [F]
</IfModule>

# -----
# Block access to backup and source files. These files may be left by some
# text/html editors and pose a great security danger, when anyone can access
# them.
# -----

<FilesMatch "%(\.bak|config|sql|fla|psd|ini|log|sh|incl|swp|dist)|(")$">
    Order allow,deny
    Deny from all
    Satisfy All
</FilesMatch>

# -----
# Suppress or force the "www." at the beginning of URLs
# -----
# IMPORTANT: NEVER USE BOTH RULES AT THE SAME TIME!
# -----
# Option 1:
# Rewrite "www.example.com -> example.com".
# -----
```

```

<IfModule mod_rewrite.c>
  RewriteCond %{HTTPS} !=on
  RewriteCond %{HTTP_HOST} ^www\.(.+$) [NC]
  RewriteRule ^ http://%1%{REQUEST_URI} [R=301,L]
</IfModule>

# -----
# Option 2:
# Rewrite "example.com -> www.example.com".
# Be aware that the following rule might not be a good idea if you use "real"
# subdomains for certain parts of your website.
# -----

# <IfModule mod_rewrite.c>
#   RewriteCond %{HTTPS} !=on
#   RewriteCond %{HTTP_HOST} !^www\..+$ [NC]
#   RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [R=301,L]
# </IfModule>

# -----
# Compression is implemented by the DEFLATE filter.
# The following directive will enable compression for documents in the container
# -----
<IfModule mod_deflate.c>

  # Force deflate for mangled headers developer.yahoo.com/blogs/ydn/posts/2010/12/pushing-bi
  <IfModule mod_setenvif.c>
    <IfModule mod_headers.c>
      SetEnvIfNoCase ^(\Accept-Encoding|X-cept-Encoding|X(15)|^(15)|-(15))$ ^((gzip|deflate)\
HAVE_Accept-Encoding
      RequestHeader append Accept-Encoding "gzip,deflate" env=HAVE_Accept-Encoding
    </IfModule>
  </IfModule>

  # Compress all output labeled with one of the following MIME-types
  <IfModule mod_filter.c>
    AddOutputFilterByType DEFLATE application/atom+xml \
      application/javascript \
      application/json \
      application/rss+xml \
      application/vnd.ms-fontobject \

```

```
application/x-font-ttf \  
application/xhtml+xml \  
application/xml \  
font/opentype \  
image/svg+xml \  
image/x-icon \  
text/css \  
text/html \  
text/plain \  
text/x-component \  
text/xml
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
Header set X-UA-Compatible "IE=Edge,chrome=1"
```

```
# mod_headers can't match by content-type, but we don't want to send this header on *ever!
```

```
<FilesMatch "\.(js|css|gif|png|jpe?
```

```
gl|pdf|xml|ogal|oggl|m4a|ogv|mp4|m4v|webm|svg|svgz|eot|ttf|otf|woff|icol|webp|appcache|manifest|
```

```
>
```

```
Header unset X-UA-Compatible
```

```
</FilesMatch>
```

```
</IfModule>
```

```
<IfModule mod_setenvif.c>
```

```
<IfModule mod_headers.c>
```

```
# mod_headers, y u no match by Content-Type?!
```

```
<FilesMatch "\.(gif|png|jpe?gl|svg|svgz|icol|webp)$">
```

```
SetEnvIf Origin ":" IS_CORS
```

```
Header set Access-Control-Allow-Origin "*" env=IS_CORS
```

```
</FilesMatch>
```

```
</IfModule>
```

```
</IfModule>
```

```
<IfModule mod_headers.c>
```

```
<FilesMatch "\.(ttf|ttcl|otf|eot|woff|font.css)$">
```

```
Header set Access-Control-Allow-Origin "*"
```

```
</FilesMatch>
```

```
</IfModule>
```

```

<IfModule mod_headers.c>
  <FilesMatch "\.(ico|pdf|flv|jpg|jpeg|png|gif|swf|mp3|mp4)$">
    Header set Cache-Control "public"
  </FilesMatch>
</IfModule>

# -----
# Expires headers (for better cache control)
# -----
# These are pretty far-future expires headers.
# They assume you control versioning with filename-based cache busting
# Additionally, consider that outdated proxies may miscache
# www.stevesouders.com/blog/2008/08/23/revving-filenames-dont-use-querystring/
# -----
# If you don't use filenames to version, lower the CSS and JS to something like
# "access plus 1 week".
# -----

<IfModule mod_expires.c>
  ExpiresActive on

# Perhaps better to whitelist expires rules? Perhaps.
  ExpiresDefault                               "access plus 1 month"

# cache.appcache needs re-requests in FF 3.6 (thanks Remy "Introducing HTML5")
  ExpiresByType text/cache-manifest           "access plus 0 seconds"

# Your document html
  ExpiresByType text/html                      "access plus 0 seconds"

# Data
  ExpiresByType text/xml                      "access plus 0 seconds"
  ExpiresByType application/xml               "access plus 0 seconds"
  ExpiresByType application/json              "access plus 0 seconds"

# Feed
  ExpiresByType application/rss+xml           "access plus 1 hour"
  ExpiresByType application/atom+xml          "access plus 1 hour"

# Favicon (cannot be renamed)
  ExpiresByType image/x-icon                  "access plus 1 week"

```

```
# Media: images, video, audio
ExpiresByType image/gif "access plus 1 month"
ExpiresByType image/png "access plus 1 month"
ExpiresByType image/jpeg "access plus 1 month"
ExpiresByType video/ogg "access plus 1 month"
ExpiresByType audio/ogg "access plus 1 month"
ExpiresByType video/mp4 "access plus 1 month"
ExpiresByType video/webm "access plus 1 month"

# HTC files (css3pie)
ExpiresByType text/x-component "access plus 1 month"

# Webfonts
ExpiresByType application/x-font-ttf "access plus 1 month"
ExpiresByType font/opentype "access plus 1 month"
ExpiresByType application/x-font-woff "access plus 1 month"
ExpiresByType image/svg+xml "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"

# CSS and JavaScript
ExpiresByType text/css "access plus 1 year"
ExpiresByType application/javascript "access plus 1 year"

</IfModule>

# -----
# Proper MIME type for all files
# -----
# JavaScript
# Normalize to standard type (it's sniffed in IE anyways)
# tools.ietf.org/html/rfc4329#section-7.2
# -----

AddType application/javascript js jsonp
AddType application/json json

# Audio
AddType audio/ogg oga ogg
AddType audio/mp4 m4a f4a f4b
```

### *# Video*

```
AddType video/ogg                ogv
AddType video/mp4                 mp4 m4v f4v f4p
AddType video/webm                webm
AddType video/x-flv               flv
```

### *# SVG*

*# Required for svg webfonts on iPad*

*# [twitter.com/FontSquirrel/status/14855840545](https://twitter.com/FontSquirrel/status/14855840545)*

```
AddType image/svg+xml           svg svgz
AddEncoding gzip                 svgz
```

### *# Webfonts*

```
AddType application/vnd.ms-fontobject eot
AddType application/x-font-ttf         ttf ttc
AddType font/opentype                 otf
AddType application/x-font-woff       woff
```

### *# Assorted types*

```
AddType image/x-icon             ico
AddType image/webp                webp
AddType text/cache-manifest       appcache manifest
AddType text/x-component          htc
AddType application/xml           rss atom xml rdf
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-xpinstall   xpi
AddType application/octet-stream   safariextz
AddType application/x-web-app-manifest+json webapp
AddType text/x-vcard              vcf
AddType application/x-shockwave-flash swf
AddType text/vtt                  vtt
```