

```
### Smart Framework sample .htaccess for Apache 2.2 / 2.4
### For the most basic version, just uncomment the 7 lines that start with the # as first character.
```

```
php_value default_mimetype    text/html
php_value variables_order     GPC
php_value request_order      GP
php_flag always_populate_raw_post_data Off
php_value max_input_vars    1500
php_value max_input_nesting_level 5
php_value max_input_time    60
php_value output_buffering   0
#php_value output_buffering 4096
php_value post_max_size     108M
php_value upload_max_filesize 102M
php_flag session.auto_start Off
php_value session.use_trans_sid 0
php_flag mail.add_x_header Off
php_flag zend.enable_gc      On
php_flag zend.multibyte     Off
```

```
#<IfModule mod_rewrite.c>
```

```
#v. 160731#
```

```
###
# RewriteEngine On
###
```

```
### sample: smart-framework/module.controller.html.html.json [ compatible with
Smart::url_make_semantic() + Rewrite ]
##RewriteCond %{QUERY_STRING} !^/
# RewriteCond %{REQUEST_FILENAME} !-f
# RewriteCond %{REQUEST_FILENAME} !-d
# RewriteRule ^(.*)\.(html|stm|json)$ index.php?page=$1 [QSA,L]
###
```

```
### sample: alternate URLs to use in combination with sub-domains (This is only for very
very advanced use ... !!!)
```

```
##RewriteCond %{HTTP_HOST} ^([0-9a-z\-\_]*).
```

```
##### module: smart-framework/controller
##RewriteRule ^(.*)/?/?$ index.php?page=$1, $1 [QSA,L]
#####
## module: smart-framework/controller
##RewriteRule ^(.*)/?/?$ index.php?page=$1, $1 [QSA,L]
#####
## controller: smart-framework/module(.html,.stml,.json)
##RewriteRule ^(.*)\.(html|stml|json)$ index.php?page=$1, $1 [QSA,L]
#####
## module: smart-framework/controller(.html,.stml,.json)
##RewriteRule ^(.*)\.(html|stml|json)$ index.php?page=$1, $1 [QSA,L]
###
```

#</IfModule>

### END