

```

# Use PHP5.3 as default
AddHandler application/x-httpd-php53 .php
#
# Apache/PHP/Drupal settings:
#

# Protect files and directories from prying eyes.
<FilesMatch "\.
(engineincl|info|install|make|module|profile|test|po|sh|. *sql|theme|tpl(\.php)?
|xtmpl)$|^(\. *|Entries|Repository|Root|Tag|Template)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
# For security reasons, Option followsymlinks cannot be overridden.
#Options +FollowSymLinks
Options +SymLinksIfOwnerMatch

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Set the default handler.
DirectoryIndex index.php index.html index.htm

# Override PHP settings that cannot be changed at runtime. See
# sites/default/default.settings.php and drupal_environment_initialize() in
# includes/bootstrap.inc for settings that can be changed at runtime.

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_flag magic_quotes_gpc          off
    php_flag magic_quotes_sybase      off
    php_flag register_globals         off
    php_flag session.auto_start      off
    php_value mbstring.http_input     pass
    php_value mbstring.http_output    pass
    php_flag mbstring.encoding_translation off

```

```
</IfModule>
```

```
# Requires mod_expires to be enabled.
```

```
<IfModule mod_expires.c>
```

```
# Enable expirations.
```

```
ExpiresActive On
```

```
# Cache all files for 2 weeks after access (A).
```

```
ExpiresDefault A1209600
```

```
<FilesMatch \.php$>
```

```
# Do not allow PHP scripts to be cached unless they explicitly send cache  
# headers themselves. Otherwise all scripts would have to overwrite the  
# headers set by mod_expires if they want another caching behavior. This may  
# fail if an error occurs early in the bootstrap process, and it may cause  
# problems if a non-Drupal PHP file is installed in a subdirectory.
```

```
ExpiresActive Off
```

```
</FilesMatch>
```

```
</IfModule>
```

```
# Various rewrite rules.
```

```
<IfModule mod_rewrite.c>
```

```
RewriteEngine on
```

```
# Block access to "hidden" directories whose names begin with a period. This  
# includes directories used by version control systems such as Subversion or  
# Git to store control files. Files whose names begin with a period, as well  
# as the control files used by CVS, are protected by the FilesMatch directive  
# above.
```

```
#
```

```
# NOTE: This only works when mod_rewrite is loaded. Without mod_rewrite, it is  
# not possible to block access to entire directories from .htaccess, because  
# <DirectoryMatch> is not allowed here.
```

```
#
```

```
# If you do not have mod_rewrite installed, you should remove these  
# directories from your webroot or otherwise protect them from being  
# downloaded.
```

```
RewriteRule "(^|/)\." - [F]
```

```
# If your site can be accessed both with and without the 'www.' prefix, you  
# can use one of the following settings to redirect users to your preferred  
# version. To force www use instead, use the following: http://httpd.apache.org/docs/2.4/mod/mod\_rewrite.html
```

```
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:
#
# To redirect all users to access the site WITH the 'www.' prefix,
# (http://example.com/... will be redirected to http://www.example.com/...)
# uncomment the following:
# RewriteCond %{HTTP_HOST} !^www\. [NC]
# RewriteRule ^ http://www.%{HTTP_HOST}%{REQUEST_URI} [L,R=301]
#
# To redirect all users to access the site WITHOUT the 'www.' prefix,
# (http://www.example.com/... will be redirected to http://example.com/...)
# uncomment the following:
# RewriteCond %{HTTP_HOST} ^www\. (.+)$ [NC]
# RewriteRule ^ http://%1%{REQUEST_URI} [L,R=301]

# Modify the RewriteBase if you are using Drupal in a subdirectory or in a
# VirtualDocumentRoot and the rewrite rules are not working properly.
# For example if your site is at http://example.com/drupal uncomment and
# modify the following line:
# RewriteBase /drupal
#
# If your site is running in a VirtualDocumentRoot at http://example.com/,
# uncomment the following line:
# RewriteBase /

# Pass all requests not referring directly to files in the filesystem to
# index.php. Clean URLs are handled in drupal_environment_initialize().
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteCond %{REQUEST_URI} !=/favicon.ico
RewriteRule ^ index.php [L]

# Rules to correctly serve gzip compressed CSS and JS files.
# Requires both mod_rewrite and mod_headers to be enabled.
<IfModule mod_headers.c>
  # Serve gzip compressed CSS files if they exist and the client accepts gzip.
  RewriteCond %{HTTP:Accept-encoding} gzip
  RewriteCond %{REQUEST_FILENAME}\.gz -s
  RewriteRule ^(.*)\.css $1\.css\.gz [QSA]

  # Serve gzip compressed JS files if they exist and the client accepts gzip.
  RewriteCond %{HTTP:Accept-encoding} gzip
```

```
RewriteCond %{REQUEST_FILENAME}\.gz -s  
RewriteRule ^(.*)\.js $1\.js\.gz [QSA]
```

Serve correct content types, and prevent mod_deflate double gzip.

```
RewriteRule \.css\.gz$ - [T=text/css,E=no-gzip:1]
```

```
RewriteRule \.js\.gz$ - [T=text/javascript,E=no-gzip:1]
```

```
<FilesMatch "(\\.js\\.gz|\\.css\\.gz)$">
```

Serve correct encoding type.

```
Header set Content-Encoding gzip
```

Force proxies to cache gzipped & non-gzipped css/js files separately.

```
Header append Vary Accept-Encoding
```

```
</FilesMatch>
```

```
</IfModule>
```

```
</IfModule>
```