

DirectoryIndex index.php

```
# Don't show directory listings for URLs which map to a directory.  
Options -Indexes -MultiViews
```

```
# Follow symbolic links in this directory.  
Options +FollowSymLinks
```

AddDefaultCharset UTF-8

```
<IfModule mod_php7.c>
```

```
    php_flag register_globals Off  
    php_flag magic_quotes_gpc Off  
    php_flag magic_quotes_runtime Off  
    php_flag magic_quotes_sybase Off  
    php_value session.auto_start 0  
    php_value output_buffering 0  
    php_value session.use_trans_sid 0  
    php_value memory_limit 128M  
    php_value max_execution_time 18000  
    php_flag suhosin.session.cryptua off  
    php_flag zend.zel_compatibility_mode Off  
    php_value short_open_tag On  
    php_value mbstring.func_overload 0  
    php_value default_charset UTF-8
```

```
</IfModule>
```

```
<IfModule mod_security.c>
```

```
# disable POST processing to not break multiple image upload  
    SecFilterEngine Off  
    SecFilterScanPOST Off
```

```
</IfModule>
```

```
<IfModule mod_ssl.c>
```

```
## make HTTPS env vars available for CGI mode  
    SSLOptions StdEnvVars
```

```
</IfModule>
```

```
<IfModule mod_expires.c>
```

```
# Add default Expires header  
    ExpiresDefault "max-age=3600"
```

```

    ExpiresDefault access plus 1 year
</IfModule>

<IfModule mod_headers.c>
<FilesMatch "\.(ico|pdf|flv)$">
    Header set Cache-Control "max-age=29030400, public"
</FilesMatch>

<FilesMatch "\.(jpg|jpeg|png|gif|swf)$">
    Header set Cache-Control "max-age=604800, public"
</FilesMatch>

<FilesMatch "\.(xml|txt|css|js)$">
    Header set Cache-Control "max-age=172800, proxy-revalidate"
</FilesMatch>

<FilesMatch "\.(html|html|php)$">
    Header set Cache-Control "max-age=60, private, proxy-revalidate"
</FilesMatch>
</IfModule>

<IfModule mod_rewrite.c>
    RewriteEngine On
    RewriteBase /

    RewriteCond %{QUERY_STRING} /\.\/\./ [NC,OR]
    RewriteCond %{QUERY_STRING} boot\.ini [NC,OR]
    RewriteCond %{QUERY_STRING} ftp\:/ [NC,OR]
    RewriteCond %{QUERY_STRING} http\:/ [NC,OR]
    RewriteCond %{QUERY_STRING} https\:/ [NC,OR]
    RewriteCond %{QUERY_STRING} (<|>|%)\.*script\.*(\\|) [NC,OR]
    RewriteCond %{QUERY_STRING} GLOBALS(=| \[| \]| \[0-9A-Z]{0,2}) [OR]
    RewriteCond %{QUERY_STRING} _REQUEST(=| \[| \]| \[0-9A-Z]{0,2})
    RewriteCond %{QUERY_STRING} ^.*(\\|\/| |<|>|'|"|;|\\?|\\*).* [NC,OR]
    RewriteCond %{QUERY_STRING} ^.*(%%22|%%27|%%3C|%%3E|%%5C|%%7B|%%7C).* [NC,OR]
    RewriteCond %{QUERY_STRING} ^.*(%%0|%%A|%%B|%%C|%%D|%%E|%%F|127\\.|0).* [NC,OR]
    RewriteCond %{QUERY_STRING} ^.*(global|sl|encode|config|localhost|loopback).* [NC,OR]
    RewriteCond %{QUERY_STRING} ^.*(request|select|insert|union|declare|drop).* [NC]

    RewriteRule ^(.*)$ - [F,L]
    RewriteRule .* - [E=HTTP_AUTHORIZATION:%{HTTP:Authorization}]

```

```
RewriteCond %{REQUEST_METHOD} ^TRACE[EK]
RewriteRule .* - [L,R=405]
```

```
RewriteRule
```

```
^(data|config|modules|packages|vendor|bootstrap.php|script.php|environment.php|.svn|.git|.t)
- [F,L]
```

```
# RewriteRule    ^(admin+)/?    admin.php    [NC,L]
# RewriteRule    ^(api+)/?      api.php     [NC,L]
```

```
# The following rule tells Apache that if the requested filename
# exists, simply serve it.
```

```
RewriteCond %{REQUEST_FILENAME} -s [OR]
RewriteCond %{REQUEST_FILENAME} -l [OR]
RewriteCond %{REQUEST_FILENAME} -d
RewriteRule ^.*$ - [NC,L]
```

```
# The following rewrites all other queries to index.php. The
# condition ensures that if you are using Apache aliases to do
# mass virtual hosting, the base path will be prepended to
# allow proper resolution of the index.php file; it will work
# in non-aliased environments as well, providing a safe, one-size
# fits all solution.
```

```
RewriteCond %{REQUEST_URI}::$1 ^(/.+)(.+)::\2$
RewriteRule ^(.*) - [E=BASE:%1]
RewriteRule ^(.*)$ %{ENV:BASE}index.php [NC,L]
```

```
</IfModule>
```