

```

# -----
# | Proper MIME types for all files |
# -----
<IfModule mod_mime.c>

# Audio
AddType audio/mp4          m4a f4a f4b
AddType audio/ogg          oga ogg opus

# Data interchange
AddType application/json   json map

# JavaScript
# Normalize to standard type (it's sniffed in IE anyways):
# http://tools.ietf.org/html/rfc4329#section-7.2
AddType application/javascript    js

# Video
AddType video/mp4          f4v f4p m4v mp4
AddType video/ogg          ogv
AddType video/webm         webm
AddType video/x-flv        flv

# Web fonts
AddType application/font-woff          woff
AddType application/vnd.ms-fontobject eot

# Browsers usually ignore the font MIME types and sniff the content,
# however, Chrome shows a warning if other MIME types are used for the
# following fonts.
AddType application/x-font-ttf         ttc ttf
AddType font/opentype                  otf

# Make SVGZ fonts work on iPad:
# https://twitter.com/FontSquirrel/status/14855840545
AddType image/svg+xml                 svgz
AddEncoding gzip                       svgz

# Other
AddType application/octet-stream       safariextz
AddType application/octet-stream       ...

```

```
AddType application/x-chrome-extension crx
AddType application/x-opera-extension oex
AddType application/x-web-app-manifest+json webapp
AddType application/x-xpinstall xpi
AddType application/xml atom rdf rss xml
AddType image/webp webp
AddType image/x-icon cur
AddType text/cache-manifest appcache manifest
AddType text/vtt vtt
AddType text/x-component htc
AddType text/x-vcard vcf
```

</IfModule>

```
# -----
# | Expires headers (for better cache control) |
# -----
```

```
# The following expires headers are set pretty far in the future. If you don't
# control versioning with filename-based cache busting, consider lowering the
# cache time for resources like CSS and JS to something like 1 week.
```

<IfModule mod\_expires.c>

```
ExpiresActive on
ExpiresDefault "access plus 1 second"
```

*# CSS*

```
ExpiresByType text/css "access plus 1 day"
```

*# Favicon (cannot be renamed!) and cursor images*

```
ExpiresByType image/x-icon "access plus 1 week"
```

*# JavaScript*

```
ExpiresByType application/javascript "access plus 1 day"
```

*# Manifest files*

```
ExpiresByType application/x-web-app-manifest+json "access plus 0 seconds"
```

```
ExpiresByType text/cache-manifest "access plus 0 seconds"
```

*# Media*

```
ExpiresByType image/jpeg "access plus 1 month"
```

```

ExpiresByType audio/ogg                "access plus 1 week"
ExpiresByType image/gif                "access plus 1 week"
ExpiresByType image/jpeg              "access plus 1 week"
ExpiresByType image/png                "access plus 1 week"
ExpiresByType video/mp4                "access plus 1 week"
ExpiresByType video/ogg                "access plus 1 week"
ExpiresByType video/webm               "access plus 1 week"

# Web feeds
ExpiresByType application/atom+xml     "access plus 1 hour"
ExpiresByType application/rss+xml      "access plus 1 hour"

# Web fonts
ExpiresByType application/font-woff    "access plus 1 month"
ExpiresByType application/vnd.ms-fontobject "access plus 1 month"
ExpiresByType application/x-font-ttf   "access plus 1 month"
ExpiresByType font/opentype            "access plus 1 month"
ExpiresByType image/svg+xml            "access plus 1 month"

</IfModule>

# BEGIN rewrites
<IfModule mod_rewrite.c>
    RewriteEngine On

    ## enable TREES
    ## Options iIndexes

    RewriteBase /

    ## don't touch /example URIs
    ## RewriteRule ^dox/ - [L,NC]

    RewriteRule ^index\.php$ - [L]

    # To externally redirect /dir/foo.* to /dir/foo
    # only redirect if original exists
    RewriteCond %{REQUEST_FILENAME} -f
    RewriteCond %{THE_REQUEST} ^[A-Z]{3,}\s(?:[^.]+)\. (php|html|htm) [NC]
    RewriteRule ^ %1 [R,L]

```

*# To internally forward /dir/foo to /dir/foo.???*

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME}.phtml -f
RewriteRule ^(.)$ $1.phtml [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME}.php -f
RewriteRule ^([^.]+)$ $1.php [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME}.html -f
RewriteRule ^([^.]+)$ $1.html [L]
```

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME}.htm -f
RewriteRule ^([^.]+)$ $1.htm [L]
```

*# Internally redirect everything else to index*

```
RewriteCond %{REQUEST_FILENAME} !-f
RewriteCond %{REQUEST_FILENAME} !-d
RewriteRule . index.php [L]
```

</IfModule>

*# END rewrites*