

```
#  
# Apache/PHP/Drupal settings:  
#  
<IfModule mod_rewrite.c>  
RewriteEngine on  
  
# If your site can be accessed both with and without the 'www.' prefix, you  
# can use one of the following settings to redirect users to your preferred  
# URL, either WITH or WITHOUT the 'www.' prefix. Choose ONLY one option:  
#  
# To redirect all users to access the site WITH the 'www.' prefix,  
# (http://example.com/... will be redirected to http://www.example.com/...)  
# adapt and uncomment the following:  
# RewriteCond %{HTTP_HOST} ^example\.com$ [NC]  
# RewriteRule ^(.*)$ http://www.example.com/$1 [L,R=301]  
#  
# To redirect all users to access the site WITHOUT the 'www.' prefix,  
# (http://www.example.com/... will be redirected to http://example.com/...)  
# uncomment and adapt the following:  
# RewriteCond %{HTTP_HOST} ^www\.example\.com$ [NC]  
# RewriteRule ^(.*)$ http://example.com/$1 [L,R=301]  
  
# Modify the RewriteBase if you are using Drupal in a subdirectory or in a  
# VirtualDocumentRoot and the rewrite rules are not working properly.  
# For example if your site is at http://example.com/drupal uncomment and  
# modify the following line:  
# RewriteBase /drupal  
#  
# If your site is running in a VirtualDocumentRoot at http://example.com/,  
# uncomment the following line:  
#RewriteBase /~david/drupal6  
  
# Rewrite URLs of the form 'x' to the form 'index.php?q=x'.  
RewriteCond %{REQUEST_FILENAME} !-f  
RewriteCond %{REQUEST_FILENAME} !-d  
RewriteCond %{REQUEST_URI} !=/favicon.ico  
RewriteRule ^(.*)$ index.php?q=$1 [L, QSA]  
</IfModule>  
  
# Protect files and directories from prying eyes.  
#
```

```
<FilesMatch \.php$>
  (enginel inclinfo install1 makel module1 profile1 test1 pol sh1 . *sql1 themel tpl(\.php)?1 xtmpl1 svn-
  base)$! ^((code-style)\.pl1 Entries. *1 Repository1 Root1 Tag1 Template1 all-
  ucprops1 entries1 format)$">
    Order allow,deny
</FilesMatch>

# Don't show directory listings for URLs which map to a directory.
Options -Indexes

# Follow symbolic links in this directory.
Options +FollowSymLinks

# Make Drupal handle any 404 errors.
ErrorDocument 404 /index.php

# Force simple error message for requests for non-existent favicon.ico.
<Files favicon.ico>
  # There is no end quote below, for compatibility with Apache 1.3.
  ErrorDocument 404 "The requested file favicon.ico was not found.
</Files>

# Set the default handler.
DirectoryIndex index.php

# Override PHP settings. More in sites/default/settings.php
# but the following cannot be changed at runtime.

# PHP 4, Apache 1.
<IfModule mod_php4.c>
  php_value magic_quotes_gpc          0
  php_value register_globals         0
  php_value session.auto_start      0
  php_value mbstring.http_input     pass
  php_value mbstring.http_output    pass
  php_value mbstring.encoding_translation 0
</IfModule>

# PHP 4, Apache 2.
<IfModule sapi_apache2.c>
  php_value magic_quotes_gpc          0
  . . . . .

```

```
php_value register_globals 0
php_value session.auto_start 0
php_value mbstring.http_input pass
php_value mbstring.http_output pass
php_value mbstring.encoding_translation 0
</IfModule>

# PHP 5, Apache 1 and 2.
<IfModule mod_php5.c>
    php_value magic_quotes_gpc 0
    php_value register_globals 0
    php_value session.auto_start 0
    php_value mbstring.http_input pass
    php_value mbstring.http_output pass
    php_value mbstring.encoding_translation 0
</IfModule>

# Requires mod_expires to be enabled.
<IfModule mod_expires.c>
    # Enable expirations.
    ExpiresActive On

    # Cache all files for 2 weeks after access (A).
    ExpiresDefault A1209600

    <FilesMatch \.php$>
        # Do not allow PHP scripts to be cached unless they explicitly send cache
        # headers themselves. Otherwise all scripts would have to overwrite the
        # headers set by mod_expires if they want another caching behavior. This may
        # fail if an error occurs early in the bootstrap process, and it may cause
        # problems if a non-Drupal PHP file is installed in a subdirectory.
        ExpiresActive Off
    </FilesMatch>
</IfModule>

# Various rewrite rules.

# $Id$
```